

FieldFox Handheld Analyzers

4/6.5/9/14/18/26.5/32/44/50 GHz

| | | | |
|--------|--------|--------|--------|
| N9913B | N9950B | N9933B | N9960B |
| N9914B | N9951B | N9934B | N9961B |
| N9915B | N9952B | N9935B | N9962B |
| N9916B | | N9936B | |
| N9917B | | N9937B | |
| N9918B | | N9938B | |



Table of Contents

| | |
|--|-----|
| Definitions..... | 3 |
| Cable and Antenna Analyzer and Vector Network Analyzer | 4 |
| TDR Cable Measurements (Option 215) | 34 |
| VNA Time Domain (Option 010) | 35 |
| Mixed-Mode S-Parameters (Option 212) | 35 |
| Vector Voltmeter (VVM) (Option 308) | 36 |
| Spectrum Analyzer (Option 233 on Combination Analyzers) | 37 |
| Tracking Generator or Independent Source | 52 |
| Real-Time Spectrum Analyzer (RTSA) (Option 350) | 55 |
| I/Q Analyzer (IQA) (Option 351) | 56 |
| Noise Figure (NF) (Option 356) | 64 |
| Spectrum Analyzer IF Output..... | 70 |
| Preamplifier (Option 235) | 71 |
| Interference Analyzer and Spectrogram (Option 236) | 71 |
| Channel Scanner (Option 312) | 71 |
| 89600 VSA Software..... | 72 |
| Over-the-Air (OTA) LTE FDD/TDD (Option 370/371) | 73 |
| Over-the-Air (OTA) 5G TF (Option 377) | 74 |
| Over-the-Air (OTA) 5G NR (Option 378)..... | 76 |
| Indoor and Outdoor Mapping (Option 352) | 79 |
| EMF Measurements (Option 358)..... | 80 |
| AM/FM Analog demodulation, Tune and Listen (Option 355)..... | 81 |
| Spectrum Analyzer Time Gating (Option 238) | 82 |
| Reflection Measurements (RL, VSWR) (Option 320, applicable to SA only models)..... | 82 |
| Extended Range Transmission Analysis (ERTA) (Option 209) | 83 |
| Built-in Power Meter (Option 310)..... | 89 |
| External USB Power Sensor Support (Option 302) | 90 |
| Pulse Measurements (Option 330) | 91 |
| USB Power Sensor Measurements versus Frequency (Option 208) | 91 |
| Built-In GNSS (GPS+) Receiver (Option 307) | 93 |
| DC Bias Variable-Voltage Source (Option 309)..... | 93 |
| Remote Control Capability (Option 030) | 94 |
| General Information | 94 |
| FieldFox Physical Dimensions | 98 |
| Carry Precision With You | 101 |

This data sheet provides the specified and typical performance of the FieldFox family of portable analyzers. This data sheet should be used in conjunction with the technical overviews and configuration guide, for a complete description of the analyzers.

The specifications and measurement capabilities listed in this document require certain options on the FieldFox analyzer. Refer to the FieldFox Configuration Guide to obtain option information. The configuration guide is the main resource for option/measurement capability information (<http://literature.cdn.keysight.com/litweb/pdf/5992-3701EN.pdf>).

Definitions

Specification (spec)

Specifications include guardbands to account for the expected statistical performance distribution, measurement uncertainties, and changes in performance due to environmental conditions. Specifications are warranted performance. FieldFox must be within its calibration cycle. No warm-up required for the specifications listed on pages 37 through 93.

Typical

Describes additional product performance information not covered by the product warranty. It is performance beyond specifications that 80% of the units exhibit with a 90% confidence level over the temperature range 23 ± 5 °C, unless otherwise noted. Typical performance does not include measurement uncertainty. FieldFox must be within its calibration cycle.

Nominal

A general, descriptive term or design parameter. It is not tested, and not covered by the product warranty. FieldFox must be within its calibration cycle.

Cable and Antenna Analyzer and Vector Network Analyzer

The performance listed in this section applies to the cable and antenna analyzer (referred to as CAT) and vector network analyzer (VNA) capabilities available in the following models:

FieldFox RF & microwave (combination) analyzers: N9913B, N9914B, N9915B, N9916B, N9917B, N9918B, N9950B, N9951B, N9952B

NOTE: Combination analyzers = Cable and antenna tester (CAT) + Vector network analyzer (VNA) + Spectrum analyzer (SA)

See [FieldFox Configuration Guide](#) for option information. Many capabilities listed in this Data Sheet require options.

Frequency specifications

| | Models | Frequency range |
|--|---|--------------------------------------|
| N991xB | N9913B | 30 kHz to 4 GHz |
| | N9914B | 30 kHz to 6.5 GHz |
| | N9915B | 30 kHz to 9 GHz |
| | N9916B | 30 kHz to 14 GHz |
| | N9917B | 30 kHz to 18 GHz |
| | N9918B | 30 kHz to 26.5 GHz |
| N995xB | N9950B | 300 kHz to 32 GHz |
| | N9951B | 300 kHz to 44 GHz |
| | N9952B | 300 kHz to 50 GHz |
| Frequency reference, -10 to 55 °C | | |
| Accuracy | ± 0.9 ppm (spec) + aging | |
| | ± 0.5 ppm (typical) + aging | |
| Accuracy, when locked to GPS | ± 0.010 ppm (spec) | |
| Accuracy, when GPS antenna is disconnected | ± 0.4 ppm (nominal) ¹ | |
| Aging Rate | ± 1 ppm/yr for 20 years (spec), will not exceed ± 3.5 ppm | |
| Frequency resolution | Spec (Hz) | |
| 30 kHz to 1.91211 GHz | 0.67 | N991xB, or N995xB (starting 300 kHz) |
| ≥ 1.91211 to 3.82461 GHz | 1.34 | N991xB, or N995xB |
| ≥ 3.82461 to 7.64961 GHz | 2.68 | N991xB, or N995xB |
| ≥ 7.64961 to 15.29961 GHz | 5.36 | N991xB, or N995xB |
| ≥ 15.29961 to 26.5 GHz | 10.73 | N991xB, or N995xB |
| ≥ 26.5 to 45.8 GHz | 16.09 | N995xB |
| ≥ 45.8 to 50 GHz | 32.19 | N995xB |
| Data points or resolution | | |
| 101, 201, 401, 601, 801, 1001, 1601, 4001, 10,001 | | |
| Arbitrary number of points settable through front panel and SCPI | | |

¹ The maximum drift expected in the frequency reference applicable when the ambient temperature changes ±5°C from the temperature when the GPS signal was last connected.

| | |
|---------------------------------|---|
| IF bandwidth¹ | |
| | 3 Hz, 10 Hz, 30 Hz, 100 Hz, 300 Hz, 1 kHz, 3 kHz, 10 kHz, 30 kHz, 100 kHz |
| System impedance | |
| | 50 Ω (nominal), 75 Ω with appropriate adapter and calibration kit |

¹ VNA mode only. Recommend using averaging in CAT mode.

Cable and Antenna Analyzer and Vector Network Analyzer (continued)

Test port output specifications

High power in the N991xB and N995xB refers to the analyzer's target output power level when the *Power Setting* is *High*. Examples:

- N991xB: For a 5 to 10 GHz frequency sweep, the analyzer achieves a 7 dBm power level across the band.
- N995xB: For an 18 to 26.5 GHz frequency sweep, the analyzer achieves a 5 dBm power level across the band.

Low power level for N991xB and N995xB analyzers flattens at -50 dBm across the entire frequency band and is the analyzer's output when the *Power Setting* is *Low*.

Max leveled power in the N991xB and N995xB refers to the maximum leveled (flattened) power achieved across the designated frequency range. Examples:

- N991xB: For a 1 to 10 GHz frequency sweep with the analyzer configured to measure all four S-parameters, needing both ports 1 and 2, the maximum power the analyzer can be set to is 5 dBm.
- N995xB: For an 18 to 26.5 GHz frequency sweep with the analyzer configured to measure all four S-parameters, needing both ports 1 and 2, the maximum power the analyzer can be set to is 4 dBm.

| Test port output power (dBm), high power | Typical | Typical |
|--|---------|---------|
| N991xB | Port 1 | Port 2 |
| 30 kHz to 500 kHz | -4 | -2 |
| > 500 kHz to 10 MHz | 0 | 0 |
| > 10 MHz to 1 GHz | 9 | 8 |
| > 1 to 5 GHz | 8 | 7 |
| > 5 to 10 GHz | 7 | 7 |
| > 10 to 18 GHz | 6 | 5 |
| > 18 to 26.5 GHz | 3 | 2 |
| N995xB | Port 1 | Port 2 |
| 300 kHz to 1 MHz | -5 | -4 |
| > 1 MHz to 10 MHz | -1 | -1 |
| > 10 MHz to 6 GHz | 5 | 5 |
| > 6 to 18 GHz | 7 | 6 |
| > 18 to 26.5 GHz | 5 | 5 |
| > 26.5 to 32 GHz | 4 | 2 |
| > 32 to 40 GHz | 2 | 0 |
| > 40 to 44 GHz | -3 | -2 |
| > 44 to 50 GHz | -9 | -8 |

| Test port output power (dBm), low power | | Typical Port 1 or Port 2 | Nominal Port 1 or Port 2 |
|---|--------------------|----------------------------------|-----------------------------|
| N991xB | 30 kHz to 26.5 GHz | -50 dBm (flattened) ± 0.5 dB | — |
| N995xB | 300 kHz to 50 GHz | -50 dBm (flattened) ± 0.5 dB | — |
| Max leveled output power (dBm) | | Nominal Port 1 | Nominal Port 2 |
| N991xB | | Port 1 | Port 2 |
| > 10 MHz to 1 GHz | | 6 | 6 |
| > 1 to 10 GHz | | 6 | 5 |
| > 10 to 18 GHz | | 4 | 3 |
| > 18 to 26.5 GHz | | 2 | 0 |
| N995xB | | Port 1 | Port 2 |
| > 300 kHz to 1 MHz | | -1 | -1 |
| > 1 MHz to 10 MHz | | 5 | 4 |
| > 10 MHz to 6 GHz | | 8 | 8 |
| > 6 to 18 GHz | | 7 | 5 |
| > 18 to 26.5 GHz | | 5 | 4 |
| > 26.5 to 32 GHz | | 4 | 2 |
| > 32 to 44 GHz | | -5 | -3 |
| > 44 to 50 GHz | | -13 | -10 |

| Output power range | |
|--|---|
| CAT | High, low, and manual. Default (preset) power is manual, -15 dBm. Manual power is flattened. |
| VNA | High, low, and manual. Default (preset) power is manual, -15 dBm. Manual power is flattened. |
| Power step size | |
| Power settable in 1 dB steps across power range. Flat power, in 1 dB steps, is available across the whole frequency span, nominal. | |

Cable and Antenna Analyzer and Vector Network Analyzer (continued)

Test port output specifications (continued)

| Power level accuracy ⁴ N991xB ¹ | Typical Port 1 or Port 2 at -15 dBm |
|--|--|
| 30 kHz to 10 MHz | ± 0.7 dB |
| > 10 MHz to 26.5 GHz | ± 0.5 dB |
| Power level accuracy ⁴ N995xB ¹ | Port 1 or Port 2 at -15 dBm |
| 300 kHz to 50 GHz | ± 0.5 dB |
| Power level linearity N991xB | Nominal Port 1 or Port 2, -50 dBm ≤ P < max leveled power |
| > 10 MHz to 26.5 GHz | ± 0.5 dB |
| Power level linearity N995xB | Port 1 or Port 2, -50 dBm ≤ P < max leveled power |
| > 300 kHz to 50 GHz | ± 0.5 dB |

System performance specifications

| System dynamic range ^{2,3} (dB), high power, 300 Hz IFBW, 100-point average, Port 1 or Port 2 (-10 to 55°C) | | | | |
|--|----------|---------------|----------|---------------|
| N991xB | S12 Spec | S12 Typical | S21 Spec | S21 Typical |
| 30 kHz to 1 MHz | -- | 114 (nominal) | -- | 113 (nominal) |
| > 1 to 6.34 MHz | 105 | 114 | 104 | 111 |
| > 6.34 MHz to 16 GHz | 108 | 114 | 106 | 116 |
| > 16 to 18 GHz | 109 | 117 | 104 | 114 |
| > 18 to 24 GHz | 105 | 115 | 102 | 113 |
| > 24 to 26.5 GHz | 102 | 113 | 97 | 109 |
| N995xB | S12 Spec | S12 Typical | S21 Spec | S21 Typical |
| 300 kHz to 1 MHz | -- | 105 (nominal) | -- | 103 (nominal) |
| > 1 to 10 MHz | 101 | 113 | 100 | 110 |
| > 10 MHz to 6 GHz | 110 | 121 | 108 | 118 |
| > 6 to 16 GHz | 107 | 116 | 106 | 117 |
| > 16 to 18 GHz | 109 | 118 | 105 | 117 |
| > 18 to 24 GHz | 107 | 117 | 105 | 115 |
| > 24 to 26.5 GHz | 104 | 115 | 103 | 113 |
| > 26.5 to 32 GHz | 99 | 111 | 100 | 111 |
| > 32 to 39 GHz | 93 | 107 | 98 | 109 |
| > 39 to 46 GHz | 90 | 101 | 87 | 100 |
| > 46 to 50 GHz | 86 | 96 | 81 | 94 |

¹ N995xB power levels are calibrated based on PNA-X's tuned receiver for the entire frequency range.

² System dynamic range is measured in the factory with loads on the test ports after a thru normalization.

³ For CAT mode, "Insertion loss (2-port)", decrease listed dynamic range specifications by 20 dB, as CAT mode IFBW is fixed at 10 kHz. Can obtain full dynamic range by using S21 measurement in VNA mode with 100 Hz IFBW.

| Measurement stability over temperature | | Nominal | |
|--|--------------------|-------------------|----------------|
| | Frequency | Magnitude (dB/°C) | Phase (deg/°C) |
| N991xB | ≤ 6 GHz | ± 0.010 | ± 0.15 |
| | > 6 GHz to 15 GHz | ± 0.025 | ± 0.5 |
| | > 15 to 26.5 GHz | ± 0.035 | ± 0.5 |
| N995xB | 300 kHz to 6 GHz | ± 0.010 | ± 0.15 |
| | 6 GHz to 15 GHz | ± 0.025 | ± 0.5 |
| | 15 GHz to 26.5 GHz | ± 0.035 | ± 0.5 |
| | 26.5 GHz to 40 GHz | ± 0.06 | ± 0.6 |
| | 40 GHz to 50 GHz | ± 0.06 | ± 1.5 |

| Measurement speed (Sweep time) | | |
|---|------------|------------|
| CAT | N991xB | N995xB |
| Return loss, 30 kHz to 26.5 GHz, 1-port cal, 1001 points | 409 μs /pt | - |
| Return loss, 300 kHz to 50 GHz, 1-port cal 1001 points | - | 457 μs /pt |
| Distance-to-fault, 100-meter cable, 1-port cal, 1001 points | 470 μs /pt | 506 μs /pt |
| VNA | N991xB | N995xB |
| S11 and S21, 30 kHz to 26.5 GHz, enhanced response cal, 100 kHz IF bandwidth, 1001 points | 171 μs /pt | - |
| S11 and S21, 300 kHz to 50 GHz, enhanced response cal, 100 kHz IF bandwidth, 1001 points | - | 196 μs /pt |

Cable and Antenna Analyzer and Vector Network Analyzer (continued)

Test port input specifications

| Trace noise ¹ , high power, 300 Hz IFBW, Port 1 or Port 2 | | Spec (-10 to 55°C) | |
|--|----------------------------------|--------------------|-----------------|
| | Frequency | Magnitude (dB rms) | Phase (deg rms) |
| N991xB | 30 kHz to 100 kHz | 0.0008 (nominal) | 0.007 (nominal) |
| | ≥ 100 kHz to 5 GHz | 0.0010 | 0.005 |
| | > 5 to 15 GHz | 0.0014 | 0.014 |
| | > 15 to 26.5 GHz | 0.0020 | 0.027 |
| N995xB | ≥ 300 kHz to 34 MHz ² | 0.0010 | 0.0070 |
| | > 34 MHz to 5 GHz | 0.0010 | 0.0070 |
| | > 5 to 15 GHz | 0.0014 | 0.0140 |
| | > 15 to 26.5 GHz | 0.0020 | 0.0270 |
| | > 26.5 to 32 GHz | 0.0023 | 0.0320 |
| | > 32 to 44 GHz | 0.0030 | 0.0500 |
| | > 44 to 50 GHz | 0.0040 | 0.1200 |

| Receiver compression | | Typical |
|----------------------|---------------------|-----------------------------|
| | Frequency | Port 1 or Port 2 |
| N991xB | 250 kHz to 2 GHz | +8 dBm, 0.20 dB compression |
| | > 2 to 5 GHz | +8 dBm, 0.15 dB compression |
| | > 5 to 26.5 GHz | +8 dBm, 0.10 dB compression |
| N995xB | 300 kHz to 2 MHz | +5 dBm, 0.20 dB compression |
| | > 2 MHz to 26.5 GHz | +5 dBm, 0.10 dB compression |
| | > 26.5 to 50 GHz | +5 dBm, 0.15 dB compression |

| Maximum input level | | Port 1 or Port 2 |
|---|--------------------|------------------|
| | Average CW power | DC |
| N991xB | +27 dBm, 0.5 watts | ± 50 VDC |
| N995xB | +25 dBm, 0.5 watts | ± 40 VDC |
| Immunity to interfering signals (Nominal) | | |
| | N991xB | N995xB |
| On carrier frequency | +10 dBm | +9 dBm |
| Offset from carrier frequency | > 1 MHz | +12 dBm |
| | > 10 MHz | +80 dBm |

¹ For CAT mode, increase trace noise by a factor of 5.7, as CAT mode IFBW is fixed at 10 kHz. Can use averaging in CAT mode to reduce trace noise or use VNA mode with 300 Hz IFBW.

² Excludes multiples of 65 kHz, and 7.792198 MHz, 8.190585 MHz, and 8.954400 MHz.

CAT and VNA measurements

| CAT mode | |
|----------------------------------|--|
| CAT measurements | Distance-to-fault (dB) Return loss (dB) Return loss & DTF (dB) VSWR Distance-to-fault (VSWR) Cable loss (1-port) Insertion loss (2-port) (requires option 211) Distance-to-fault (Lin) TDR (Lin rho) (requires option 215) TDR (ohm) (requires option 215) TDR & DTF (requires option 215) |
| Distance-to-fault (DTF) settings | |
| Frequency/distance | Start distance, stop distance |
| Sweep time | Units: meters or feet (Can also be set as Preferences) |
| Frequency mode | Bandpass, lowpass |
| CAT mode averaging | Set sweep time in seconds |

Cable and Antenna Analyzer and Vector Network Analyzer (continued)

CAT and VNA measurements (continued)

| CAT mode (continued) | |
|-----------------------------------|--|
| Distance-to-fault | Available in CAT mode. Standard on N991xB analyzers. Range = velocity factor x speed of light x (number of points -1) / frequency span x 2; Number of points auto coupled according to start and stop distance entered. Resolution = range / (number of points -1) Transform modes: Bandpass, low-pass Window types: Maximum, medium, and minimum Alias free range indicator: On/Off Dispersion compensation for waveguide: Yes |
| Return loss, log magnitude | -500 to 500 dB |
| Log magnitude resolution | 0.01 dB |
| VSWR | 1.01 to 1000 |
| VSWR resolution | 0.01 |
| VNA mode | |
| VNA Transmission/Reflection (T/R) | S11, S21 magnitude and phase (requires option 210) |
| VNA S-parameters | S11, S21, S22, S12 magnitude and phase (requires options 210 and 211) |
| Number of traces | Four traces available: Tr1, Tr2, Tr3, Tr4 |
| Display formats | Single-trace Dual-trace split (each trace on separate graticule) Dual-trace overlay (both traces on one graticule) Three-trace split (each trace on separate graticule) Three-trace overlay (all three traces on one graticule) Quad-trace split (each trace on separate graticule) Quad-trace overlay (all four traces on one graticule) |
| VNA trace formats | Log magnitude, linear magnitude, VSWR, phase, Smith chart, polar, group delay, unwrapped phase, real impedance, imaginary impedance, Z magnitude |
| Frequency settings | Start, stop, center, span |
| Frequency sweep type | Linear |
| Sweep type trigger | Continuous, single |
| Sweep trigger source | Internal, external, point (point trigger applies to 1-port cal only) |
| Sweep trigger slope | Positive, negative |
| Sweep trigger delay | 0 to 10 seconds |
| Averaging | Sweep: 2 to 1000; Point: 2 to 500 |
| Smoothing | Computes the moving average of adjacent data points. Smoothing aperture defines the trace width (number of points) to be averaged. Minimum aperture: 0.05% of frequency span Maximum aperture: 25% of frequency span |

Cable and Antenna Analyzer and Vector Network Analyzer (continued)

CAT and VNA measurements (continued)

| VNA mode (continued) | |
|--------------------------|--|
| Scale | Autoscale, scale, reference level, reference position Autoscale: Automatically selects scale resolution and reference value to center the trace. Autoscale all: Scales all visible traces. |
| S11, log magnitude | -500 to 500 dB |
| Log magnitude resolution | 0.01 dB |
| VSWR | 1.01 to 1000 |
| VSWR resolution | 0.01 |
| Phase | -180 to +180 degrees (unwrapped phase can show larger values) |
| Phase resolution | 0.01 degrees |
| Phase offset | -360 to +360 degrees |
| Magnitude offset | -100 to +100 dB |
| Trace math | Vector division or subtraction of current linear measurement values and memory data |
| Port extension | For both port 1 and port 2, delay settings. Port extensions apply to all measurements. |
| Marker formats | Default marker format is the trace format. Other formats: R + jX Z magnitude Phase Real Imaginary Mag & Phase dB Angle |
| General CAT / VNA modes | |
| Marker functions | Peak, Next Peak, Peak Left, Peak Right, Mkr→Center, Mkr→Delay, Min Search, Peak Excursion, Peak Threshold, Target, Bandwidth (BW, Q, Loss), Tracking CAT mode only: Tracking 3 peaks (CAT mode), Marker→Start distance, Marker→Stop distance |
| Marker table | On/Off |
| Marker types | Normal, delta, data trace and memory trace markers |
| Marker coupling | On/Off (coupling between traces) |
| Frequency blanking | Security level: none, high. If high, all frequency information is blanked out. An instrument preset is required to re-enable the frequency information. |
| Display data | Display data, memory, data and memory, or data math |
| Trace math | One memory trace per data trace. |

Cable and Antenna Analyzer and Vector Network Analyzer (continued)

CAT and VNA mode Calibrations

FieldFox analyzers offer three tiers of calibrations, thus providing users with different levels of calibration effort and accuracy.

CalReady

CalReady is the most basic calibration and is sufficient for a quick pass/fail or go/no go verification. Every FieldFox is calibrated at the factory, at test ports 1 and 2, at room temperature. CalReady can be applied either as an “enhanced response CalReady” or a “2-port CalReady.” The default setting is 2-port CalReady, so correction is applied to both ports. A user preference allows user to change the CalReady methodology to enhanced response CalReady.

A 30-minute warm-up period is recommended for a quick test. A 60-minute warm-up is necessary for more stringent test requirements.

If CalReady is the basis for most measurements, the annual cal cycle must be followed, as the CalReady calibration will be updated during the annual cal cycle.

Cable and Antenna Analyzer and Vector Network Analyzer (continued)

Standard calibrations

Standard calibrations are the most accurate calibrations offered in FieldFox. FieldFox's calibration engine is based on Keysight's flagship PNA calibration engine, and as such, offers many of the standard calibrations. FieldFox supports both coaxial and waveguide calibrations. The table below lists the commonly used calibrations.

Keysight recommends a 30-minute warm-up period for standard calibrations. For ultimate in stability and accuracy, a 90-minute warm-up period is necessary.

| | |
|---|--|
| Frequency response Open response Short response Thru response With and without isolation | Simultaneous magnitude and phase correction of frequency response errors for either reflection or transmission measurements. Isolation corrects for crosstalk errors. |
| 1-port OSL (Port 1) 1-port OSL (Port 2) | Open, short, and load Traditional 1-port calibration for reflection measurements. Corrects for directivity, source match, and frequency response errors. |
| SSL (for waveguide) | For waveguide calibrations, depending on the calibration kit definition, this is presented as a short, offset short and load calibration. |
| Enhanced response (also known as one-path, two-port) Forward enhanced response Reverse enhanced response | Corrects for frequency response and source match. Partial correction for load match for low-loss reciprocal devices. |
| QSOLT (2-port) | QSOLT or Quick short-open-load-thru is FieldFox's default recommended calibration for insertable devices. Full 12-term error correction. Requires fewer connections, compared to traditional SOLT (4 compared to 7). Corrects for directivity, source match, reflection frequency response, load match, and transmission frequency response. |
| Full 2-port (unknown thru calibration) | FieldFox's default recommended calibration for non-insertable devices. Full 12-term error correction. Beneficial for characterizing non-insertable devices such as Type-N to 3.5 mm, or female-female devices. Corrects for directivity, source match, reflection frequency response, load match, and transmission frequency response. |
| TRL | TRL or thru-reflect-line compensates for directivity, reflection, and transmission frequency response in both the forward and reverse directions. |

** Note: FieldFox does not offer the traditional SOLT calibration. Instead, it offers the more accurate Full 2-port (unknown thru), and QSOLT.

ECal

FieldFox supports all Keysight USB ECal modules, both standard and value-line ECals.

FieldFox's Guided Calibration Wizard

FieldFox's calibration wizard recommends a calibration type and calibration kit based on selected parameters and connector types. Alternatively, users can select their own calibration type and calibration kit. FieldFox's calibration wizard ensures a valid calibration selection.

Cable and Antenna Analyzer and Vector Network Analyzer (continued)

Interpolation Error Correction

With any type of accuracy enhancement applied, interpolated mode recalculates the error coefficients when the test frequencies are changed. The number of points can be increased or decreased, and the start/stop frequencies can be changed, but the resulting frequency span must be a subset of the original calibration frequency span.

Connectors

The FieldFox firmware supports the following connector types by default. Add other connector types with a calibration kit that contains the connector type.

| Coaxial | Waveguide | |
|---------------|-----------|--------|
| Type-N 50 ohm | WR-10 | WR-90 |
| Type-N 75 ohm | WR-15 | WR-112 |
| 7/16 | WR-22 | WR-137 |
| TNC | WR-28 | WR-187 |
| Type-F | WR-42 | WR-284 |
| 7 mm | WR-62 | WR-650 |
| 3.5 mm | WR-75 | |
| 2.4 mm | | |
| 2.92 mm | | |

FieldFox S-parameter measurement uncertainties

The configurations listed below include measurement uncertainties based on ISO GUM methodology calculations.

| FieldFox model | Calibration Kit | Calibration Type | DUT Connector | Uncertainty |
|----------------|------------------|-------------------------|---------------|-------------|
| N991xB, N995xB | 85518A or 85519A | Full 2-port calibration | Type-N | Spec |
| N991xB, N995xB | 85054D | Full 2-port calibration | Type-N | Spec |
| N991xB, N995xB | 85520A or 85521A | Full 2-port calibration | 3.5 mm | Spec |
| N991xB, N995xB | 85052D | Full 2-port calibration | 3.5 mm | Spec |
| N991xB, N995xB | N7554A | Full 2-port calibration | Type-N | Spec |
| N991xB, N995xB | N7555A | Full 2-port calibration | 3.5 mm | Spec |
| N991xB, N995xB | N4690D | Full 2-port calibration | Type-N | Spec |
| N991xB, N995xB | N4691D | Full 2-port calibration | 3.5 mm | Spec |
| N995xB | 85563A or 85564A | Full 2-port calibration | 2.4 mm | Spec |
| N995xB | 85056D | Full 2-port calibration | 2.4 mm | Spec |
| N995xB | N4693D ECal | Full 2-port calibration | 2.4 mm | Spec |
| N995xB | 85561A or 85562A | Full 2-port calibration | 2.92 mm | Spec |

Corrected Measurement Uncertainty (continued)



N9913/4/5/6/7/8B, 85518A or 85519A, Full 2-port Cal, DUT: Type-N, Spec

Corrected performance table calculated using uncertainties with a coverage factor of 2.



| Corrected performance (dB) | 0.2 to 500 MHz | 0.5 to 6 GHz | 6 to 9 GHz | 9 to 18 GHz |
|------------------------------------|----------------|--------------|-------------|-------------|
| Directivity | 40 | 39 | 32 | 29 |
| Source match | 38 | 31 | 29 | 26 |
| Load match ¹ | 38 | 33 | 28 | 26 |
| Reflection tracking | ± 0.00011 | ± 0.033 | ± 0.014 | ± 0.043 |
| Transmission tracking ¹ | ± 0.062 | ± 0.17 | ± 0.29 | ± 0.32 |

Uncertainty plots: power level of -15 dBm, 10 Hz IF bandwidth, no averaging, battery saver off, and 60-minute warm-up time. Includes uncertainties due to drift, noise, compression, and dynamic accuracy. Coverage factor of 1 applied to uncertainties, for ease of comparison with other industry handheld analyzers.

Transmission uncertainty (S21, S12)



Reflection uncertainty (S11, S22)



¹ Load match and transmission tracking are typical values.

Corrected Measurement Uncertainty (continued)



N9913/4/5/6/7/8B, 85054D, Full 2-port Cal, DUT: Type-N, Spec

Corrected performance table calculated using uncertainties with a coverage factor of 2.



| Corrected performance (dB) | 0.2 to 500 MHz | 0.5 to 2 GHz | 2 to 8 GHz | 8 to 18 GHz |
|------------------------------------|----------------|--------------|--------------|-------------|
| Directivity | 37 | 37 | 33 | 31 |
| Source match | 37 | 37 | 33 | 30 |
| Load match ¹ | 37 | 37 | 33 | 30 |
| Reflection tracking | ± 0.00068 | ± 0.0019 | ± 0.0053 | ± 0.026 |
| Transmission tracking ¹ | ± 0.0057 | ± 0.017 | ± 0.053 | ± 0.12 |

Uncertainty plots: power level of -15 dBm, 10 Hz IF bandwidth, no averaging, battery saver off, and 60-minute warm-up time. Includes uncertainties due to drift, noise, compression, and dynamic accuracy. Coverage factor of 1 applied to uncertainties, for ease of comparison with other industry handheld analyzers.

Transmission uncertainty (S21, S12)



Reflection uncertainty (S11, S22)



¹ Load match and transmission tracking are typical values.

Corrected Measurement Uncertainty (continued)



N9913/4/5/6/7/8B, 85520A or 85521A, Full 2-port Cal, DUT: 3.5 mm, Spec

Corrected performance table calculated using uncertainties with a coverage factor of 2.



| Corrected performance (dB) | 0.2 to 500 MHz | 0.5 to 5 GHz | 5 to 15 GHz | 15 to 26.5 GHz |
|------------------------------------|----------------|--------------|-------------|----------------|
| Directivity | 41 | 39 | 33 | 29 |
| Source match | 34 | 33 | 29 | 25 |
| Load match ¹ | 35 | 32 | 28 | 24 |
| Reflection tracking | ± 0.0078 | ± 0.022 | ± 0.024 | ± 0.060 |
| Transmission tracking ¹ | ± 0.13 | ± 0.18 | ± 0.29 | ± 0.45 |

Uncertainty plots: power level of -15 dBm, 10 Hz IF bandwidth, no averaging, battery saver off, and 60-minute warm-up time. Includes uncertainties due to drift, noise, compression, and dynamic accuracy. Coverage factor of 1 applied to uncertainties, for ease of comparison with other industry handheld analyzers.

Transmission uncertainty (S21, S12)



Reflection uncertainty (S11, S22)



¹ Load match and transmission tracking are typical values.

Corrected Measurement Uncertainty (continued)



N9913/4/5/6/7/8B, 85052D, Full 2-port Cal, DUT: 3.5 mm, Spec

Corrected performance table calculated using uncertainties with a coverage factor of 2.



| Corrected performance (dB) | 0.2 MHz to 3 GHz | 3 to 8 GHz | 8 to 20 GHz | 20 to 26.5 GHz |
|------------------------------------|------------------|------------|-------------|----------------|
| Directivity | 41 | 35 | 33 | 31 |
| Source match | 40 | 34 | 31 | 30 |
| Load match ¹ | 40 | 33 | 30 | 29 |
| Reflection tracking | ± 0.0019 | ± 0.0085 | ± 0.021 | ± 0.019 |
| Transmission tracking ¹ | ± 0.053 | ± 0.12 | ± 0.20 | ± 0.20 |

Uncertainty plots: power level of -15 dBm, 10 Hz IF bandwidth, no averaging, battery saver off, and 60-minute warm-up time. Includes uncertainties due to drift, noise, compression, and dynamic accuracy. Coverage factor of 1 applied to uncertainties, for ease of comparison with other industry handheld analyzers.

Transmission uncertainty (S₂₁, S₁₂)



Reflection uncertainty (S₁₁, S₂₂)



¹ Load match and transmission tracking are typical values.

Corrected Measurement Uncertainty (continued)



N9913/4/5/6/7/8B, N7554A ECal, Full 2-port Cal, DUT: Type-N, Spec

Corrected performance table calculated using uncertainties with a coverage factor of 2.



| Corrected performance (dB) ¹ | 0.2 MHz to .5 GHz | 0.5 to 4 GHz | 4 to 9 GHz | 9 to 18 GHz |
|---|-------------------|--------------|------------|-------------|
| Directivity | 42 | 36 | 36 | 36 |
| Source match | 37 | 30 | 30 | 28 |
| Load match ² | 37 | 30 | 30 | 28 |
| Reflection tracking | ± 0.13 | ± 0.13 | ± 0.18 | ± 0.25 |
| Transmission tracking ² | ± 0.13 | ± 0.13 | ± 0.18 | ± 0.25 |

Uncertainty plots: power level of -15 dBm, 10 Hz IF bandwidth, no averaging, battery saver off, and 60-minute warm-up time. Includes uncertainties due to drift, noise, compression, and dynamic accuracy. Coverage factor of 1 applied to uncertainties, for ease of comparison with other industry handheld analyzers.

Transmission uncertainty (S21, S12)



Reflection uncertainty (S11, S22)



¹ When applied power exceeds -10 dBm, calibration results will be degraded from the performance indicated in this table.

² Load match and transmission tracking are typical values.

Corrected Measurement Uncertainty (continued)



N9913/4/5/6/7/8B, N7555A ECal, Full 2-port Cal, DUT: 3.5 mm, Spec

Corrected performance table calculated using uncertainties with a coverage factor of 2.



| Corrected performance (dB) ¹ | 0.2 MHz to .5 GHz | 0.5 to 4 GHz | 4 to 9 GHz | 9 to 18 GHz | 18 to 26.5 GHz |
|---|-------------------|--------------|------------|-------------|----------------|
| Directivity | 42 | 36 | 36 | 36 | 36 |
| Source match | 37 | 30 | 30 | 28 | 27 |
| Load match ² | 37 | 30 | 30 | 28 | 27 |
| Reflection tracking | ± 0.13 | ± 0.13 | ± 0.18 | ± 0.25 | ± 0.30 |
| Transmission tracking ² | ± 0.13 | ± 0.13 | ± 0.18 | ± 0.25 | ± 0.30 |

Uncertainty plots: power level of -15 dBm, 10 Hz IF bandwidth, no averaging, battery saver off, and 60-minute warm-up time. Includes uncertainties due to drift, noise, compression, and dynamic accuracy. Coverage factor of 1 applied to uncertainties, for ease of comparison with other industry handheld analyzers.

Transmission uncertainty (S21, S12)



Reflection uncertainty (S11, S22)



¹ When applied power exceeds -10 dBm, calibration results will be degraded from the performance indicated in this table.

² Load match and transmission tracking are typical values.

Corrected Measurement Uncertainty (continued)



N9913/4/5/6/7/8B, N4690D ECal, Full 2-port Cal, DUT: Type-N, Spec

Corrected performance table calculated using uncertainties with a coverage factor of 2.



| Corrected performance (dB) ¹ | .2 to 10 MHz ² | 300 kHz to 2 MHz ³ | 2 to 10 MHz ³ | 10 to 500 MHz | .5 to 2 GHz | 2 to 10 GHz | 10 to 18 GHz |
|---|---------------------------|-------------------------------|--------------------------|---------------|-------------|-------------|--------------|
| Directivity | 45 | 30 | 40 | 45 | 45 | 40 | 38 |
| Source match | 40 | 28 | 35 | 40 | 43 | 40 | 35 |
| Load match ⁴ | 40 | 28 | 35 | 40 | 43 | 40 | 35 |
| Reflection tracking | ± 0.05 | ± 0.12 | ± 0.07 | ± 0.05 | ± 0.03 | ± 0.03 | ± 0.05 |
| Transmission tracking ⁴ | ± 0.05 | ± 0.12 | ± 0.07 | ± 0.05 | ± 0.03 | ± 0.03 | ± 0.05 |

Uncertainty plots⁵: power level of -15 dBm, 10 Hz IF bandwidth, no averaging, battery saver off, and 60-minute warm-up time. Includes uncertainties due to drift, noise, compression, and dynamic accuracy. Coverage factor of 1 applied to uncertainties, for ease of comparison with other industry handheld analyzers.

Transmission uncertainty (S21, S12)



Reflection uncertainty (S11, S22)



¹ When applied power exceeds -10 dBm, calibration results will be degraded from the performance indicated in this table.

² For N4690D ECal Option 0DC.

³ For N4690D ECal Option 003.

⁴ Load match and transmission tracking are typical values.

⁵ Uncertainty plots generated with data from N4690B ECal modules.

Corrected Measurement Uncertainty (continued)



N9913/4/5/6/7/8B, N4691D ECal, Full 2-port Cal, DUT: 3.5 mm, Spec

Corrected performance table calculated using uncertainties with a coverage factor of 2.



| Corrected performance (dB) ¹ | .2 to 10 MHz ² | 300 kHz to 2 MHz ³ | 2 to 10 MHz ³ | 10 to 500 MHz | .5 to 2 GHz | 2 to 10 GHz | 10 to 20 GHz | 20 to 26.5 GHz |
|---|---------------------------|-------------------------------|--------------------------|---------------|-------------|-------------|--------------|----------------|
| Directivity | 46 | 31 | 41 | 46 | 47 | 46 | 43 | 41 |
| Source match | 41 | 29 | 36 | 41 | 47 | 45 | 42 | 40 |
| Load match ⁴ | 41 | 29 | 36 | 41 | 47 | 45 | 42 | 40 |
| Reflection tracking | ± 0.05 | ± 0.11 | ± 0.06 | ± 0.05 | ± 0.02 | ± 0.03 | ± 0.04 | ± 0.05 |
| Transmission tracking ⁴ | ± 0.05 | ± 0.11 | ± 0.06 | ± 0.05 | ± 0.02 | ± 0.03 | ± 0.04 | ± 0.05 |

Uncertainty plots⁵: power level of -15 dBm, 10 Hz IF bandwidth, no averaging, battery saver off, and 60-minute warm-up time. Includes uncertainties due to drift, noise, compression, and dynamic accuracy. Coverage factor of 1 applied to uncertainties, for ease of comparison with other industry handheld analyzers.

Transmission uncertainty (S21, S12)



Reflection uncertainty (S11, S22)



¹ When applied power exceeds -10 dBm, calibration results will be degraded from the performance indicated in this table.

² For N4691D ECal Option ODC.

³ For N4691D ECal Option 003.

⁴ Load match and transmission tracking are typical values.

⁵ Uncertainty plots generated with data from N4691B ECal modules.

Corrected Measurement Uncertainty (continued)



N9950/1/2B, 85056D, 85563A, or 85564A, Full 2-port Cal, DUT: 2.4 mm, Spec

Corrected performance table calculated using uncertainties with a coverage factor of 2.



| Corrected performance (dB) | 0.3 MHz to 4 GHz | 4 to 20 GHz | 20 to 26.5 GHz | 26.5 to 50 GHz |
|------------------------------------|------------------|-------------|----------------|----------------|
| Directivity | 42 | 34 | 26 | 26 |
| Source match | 40 | 30 | 24 | 23 |
| Load match ¹ | 38 | 29 | 26 | 22 |
| Reflection tracking | ± 0.029 | ± 0.029 | ± 0.080 | ± 0.080 |
| Transmission tracking ¹ | ± 0.047 | ± 0.12 | ± 0.12 | ± 0.20 |

Uncertainty plots: power level of -15 dBm, 10 Hz IF bandwidth, no averaging, battery saver off, and 60-minute warm-up time. Includes uncertainties due to drift, noise, compression, and dynamic accuracy. Coverage factor of 1 applied to uncertainties, for ease of comparison with other industry handheld analyzers.

Transmission uncertainty (S21, S12)



Reflection uncertainty (S11, S22)



¹ Load match and transmission tracking are typical values.

Corrected Measurement Uncertainty (continued)


N9950/1/2B, 85561A, Full 2-port Cal, DUT: 2.92 mm, Spec

Corrected performance table calculated using uncertainties with a coverage factor of 2.


| Corrected performance (dB) | 0.3 MHz to 4 GHz | 4 to 20 GHz | 20 to 26.5 GHz | 26.5 to 40 GHz |
|------------------------------------|------------------|-------------|----------------|----------------|
| Directivity | 36 | 26 | 24 | 20 |
| Source match | 31 | 25 | 23 | 19 |
| Load match ¹ | 32 | 24 | 22 | 19 |
| Reflection tracking | ± 0.001 | ± 0.041 | ± 0.049 | ± 0.11 |
| Transmission tracking ¹ | ± 0.16 | ± 0.30 | ± 0.43 | ± 0.52 |

Uncertainty plots: power level of -15 dBm, 10 Hz IF bandwidth, no averaging, battery saver off, and 60-minute warm-up time. Includes uncertainties due to drift, noise, compression, and dynamic accuracy. Coverage factor of 1 applied to uncertainties, for ease of comparison with other industry handheld analyzers.

Transmission uncertainty (S21, S12)



Reflection uncertainty (S11, S22)



¹ Load match and transmission tracking are typical values.

Corrected Measurement Uncertainty (continued)



N9950/1/2B, 85562A, Full 2-port Cal, DUT: 2.92 mm, Spec

Corrected performance table calculated using uncertainties with a coverage factor of 2.



| Corrected performance (dB) | 0.3 MHz to 4 GHz | 4 to 20 GHz | 20 to 26.5 GHz | 26.5 to 40 GHz |
|------------------------------------|------------------|-------------|----------------|----------------|
| Directivity | 36 | 28 | 28 | 25 |
| Source match | 34 | 27 | 25 | 23 |
| Load match ¹ | 32 | 26 | 23 | 22 |
| Reflection tracking | ± 0.006 | ± 0.026 | ± 0.062 | ± 0.13 |
| Transmission tracking ¹ | ± 0.16 | ± 0.24 | ± 0.42 | ± 0.48 |

Uncertainty plots: power level of -15 dBm, 10 Hz IF bandwidth, no averaging, battery saver off, and 60-minute warm-up time. Includes uncertainties due to drift, noise, compression, and dynamic accuracy. Coverage factor of 1 applied to uncertainties, for ease of comparison with other industry handheld analyzers.

Transmission uncertainty (S21, S12)



Reflection uncertainty (S11, S22)



¹ Load match and transmission tracking are typical values.

Corrected Measurement Uncertainty (continued)



N9950/1/2B, BN 534913, Full 2-port Cal, DUT: 2.92 mm, Spec

Corrected performance table calculated using uncertainties with a coverage factor of 2.



| Corrected performance (dB) | 0.3 MHz to 4 GHz | 4 to 20 GHz | 20 to 26.5 GHz | 26.5 to 44 GHz |
|------------------------------------|------------------|-------------|----------------|----------------|
| Directivity | 34 | 30 | 25 | 19 |
| Source match | 34 | 26 | 23 | 18 |
| Load match ¹ | 31 | 26 | 22 | 17 |
| Reflection tracking | ± 0.006 | ± 0.026 | ± 0.086 | ± 0.25 |
| Transmission tracking ¹ | ± 0.22 | ± 0.33 | ± 0.41 | ± 0.54 |

Uncertainty plots: power level of -15 dBm, 10 Hz IF bandwidth, no averaging, battery saver off, and 60-minute warm-up time. Includes uncertainties due to drift, noise, compression, and dynamic accuracy. Coverage factor of 1 applied to uncertainties, for ease of comparison with other industry handheld analyzers.

Transmission uncertainty (S21, S12)



Reflection uncertainty (S11, S22)



¹ Load match and transmission tracking are typical values.

Corrected Measurement Uncertainty (continued)



N9950/1/2B, BN 534914, Full 2-port Cal, DUT: 2.92 mm, Spec

Corrected performance table calculated using uncertainties with a coverage factor of 2.



| Corrected performance (dB) | 0.3 MHz to 4 GHz | 4 to 20 GHz | 20 to 26.5 GHz | 26.5 to 44 GHz |
|------------------------------------|------------------|-------------|----------------|----------------|
| Directivity | 30 | 29 | 25 | 18 |
| Source match | 29 | 28 | 23 | 18 |
| Load match ¹ | 29 | 25 | 22 | 18 |
| Reflection tracking | ± 0.005 | ± 0.042 | ± 0.072 | ± 0.24 |
| Transmission tracking ¹ | ± 0.18 | ± 0.37 | ± 0.43 | ± 0.47 |

Uncertainty plots: power level of -15 dBm, 10 Hz IF bandwidth, no averaging, battery saver off, and 60-minute warm-up time. Includes uncertainties due to drift, noise, compression, and dynamic accuracy. Coverage factor of 1 applied to uncertainties, for ease of comparison with other industry handheld analyzers.

Transmission uncertainty (S21, S12)



Reflection uncertainty (S11, S22)



¹ Load match and transmission tracking are typical values.

Corrected Measurement Uncertainty (continued)


N9950/1/2B, N4692D ECal Option 0DC, Full 2-port Cal, DUT: 2.92 mm, Spec

Corrected performance table calculated using uncertainties with a coverage factor of 2.


| Corrected performance (dB) ¹ | 0.3 MHz to 4 GHz | 4 to 20 GHz | 20 to 26.5 GHz | 26.5 to 40 GHz |
|---|------------------|-------------|----------------|----------------|
| Directivity | 40 | 38 | 35 | 32 |
| Source match | 38 | 35 | 30 | 29 |
| Load match ² | 30 | 27 | 27 | 26 |
| Reflection tracking | ± 0.1 | ± 0.1 | ± 0.10 | ± 0.12 |
| Transmission tracking ² | ± 0.2 | ± 0.25 | ± 0.25 | ± 0.29 |

Uncertainty plots: power level of -15 dBm, 10 Hz IF bandwidth, no averaging, battery saver off, and 60-minute warm-up time. Includes uncertainties due to drift, noise, compression, and dynamic accuracy. Coverage factor of 1 applied to uncertainties, for ease of comparison with other industry handheld analyzers.

Transmission uncertainty (S21, S12) – N4692D ECal Option 0DC



Reflection uncertainty (S11, S22) – N4692D ECal Option 0DC



¹ When applied power exceeds -10 dBm, calibration results will be degraded from the performance indicated in this table.

² Load match and transmission tracking are typical values.

Corrected Measurement Uncertainty (continued)



N9950/1/2B, N4692D ECal Option 010, Full 2-port Cal, DUT: 2.92 mm, Spec

Corrected performance table calculated using uncertainties with a coverage factor of 2.



| Corrected performance (dB) ¹ | 10 MHz to 4 GHz | 4 to 20 GHz | 20 to 26.5 GHz | 26.5 to 40 GHz |
|---|-----------------|-------------|----------------|----------------|
| Directivity | 29 | 38 | 35 | 32 |
| Source match | 29 | 35 | 30 | 29 |
| Load match ² | 24 | 27 | 27 | 26 |
| Reflection tracking | ± 0.18 | ± 0.1 | ± 0.10 | ± 0.12 |
| Transmission tracking ² | ± 0.34 | ± 0.25 | ± 0.25 | ± 0.29 |

Uncertainty plots: power level of -15 dBm, 10 Hz IF bandwidth, no averaging, battery saver off, and 60-minute warm-up time. Includes uncertainties due to drift, noise, compression, and dynamic accuracy. Coverage factor of 1 applied to uncertainties, for ease of comparison with other industry handheld analyzers.

Transmission uncertainty (S21, S12) – N4692D ECal Option 010



Reflection uncertainty (S11, S22) – N4692D ECal Option 010



¹ When applied power exceeds -10 dBm, calibration results will be degraded from the performance indicated in this table.

² Load match and transmission tracking are typical values.

Corrected Measurement Uncertainty (continued)



N9950/1/2B, N4693D ECal Option 0DC, Full 2-port Cal, DUT: 2.4 mm, Spec

Corrected performance table calculated using uncertainties with a coverage factor of 2.



| Corrected performance (dB) ¹ | .3 MHz to 4 GHz | 4 to 20 GHz | 20 to 26.5 GHz | 26.5 to 50 GHz |
|---|-----------------|-------------|----------------|----------------|
| Directivity | 40 | 44 | 38 | 34 |
| Source match | 38 | 37 | 35 | 32 |
| Load match ² | 34 | 32 | 32 | 29 |
| Reflection tracking | ± 0.05 | ± 0.05 | ± 0.06 | ± 0.08 |
| Transmission tracking ² | ± 0.11 | ± 0.14 | ± 0.14 | ± 0.20 |

Uncertainty plots: power level of -15 dBm, 10 Hz IF bandwidth, no averaging, battery saver off, and 60-minute warm-up time. Includes uncertainties due to drift, noise, compression, and dynamic accuracy. Coverage factor of 1 applied to uncertainties, for ease of comparison with other industry handheld analyzers.

Transmission uncertainty (S21, S12) – N4693D ECal Option 0DC



Reflection uncertainty (S11, S22) – N4693D ECal Option 0DC



¹ When applied power exceeds -10 dBm, calibration results will be degraded from the performance indicated in this table.

² Load match and transmission tracking are typical values.

Corrected Measurement Uncertainty (continued)



N9950/1/2B, N4693D ECal Option 010, Full 2-port Cal, DUT: 2.4 mm, Spec

Corrected performance table calculated using uncertainties with a coverage factor of 2.



| Corrected performance (dB) ¹ | 10 MHz to 4 GHz | 4 to 20 GHz | 20 to 26.5 GHz | 26.5 to 50 GHz |
|---|-----------------|-------------|----------------|----------------|
| Directivity | 27 | 44 | 38 | 34 |
| Source match | 25 | 37 | 35 | 32 |
| Load match ² | 23 | 32 | 32 | 29 |
| Reflection tracking | ± 0.05 | ± 0.05 | ± 0.06 | ± 0.08 |
| Transmission tracking ² | ± 0.43 | ± 0.14 | ± 0.14 | ± 0.20 |

Uncertainty plots: power level of -15 dBm, 10 Hz IF bandwidth, no averaging, battery saver off, and 60-minute warm-up time. Includes uncertainties due to drift, noise, compression, and dynamic accuracy. Coverage factor of 1 applied to uncertainties, for ease of comparison with other industry handheld analyzers.

Transmission uncertainty (S21, S12) – N4693D ECal Option 010



Reflection uncertainty (S11, S22) – N4693D ECal Option 010



¹ When applied power exceeds -10 dBm, calibration results will be degraded from the performance indicated in this table.

² Load match and transmission tracking are typical values.

The performance listed in TDR cable measurements, VNA time domain, mixed-mode S-parameters and vector voltmeter sections applies to the capabilities available in the following models:

FieldFox RF & microwave (combination) analyzers: N9913B, N9914B, N9915B, N9916B, N9917B, N9918B,
N9950B, N9951B, N9952B

See [FieldFox Configuration Guide](#) for option information. Many capabilities listed in this Data Sheet require options.

TDR Cable Measurements (Option 215)

The TDR cable option adds time domain reflectometry (TDR) measurements to FieldFox's CAT mode. FieldFox's TDR measurements are based on an inverse Fourier transform of the frequency-domain data. TDR measurements are useful in not only identifying the location of faults along cables, but also the nature of the fault. Resistive, inductive and capacitive faults will each have a different response. These differences help engineers and technicians' trouble-shoot line faults.

Measurements: TDR (linear rho), TDR (ohm), TDR & DTF

Y-axis: linear (rho) or impedance (ohm)

X-axis: distance (meters or feet)

VNA Time Domain (Option 010)

In time-domain mode, FieldFox computes the inverse Fourier transform of the frequency-domain data to display reflection or transmission coefficients versus time.

| Setup parameters | |
|--|--|
| Time | Start, stop, center, span |
| Gating | Start, stop, center, span, and on/off |
| Numbers of points, velocity vector, line loss, window shape, independent control for all four traces | |
| Time stimulus modes | |
| Low-pass step | Low-pass step is similar to a traditional time domain reflectometer (TDR) stimulus waveform. It is used to measure low-pass devices. The frequency-domain data should extend from DC (extrapolated value) to a higher value. |
| Low-pass impulse | Low-pass impulse response is used to measure low-pass devices. |
| Bandpass impulse | The bandpass impulse simulates a pulsed RF signal and is used to measure the time domain response of band-limited devices. |
| Windows | |
| The windowing function can be used to filter the frequency domain data and thereby reduce overshoot and ringing in the time domain response. | |
| Windows | Minimum, medium and maximum, manual entry of Kaiser Beta and impulse width. |
| Gating | |
| The gating function can be used to selectively remove reflection or transmission time domain responses. In converting back to the frequency domain, the effects of the responses outside the gate are removed. The results can be viewed with gating on and off, using two traces. | |
| Gate types | Notch, bandpass |
| Gate shapes | Maximum, wide, normal, minimum |

Mixed-Mode S-Parameters (Option 212)

Mixed-mode S-parameters are also known as balanced measurements.

| Measurements | |
|--------------------|--|
| Sc _c 11 | Common mode reflection |
| S _d d11 | Differential mode reflection |
| Sc _d 11 | Differential mode stimulus, common mode response |
| S _d c11 | Common mode stimulus, differential mode response |

FieldFox's mixed-mode S-parameter measurements require the use of the default factory calibration or a user 2-port calibration. So, the FieldFox analyzer must be equipped with 2-port measurement functionality to measure mixed-mode S-parameters. Mixed-mode S-parameters are an extension of the VNA capabilities.

Vector Voltmeter (VVM) (Option 308)

With vector voltmeter mode, you can characterize the difference between two measurements easily. The zeroing function allows you to create a reference signal and characterize the difference between two device measurements. The results are shown on a large display in digital format.

| | Models | Frequency range |
|--------|--------|--------------------|
| N991xB | N9913B | 30 kHz to 4 GHz |
| | N9914B | 30 kHz to 6.5 GHz |
| | N9915B | 30 kHz to 9 GHz |
| | N9916B | 30 kHz to 14 GHz |
| | N9917B | 30 kHz to 18 GHz |
| | N9918B | 30 kHz to 26.5 GHz |
| N995xB | N9950B | 300 kHz to 32 GHz |
| | N9951B | 300 kHz to 44 GHz |
| | N9952B | 300 kHz to 50 GHz |

| Setup parameters | |
|-----------------------|---|
| 1-port cable trimming | Reflection (S11 or S22 measurement), magnitude and phase |
| 2-port transmission | Transmission or S21 measurement, magnitude, and phase |
| A/B and B/A | Ratio of two receivers or channels, magnitude, and phase – Need an external signal generator for the A/B or B/A measurement |
| | Frequency (one CW frequency point) |
| | IF bandwidth: 10 Hz to 100 kHz or 3 Hz to 30 kHz |
| | Output power: Low, high, manual |

Ratio accuracy (A/B and B/A)

Must zero before measuring DUT. Recommend using a high-quality power splitter or 6 dB attenuators to minimize uncertainty due to mismatch.

| | Frequency | Nominal (dB) |
|--------|------------------|--------------|
| N991xB | 100 kHz to 2 GHz | ± 0.2 |
| N995xB | 300 kHz to 2 GHz | ± 0.2 |

Spectrum Analyzer (Option 233 on Combination Analyzers)

The performance listed in this section applies to the spectrum analyzer capabilities available in the following models:

| | |
|--|--|
| FieldFox RF & microwave (combination) analyzers: | N9913B, N9914B, N9915B, N9916B, N9917B, N9918B |
| FieldFox RF & microwave signal analyzers: | N9933B, N9934B, N9935B, N9936B, N9937B, N9938B |
| FieldFox microwave (combination) analyzers: | N9950B, N9951B, N9952B |
| FieldFox microwave signal analyzers: | N9960B, N9961B, N9962B |

See [FieldFox Configuration Guide](#) for option information. Many capabilities listed in this Data Sheet require options.

Frequency and time specifications

| | Models | Frequency range ¹ | |
|----------------|----------------|------------------------------|-----------------|
| N991xB, N993xB | N9913B, N9933B | 9 kHz to 4 GHz | Usable to 5 kHz |
| | N9914B, N9934B | 9 kHz to 6.5 GHz | Usable to 5 kHz |
| | N9915B, N9935B | 9 kHz to 9 GHz | Usable to 5 kHz |
| | N9916B, N9936B | 9 kHz to 14 GHz | Usable to 5 kHz |
| | N9917B, N9937B | 9 kHz to 18 GHz | Usable to 5 kHz |
| | N9918B, N9938B | 9 kHz to 26.5 GHz | Usable to 5 kHz |
| N995xB, N996xB | N9950B, N9960B | 9 kHz to 32 GHz | Usable to 5 kHz |
| | N9951B, N9961B | 9 kHz to 44 GHz | Usable to 5 kHz |
| | N9952B, N9962B | 9 kHz to 50 GHz | Usable to 5 kHz |

Frequency reference, -10 to 55°C

| | |
|--|---|
| Accuracy | ± 0.9 ppm (spec) + aging |
| | ± 0.5 ppm (typical) + aging |
| Accuracy, when locked to GPS | ± 0.01 ppm (spec) |
| Accuracy, when GPS antenna is disconnected | ± 0.4 ppm (nominal) ² |
| Aging rate | ± 1 ppm/yr for 20 years (spec), will not exceed ± 3.5 ppm |

Frequency readout accuracy (start, stop, center, marker)

| | |
|--|--|
| ± (readout frequency x frequency reference accuracy + RBW centering + 0.5 x horizontal resolution) | Horizontal resolution = frequency span / (trace points – 1) |
| | RBW centering: |
| | <ul style="list-style-type: none"> • 5% x RBW, FFT mode (nominal) • 16% x RBW, step mode (nominal) |

Marker frequency counter

| | |
|------------|--|
| Accuracy | ± (marker frequency x frequency reference accuracy + counter resolution) |
| Resolution | 1 Hz |

¹ The spectrum analyzer is tunable to 0 Hz or DC.

² The maximum drift expected in the frequency reference applicable when the ambient temperature changes ± 5°C from the temperature when the GPS signal was last connected.

Spectrum Analyzer (Option 233 on Combination Analyzers) (continued)

Frequency and time specifications (continued)

| Frequency Span | Spec |
|---|---|
| Range | 0 Hz (zero span), 10 Hz to maximum frequency range of instrument |
| Resolution | 1 Hz |
| Accuracy | $\pm (2 \times \text{RBW centering} + \text{horizontal resolution})$ for detector = Normal |
| Sweep time readout | Measured value of the time required to complete a sweep from start to finish, including time to tune receiver, acquire data, and process trace. |
| Trace update | N991xB, N993xB, N995xB, N996xB (Nominal) |
| Span = 20 MHz, RBW, VBW = 3 kHz | 9 updates per second |
| Span = 100 MHz, RBW, VBW autocoupled | 25 updates per second |
| Center frequency tune and transfer¹ | N991xB, N993xB (Nominal) N995xB, N996xB (Nominal) |
| 101 points, zero span | 58 ms 83 ms |
| 101 points, 1 MHz span | 52 ms 78 ms |
| 101 points, 100 MHz span | 56 ms 84 ms |
| Sweep time, zero span | N991xB, N993xB, N995xB, N996xB (Nominal) |
| Range | 1 μ s to 6000 s |
| Resolution | 100 ns |
| Readout | Entered value representing trace horizontal scale range |
| Trigger (for zero span and FFT sweeps) | |
| Trigger type | Free run, external, video, RF burst |
| Trigger slope | Positive edge, negative edge |
| Trigger delay | Range: -150 ms to 10 s Resolution: 100 ns |
| Auto trigger | Forces a periodic acquisition in the absence of a trigger event Range: 0 (off) to 30 s |
| Trigger position (zero span) | Controls horizontal position of the pulse edge; use sweep time to zoom into pulse edge Range: 0 to 10, integer steps; 0 is left edge of graticule, 10 is right edge of graticule |
| RF burst trigger | Nominal |
| Dynamic range | 40 dB |
| Bandwidth | 20 MHz |
| Operating frequency range | 20 MHz to maximum instrument frequency |
| Sweep (trace) point range | |
| All spans | 101, 201, 401, 601, 801, 1001 (defaults to 401) Arbitrary 2 to 20,001 settable through soft key "# Points" or SCPI |

¹ Within full frequency range of instrument, not band dependent

Spectrum Analyzer (Option 233 on Combination Analyzers) (continued)

Frequency and time specifications (continued)

| Resolution bandwidth (RBW) | | Nominal |
|------------------------------|------------------|--|
| Range (-3 dB bandwidth) | | |
| Zero span | 10 Hz to 5 MHz | 1, 3, 10 sequence |
| Non-zero span | 1 Hz to 5 MHz | 1, 1.5, 2, 3, 5, 7.5, 10 sequence < 300 kHz, 300 kHz, 1 MHz, 3 MHz, 5 MHz (Other RBWs may be set depending on settings) |
| | | Step keys change RBW in 1, 3, 10 sequence |
| Selectivity (-60 dB / -3 dB) | 4:1 | |
| Bandwidth accuracy | | Nominal |
| Zero span | 10 Hz to 1 MHz | ± 5% |
| | 3 MHz | ± 10% |
| | 5 MHz | ± 15% |
| Non-zero span | 1 Hz to 100 kHz | ± 1% |
| | 300 kHz to 1 MHz | ± 5% |
| | 3 MHz | ± 10% |
| | 5 MHz | ± 15% |
| Video bandwidth (VBW) | | |
| 1 Hz to 5 MHz | | 1, 1.5, 2, 3, 5, 7.5, 10 sequence |

Amplitude accuracy and range specifications

| Amplitude range | | |
|------------------------|--|---------------------------|
| Measurement range | DANL to +20 dBm | |
| Input attenuator range | 0 to 40 dB, in 5 dB steps | |
| Preamplifier | | Nominal |
| Frequency range | Full band (9 kHz to maximum frequency of instrument) | |
| Gain | N991xB, N993xB | +20 dB, 9 kHz to 26.5 GHz |
| | N995xB, N996xB | +15 dB, 9 kHz to 50 GHz |
| Max safe input level | Average CW power | DC |
| N991xB, N993xB | +27 dBm, 0.5 watts | ± 50 VDC |
| N995xB, N996xB | +25 dBm, 0.3 watts | ± 40 VDC |
| Display range | | |
| Log scale | 10 divisions | |
| | 0.01 to 100 dB/division in 0.01 dB steps | |
| Linear scale | 10 divisions | |
| Scale units | dBm, dBmV, dBμV, dBmA, dBμA, W, V, A, dBμV/m, dBμA/m, dBG, dBT | |

Spectrum Analyzer (continued)

Amplitude accuracy and range specifications (continued)

| 50 MHz absolute amplitude accuracy (dB) | | | |
|--|-------------------------------------|---------------------------|------------------------------|
| 10 dB attenuation, input signal -40 to -5 dBm, peak detector, preamplifier off ¹ , 300 Hz RBW, all settings auto-coupled. No warm-up required. | | | |
| | | Spec (-10 to 55°C) | Typical (-10 to 55°C) |
| N991xB, N993xB, N995xB, N996xB | | ± 0.50 | ± 0.20 |
| Total absolute amplitude accuracy (dB) | | | |
| 10 dB attenuation, input signal -15 to -5 dBm, peak detector, preamplifier off ² , 300 Hz RBW, all settings auto-coupled, includes frequency response uncertainties. No warm-up required. | | | |
| | | Spec (-10 to 55°C) | Typical (-10 to 55°C) |
| N991xB, N993xB ³ | 9 kHz to 100 kHz ⁴ | ± 2.00 | ± 0.25 |
| | > 100 kHz to 500 MHz ^{4,5} | ± 0.80 | ± 0.20 |
| | > 500 MHz to 16.3 GHz ⁵ | ± 1.00 | ± 0.20 |
| | > 16.3 to 18 GHz ⁵ | ± 1.00 | ± 0.30 |
| | > 18 to 26.5 GHz ⁶ | ± 1.10 | ± 0.35 |
| N995xB, N996xB | 9 kHz to 500 kHz | ± 2.20 | ± 0.60 |
| | > 500 kHz to 15 MHz | ± 1.00 | ± 0.10 |
| | > 15 MHz to 18 GHz | ± 1.00 | ± 0.20 |
| | > 18 to 26.5 GHz | ± 1.10 | ± 0.25 |
| | > 26.5 to 32 GHz | ± 1.20 | ± 0.35 |
| | > 32 to 36 GHz | ± 1.40 | ± 0.35 |
| | > 36 to 44 GHz | ± 2.00 | ± 0.55 |
| | > 44 to 50 GHz | ± 2.40 | ± 0.55 |
| Resolution bandwidth switching uncertainty | | Nominal | |
| RBW < 5 MHz | | 0.0 dB | |
| For signals not at center frequency | | 0.7 dB peak-to-peak | |

¹ The spec and typical values, with preamp on, are identical to that with preamp off, but the input signal levels are -40 to -20 dBm

² The N991xB and N993xB preamp on specification uses 20 dB attenuation, input signal -25 to -15 dBm. The N995xB and N996xB preamp on specification uses 20 dB attenuation with -20 dBm input, and all the total absolute amplitude accuracy (Spec and Typical values) listed apply with preamp on except for the spec value at 9 to 300 kHz being ± 4 dB

³ Preamplifier on specification uses 20 dB attenuation, input signal -20 dBm. All the total absolute amplitude accuracy values listed apply with preamplifier on except for the spec value at 9 to 300 kHz which is ± 4 dB.

⁴ For frequencies 9 to 300 kHz, total absolute amplitude accuracy (Typical value) is ± 0.8 dB with preamplifier on.

⁵ For frequencies > 300 kHz to 18 GHz, total absolute amplitude accuracy (Spec and Typical values) apply with preamplifier off or on.

⁶ For frequencies > 18 to 26.5 GHz, total absolute amplitude accuracy (Spec value) is ± 1.20 dB with preamplifier on.

Spectrum Analyzer (continued)

Amplitude accuracy and range specifications (continued)

| RF input VSWR | | Nominal |
|--------------------------------------|--|---------|
| N991xB, N993xB (0 dB attenuation) | 10 MHz to 2.7 GHz | 1.7 : 1 |
| | > 2.7 to 7.5 GHz | 1.5 : 1 |
| | > 7.5 to 26.5 GHz | 2.0 : 1 |
| N995xB, N996xB (0 dB attenuation) | 10 MHz to 2.7 GHz | 1.7 : 1 |
| | > 2.7 to 7.5 GHz | 1.8 : 1 |
| | > 7.5 to 26.5 GHz | 2.0 : 1 |
| | > 26.5 to 40 GHz | 2.5 : 1 |
| | > 40 to 50 GHz | 3.0 : 1 |
| Reference level | | |
| Range | -210 to +90 dBm | |
| Traces | | |
| Detectors | Normal, positive peak, negative peak, sample, average (RMS) | |
| States | Clear/write, max hold, min hold, average, view, blank | |
| | Number of averages: 1 to 10,001 | |
| Number | 4: all four can be active simultaneously and in different states | |
| Markers | | |
| Number of markers | 6 | |
| Type | Normal, delta, marker table | |
| Marker functions | Noise, band power, frequency counter | |
| Audio beep | Volume and tone change with signal strength | |
| Marker table | Display 6 markers | |
| Marker → | Peak, next peak, peak left, peak right, center frequency, reference level, minimum | |
| | Tune frequency, for AM/FM tune and listen | |
| Marker properties | Peak criteria: peak excursion, peak threshold | |
| | Delta reference fixed: Off or On | |
| | Time zero fixed: Off or On | |

Spectrum Analyzer (continued)

Dynamic range specifications

| Displayed average noise level (DANL) - (dBm) | | | | |
|---|-----------------------|--------------------------|-----------------------|--------------------------|
| Input terminated, RMS detection, log averaging, 0 dB input attenuation, reference level of -20 dBm, normalized to 1 Hz RBW, measured at non-zero frequency span | | | | |
| N991xB, N993xB | Preamp off | | Preamp on | |
| | Spec (-10 to 55°C) | Typical (-10 to 55°C) | Spec (-10 to 55°C) | Typical (-10 to 55°C) |
| 9 kHz to 2 MHz | -122 | -134 | -129 | -148 |
| ≥ 2 MHz to 2.1 GHz | -137 | -147 | -156 | -163 |
| ≥ 2.1 to 2.6 GHz | -136 | -143 | -155 | -160 |
| ≥ 2.6 to 4.5 GHz | -141 | -147 | -156 | -162 |
| ≥ 4.5 to 7.5 GHz | -134 | -144 | -152 | -160 |
| ≥ 7.5 to 13 GHz | -138 | -143 | -156 | -161 |
| ≥ 13 to 18 GHz | -134 | -139 | -153 | -158 |
| ≥ 18 to 22 GHz | -132 | -138 | -152 | -157 |
| ≥ 22 to 25 GHz | -128 | -136 | -149 | -155 |
| ≥ 25 to 26.5 GHz | -126 | -132 | -146 | -152 |
| N995xB, N996xB | Preamp off | | Preamp on | |
| | Spec (-10 to 55°C) | Typical (-10 to 55°C) | Spec (-10 to 55°C) | Typical (-10 to 55°C) |
| 9 kHz to 2 MHz | -94 | -129 | -96 | -141 |
| ≥ 2 MHz to 2.1 GHz | -138 | -149 | -155 | -163 |
| ≥ 2.1 to 7.5 GHz | -138 | -147 | -155 | -161 |
| ≥ 7.5 to 13 GHz | -138 | -146 | -152 | -157 |
| ≥ 13 to 26.5 GHz | -132 | -142 | -145 | -153 |
| ≥ 26.5 to 32 GHz | -141 | -147 | -151 | -156 |
| ≥ 32 to 40 GHz | -134 | -144 | -147 | -154 |
| ≥ 40 to 44 GHz | -128 | -137 | -141 | -149 |
| ≥ 44 to 50 GHz | -118 | -129 | -131 | -142 |

Spectrum Analyzer (continued)

Dynamic range specifications (continued)

| Residual responses (dBm) | | | Nominal |
|---|------------------------------|--|---------|
| Input terminated preamp off, 0 dB attenuation | | | |
| N991xB, N993xB | 9 kHz to 10 MHz ¹ | | -90 |
| | ≥ 10 MHz to 10 GHz | | -105 |
| | ≥ 10 GHz to 15 GHz | | -100 |
| | ≥ 15 GHz to 26.5 GHz | | -115 |
| N995xB, N996xB | 9 kHz to 9 MHz | | -90 |
| | ≥ 9 MHz to 50 GHz | | -110 |

| Input related responses (dBc) | | | Nominal |
|---|----------------------|-------------------------------------|---------|
| N991xB, N993xB | | | |
| Tuned frequency (f) | Excitation frequency | Spur frequency | |
| -30 dBm signal at mixer input (excludes frequencies listed below) | | | -80 |
| f > 2.6 GHz to 4 GHz | f + 9.93375 GHz / 2 | f | -65 |
| f > 6 GHz to 7.5 GHz | f + 2 * 9.93375 GHz | f | -65 |
| f > 12 GHz to 14 GHz | f + 2 * 3.56625 GHz | f | -70 |
| f > 19.5 GHz to 23 GHz | f - 2 * 3.56625 GHz | f | -75 |
| f > 23 GHz to 26.5 GHz | f - 2 * 3.56625 GHz | f | -55 |
| f < 7.5 GHz | f + 933.75 MHz / 2 | f | -80 |
| f > 4 GHz to 12 GHz | f +/- 2 * 933.75 MHz | f | -65 |
| fOffset = frequency offset of excitation frequency from tuned frequency (f) | | | |
| f < 2.6 GHz, f > 7.5 GHz to 19.5 GHz | f + fOffset | f - n * fOffset, (n = 1, 2, 3, ...) | -75 |
| | f + fOffset | f - 2 * (5.625 MHz +/- fOffset) | -70 |
| f > 2.6 GHz to 7.5 GHz, f > 19.5 GHz | f + fOffset | f - n * fOffset, (n = 1, 2, 3, ...) | -75 |
| | f + fOffset | f + 2 * (5.625 MHz +/- fOffset) | -70 |

¹ Excludes 5.625 MHz at -85 dBm.

| Input related responses (dBc) | | | Nominal |
|---|-----------------------|--|---------|
| N995xB, N996xB | | | |
| Tuned frequency (f) | Excitation frequency | Spur frequency | |
| -30 dBm signal at mixer input (excludes frequencies listed below) | | | -85 |
| $f \geq 2.6$ to 7.5 GHz | $f + 2 * 9.93375$ GHz | f | -80 |
| $f \geq 7.5$ to 9.5 GHz | $f + 2 * 3.56625$ GHz | f | -85 |
| $f \geq 9.5$ to 12.3 GHz | $f + 2 * 3.56625$ GHz | f | -80 |
| $f \geq 12.3$ to 15.7 GHz | $f + 2 * 3.56625$ GHz | f | -65 |
| $f \geq 15.7$ to 19.5 GHz | $f + 2 * 3.56625$ GHz | f | -80 |
| $f \geq 19.5$ to 23 GHz | $f - 2 * 3.56625$ GHz | f | -60 |
| $f \geq 23$ to 26.5 GHz | $f - 2 * 3.56625$ GHz | f | -55 |
| $f \geq 26.5$ to 32.5 GHz | $f + 2 * 3.56625$ GHz | f | -70 |
| $f \geq 32.5$ to 36 GHz | $f - 2 * 3.56625$ GHz | f | -55 |
| $f \geq 36$ to 43 GHz | $f - 2 * 3.56625$ GHz | f | -50 |
| $f \geq 43$ to 46.2 GHz | $f + 2 * 3.56625$ GHz | f | -50 |
| $f \geq 46.2$ to 50 GHz | $f - 2 * 3.56625$ GHz | f | -45 |
| $f < 2.6$ GHz | $f + 3.56625$ GHz / 2 | f | -90 |
| $f \geq 2.6$ to 7.5 GHz | $f + 9.93375$ GHz / 2 | f | -70 |
| $f \geq 7.5$ to 15.7 GHz | $f + 3.56625$ GHz / 2 | f | -75 |
| $f \geq 15.7$ to 19.5 GHz | $f + 3.56625$ GHz / 2 | f | -80 |
| $f \geq 19.5$ to 26.5 GHz | $f - 3.56625$ GHz / 2 | f | -80 |
| $f \geq 26.5$ to 32.5 GHz | $f + 3.56625$ GHz / 2 | f | -55 |
| $f \geq 32.5$ to 39.5 GHz | $f - 3.56625$ GHz / 2 | f | -50 |
| $f \geq 39.5$ to 43 GHz | $f - 3.56625$ GHz / 2 | f | -60 |
| $f \geq 43$ to 46.2 GHz | $f + 3.56625$ GHz / 2 | f | -70 |
| $f \geq 46.2$ to 50 GHz | $f - 3.56625$ GHz / 2 | f | -65 |
| fOffset = frequency offset of excitation frequency from tuned frequency (f) | | | |
| $f < 2.6$ GHz, $f > 7.5$ GHz to 19.5 GHz, $f > 26.5$ GHz to 32.5 GHz, $f > 43$ GHz to 46.2 GHz | $f + f\text{Offset}$ | $f - n * f\text{Offset}$, ($n = 1, 2, 3, \dots$) | -75 |
| | $f + f\text{Offset}$ | $f - 2 * (5.625 \text{ MHz} \pm f\text{Offset})$ | -70 |
| $f > 2.6$ GHz to 7.5 GHz, $f > 19.5$ GHz to 26.5 GHz, $f > 32.5$ GHz to 43 GHz, $f > 46.2$ GHz | $f + f\text{Offset}$ | $f - n * f\text{Offset}$, ($n = 1, 2, 3, \dots$) | -75 |
| | $f + f\text{Offset}$ | $f + 2 * (5.625 \text{ MHz} \pm f\text{Offset})$ | -70 |

Spectrum Analyzer (continued)

Dynamic range specifications (continued)

| Other spurious responses (dBc) | | |
|--|----------------|------------------|
| Nominal | N991xB, N993xB | N995xB, N996xB |
| LO related spurs | | |
| 9 kHz to 13 GHz | -75 | -75 |
| ≥13 to 26.5 GHz | -70 | -70 |
| ≥ 26.5 to 50 GHz | - | -64 |
| Sideband | -80 | -80 |
| Battery charging sideband ¹ | -70 | -70 |
| Second harmonic distortion | | Nominal |
| -30 dBm signal at mixer input | SHI (dBm) | Distortion (dBc) |
| N991xB, N993xB | | |
| 10 to 50 MHz | +35 | -65 |
| > 50 MHz to 1.3 GHz | +50 | -80 |
| ≥ 1.3 to 3.75 GHz | +35 | -65 |
| ≥ 3.75 to 13.25 GHz | +50 | -80 |
| N995xB, N996xB | | |
| 10 to 100 MHz | +35 | -65 |
| > 100 MHz to 1.3 GHz | +50 | -80 |
| ≥ 1.3 to 3.75 GHz | +35 | -65 |
| ≥ 3.75 to 20 GHz | +25 | -55 |
| ≥ 20 to 25 GHz | +20 | -50 |


¹ Charging sidebands will only occur when battery is being charged. The charging sidebands will have an offset between 50 kHz and 350 kHz and they may have harmonics.

| Third order intermodulation distortion (TOI) – (dBm) | | Typical |
|--|--|---------|
| Two -15 dBm signals, 100 kHz spacing at mixer input (-10 to 55°C) | | |
| N991xB, N993xB | 50 MHz to 500 MHz | +8.5 |
| | ≥ 500 MHz to 2 GHz | +11 |
| | ≥ 2 to 2.4 GHz | +13 |
| | ≥ 2.4 to 2.5 GHz | +13.5 |
| | ≥ 2.5 to 7.5 GHz | +9.5 |
| | ≥ 7.5 to 10 GHz | +11 |
| | ≥ 10 to 20 GHz | +13 |
| | ≥ 20 to 26.5 GHz | +15 |
| Two -15 dBm signals, 100 kHz spacing, Ref. level = -10 dBm | | |
| N995xB, N996xB | 50 MHz to 500 MHz | +12.5 |
| | ≥ 500 MHz to 1.4 GHz | +15 |
| | ≥ 1.4 to 2.4 GHz | +15 |
| | ≥ 2.4 to 2.42 GHz | +16 |
| | ≥ 2.42 to 2.6 GHz | +16.5 |
| | ≥ 2.6 to 7.5 GHz | +13 |
| | ≥ 7.5 to 9.5 GHz | +13 |
| | ≥ 9.5 to 16.3 GHz | +13.5 |
| | ≥ 16.3 to 19.5 GHz | +14 |
| | ≥ 19.5 to 23 GHz | +15 |
| | ≥ 23 to 26.5 GHz (all >23 GHz tested with 2 MHz spacing) | +15 |
| | ≥ 26.5 to 32 GHz | +12 |
| | ≥ 32 to 36 GHz | +13 |
| | ≥ 36 to 39.5 GHz | +14 |
| | ≥ 39.5 to 43 GHz | +16 |
| | ≥ 43 to 46.2 GHz | +23 |
| | ≥ 46.2 to 50 GHz | +25 |
| Spur free dynamic range (dB) at 2.4 GHz 2/3 (TOI – DANL) in 1 Hz RBW | | Nominal |
| N991xB, N993xB, N995xB, N996xB | | >104 |

Spectrum Analyzer (continued)

Distortion and noise limited (10 Hz RBW) dynamic range (nominal)


Applies to N991xB and N993xB



Spectrum Analyzer (continued)

Distortion and noise limited (10 Hz RBW) dynamic range (nominal)

Applies to N995xB and N996xB




Spectrum Analyzer (continued)

SSB phase noise at 1 GHz center frequency

| Phase noise (dBc/Hz) | | | | |
|--------------------------|-----------------------|--------------------------|-----------------------|--------------------------|
| SSB phase noise at 1 GHz | | | | |
| N991xB, N993xB | | | N995xB, N996xB | |
| Offset | Spec (-10 to 55°C) | Typical (-10 to 55°C) | Spec (-10 to 55°C) | Typical (-10 to 55°C) |
| 10 kHz | -111 | -117 | -109 | -114 |
| 30 kHz | -110 | -115 | -110 | -114 |
| 100 kHz | -105 | -111 | -105 | -111 |
| 1 MHz | -119 | -124 | -119 | -125 |
| 3 MHz | -123 | -128 | -125 | -131 |
| 5 MHz | -124 | -129 | -126 | -131 |

Phase noise at different center frequencies (nominal)


Applies to N991xB and N993xB



Spectrum Analyzer (continued)

Phase noise at different center frequencies (nominal)


Applies to N995xB and N996xB



Spectrum Analyzer (continued)

Dynamic range versus offset frequency versus RBW (nominal)¹

Applies to N991xB, N993xB, N995xB, and N996xB



¹ For 1 MHz RBW, the sideband observed may degrade the dynamic range to -70 dBc

Tracking Generator or Independent Source

The performance listed in this section applies to the tracking generator and independent source capabilities available in the following models:

| | |
|--|--|
| FieldFox RF & microwave (combination) analyzers: | N9913B, N9914B, N9915B, N9916B, N9917B, N9918B |
| FieldFox RF & microwave signal analyzers: | N9933B, N9934B, N9935B, N9936B, N9937B, N9938B |
| FieldFox microwave (combination) analyzers: | N9950B, N9951B, N9952B |
| FieldFox microwave signal analyzers: | N9960B, N9961B, N9962B |

See [FieldFox Configuration Guide](#) for option information. Many capabilities listed in this Data Sheet require options.

Note: Traditional tracking generators track the receiver frequency only. In FieldFox analyzers, the tracking generator frequency can be set to either track the receiver frequency, or act as an independent CW source.

| | Models | Tracking generator or independent source frequency range |
|---|--|--|
| N991xB, N993xB | N9913B, N9933B | 30 kHz to 4 GHz |
| | N9914B, N9934B | 30 kHz to 6.5 GHz |
| | N9915B, N9935B | 30 kHz to 9 GHz |
| | N9916B, N9936B | 30 kHz to 14 GHz |
| | N9917B, N9937B | 30 kHz to 18 GHz |
| | N9918B, N9938B | 30 kHz to 26.5 GHz |
| N995xB, N996xB | N9950B, N9960B | 300 kHz to 32 GHz |
| | N9951B, N9961B | 300 kHz to 44 GHz |
| | N9952B, N9962B | 300 kHz to 50 GHz |
| Power step size | | |
| Power settable in 1 dB steps across power range | | |
| Functions | | |
| Mode | Continuous wave (CW), CW coupled, tracking (swept frequency) | |
| Operations | Normalization, frequency offset, spectral reversal | |

Tracking Generator or Independent Source (continued)

| Output power (high) (dBm) | Frequency | Typical |
|---|--------------------------|---------|
| N991xB, N993xB | 30 kHz to 500 kHz | -4 |
| | > 500 kHz to 10 MHz | 0 |
| | > 10 MHz to 1 GHz | 9 |
| | > 1 to 5 GHz | 8 |
| | > 5 to 10 GHz | 7 |
| | > 10 to 18 GHz | 6 |
| | > 18 to 26.5 GHz | 3 |
| N995xB, N996xB | 300 kHz to 1 MHz | -5 |
| | > 1 to 10 MHz | -1 |
| | > 10 MHz to 6 GHz | 5 |
| | > 6 to 26.5 GHz | 6 |
| | > 26.5 to 32 GHz | 4 |
| | > 32 to 40 GHz | 2 |
| | > 40 to 44 GHz | -3 |
| | > 44 to 50 GHz | -9 |
| Power level accuracy¹ | Nominal | |
| N991xB, N993xB | Port 1 at -15 dBm | |
| > 500 kHz to 10 MHz | ± 1 dB | |
| > 10 MHz to 26.5 GHz | ± 0.5 dB | |
| N995xB, N996xB² | Port 1 at -15 dBm | |
| 300 kHz to 50 GHz | ± 0.5 dB | |

¹ N991xB power levels are calibrated based on PNA-X's tuned receiver, which means primarily the fundamental is included (for frequencies ≥ 10 MHz). For frequencies < 10 MHz, power levels are calibrated in the factory using a broadband power sensor.

² N995xB power levels are calibrated based on PNA-X's tuned receiver for the entire frequency range.

| Dynamic range (dB) | Frequency | Typical (–10 to 55°C) Preamp off | Nominal Preamp on |
|--------------------|---------------------|-------------------------------------|----------------------|
| N991xB, N993xB | 300 kHz to 2 MHz | 84 | 100 |
| | > 2 MHz to 2.6 GHz | 99 | 112 |
| | > 2.6 to 7 GHz | 98 | 112 |
| | > 7 to 7.5 GHz | 94 | 112 |
| | > 7.5 to 11 GHz | 96 | 112 |
| | > 11 to 16 GHz | 81 | 95 |
| | > 16 to 18 GHz | 86 | 95 |
| | > 18 to 21 GHz | 90 | 95 |
| | > 21 to 23 GHz | 88 | 95 |
| | > 23 to 25 GHz | 78 | 90 |
| | > 25 to 26.5 GHz | 79 | 90 |
| N995xB, N996xB | 500 kHz to 2 MHz | 87 | 107 |
| | > 2 to 100 MHz | 90 | 105 |
| | > 100 MHz to 18 GHz | 96 | 110 |
| | > 18 to 19.5 GHz | 84 | 94 |
| | > 19.5 to 21 GHz | 92 | 103 |
| | > 21 to 23.8 GHz | 82 | 96 |
| | > 23.8 to 26.6 GHz | 75 | 90 |
| | > 26.6 to 36.5 GHz | 96 | 103 |
| | > 36.5 to 37.5 GHz | 91 | 100 |
| | > 37.5 to 41.5 GHz | 91 | 99 |
| | > 41.5 to 46 GHz | 84 | 95 |
| | > 46 to 50 GHz | 77 | 92 |

Real-Time Spectrum Analyzer (RTSA) (Option 350)

The performance listed in this section applies to the real-time spectrum analyzer capabilities available in the following models:

| | |
|--|--|
| FieldFox RF & microwave (combination) analyzers: | N9913B, N9914B, N9915B, N9916B, N9917B, N9918B |
| FieldFox RF & microwave signal analyzers: | N9933B, N9934B, N9935B, N9936B, N9937B, N9938B |
| FieldFox microwave (combination) analyzers: | N9950B, N9951B, N9952B |
| FieldFox microwave signal analyzers: | N9960B, N9961B, N9962B |

See [FieldFox Configuration Guide](#) for option information. Many capabilities listed in this Data Sheet require options.

| | Models | Real-time analysis frequency range ¹ | | |
|---|--|---|------------------|-----------------------|
| N991xB, N993xB | N9913B, N9933B | 1 MHz to 4 GHz | | Usable to 5 kHz |
| | N9914B, N9934B | 1 MHz to 6.5 GHz | | Usable to 5 kHz |
| | N9915B, N9935B | 1 MHz to 9 GHz | | Usable to 5 kHz |
| | N9916B, N9936B | 1 MHz to 14 GHz | | Usable to 5 kHz |
| | N9917B, N9937B | 1 MHz to 18 GHz | | Usable to 5 kHz |
| | N9918B, N9938B | 1 MHz to 26.5 GHz | | Usable to 5 kHz |
| N995xB, N996xB | N9950B, N9960B | 1 MHz to 32 GHz | | Usable to 5 kHz |
| | N9951B, N9961B | 1 MHz to 44 GHz | | Usable to 5 kHz |
| | N9952B, N9962B | 1 MHz to 50 GHz | | Usable to 5 kHz |
| Real-time analysis | | | | |
| Measurements | | Density Spectrum, Spectrogram, Real-time Spectrum | | |
| Maximum real-time bandwidth | | 10 MHz (Standard) | 40 MHz (Opt B04) | 100/120 MHz (Opt B10) |
| Resolution bandwidth (Span dependent, 20 ≤ Span/RBW ≤ 280) | | 1 Hz to 500 kHz | 1 Hz to 2 MHz | 1 Hz to 5 MHz |
| Minimum signal duration with 100% probability of intercept (POI) at full amplitude accuracy | | 9.13 us | 6.13 us | 5.52 us |
| Minimum detectable signal ² | | 11 ns | 11 ns | 47 ns |
| Min. acquisition time (Density Spectrum) | | 20 ms | 20 ms | 20 ms |
| Min. acquisition time (Spectrogram) | | 500 us/div | 500 us/div | 500 us/div |
| Max. acquisition time (Density Spectrum) | | 540 ms | 337 ms | 336 ms |
| Max. acquisition time (Spectrogram) | | 10 s/div | 10 s/div | 10 s/div |
| Spurious-free dynamic range | | 69 dB | 65 dB | 63/62 dB |
| IF flatness | | 0.1 dB (typical) | 0.1 dB (typical) | 0.1 dB (typical) |
| FFT rate | | 190,000 FFT/s | | |
| Number of display points | | 821 | | |
| Traces | | | | |
| Number of traces | 4: all four can be active simultaneously and in different states | | | |
| Detectors | Normal, positive peak, negative peak, sample, average (RMS) | | | |
| States | Clear/write, max. hold, min. hold, average, view, blank | | | |

¹ Performance specified above 1 MHz. Usable down to 5 kHz.

² Minimum detectable pulse width is the shortest pulse width of a pulsed CW signal that will display a peak amplitude that is no worse than 60 dB below the peak amplitude of a CW signal of the same power level for a defined span and auto-coupled RBW.

RTSA (continued)

| Markers | |
|-------------------|--|
| Number of markers | 6 |
| Type | Normal, delta, peak |
| Marker → | Peak, next peak, center frequency, reference level |
| Trigger | |
| Trigger type | Free run, external, video, RF burst, periodic |

I/Q Analyzer (IQA) (Option 351)

The specifications in this section apply to the I/Q analyzer capabilities available in the following models:

FieldFox RF & microwave (combination) analyzers: N9913B, N9914B, N9915B, N9916B, N9917B, N9918B

FieldFox RF & microwave signal analyzers: N9933B, N9934B, N9935B, N9936B, N9937B, N9938B

FieldFox microwave (combination) analyzers: N9950B, N9951B, N9952B

FieldFox microwave signal analyzers: N9960B, N9961B, N9962B

See [FieldFox Configuration Guide](#) for option information. Many capabilities listed in this Data Sheet require options.

| | Models | I/Q analysis frequency range ¹ |
|----------------|----------------|---|
| N991xB, N993xB | N9913B, N9933B | 1 MHz to 4 GHz |
| | N9914B, N9934B | 1 MHz to 6.5 GHz |
| | N9915B, N9935B | 1 MHz to 9 GHz |
| | N9916B, N9936B | 1 MHz to 14 GHz |
| | N9917B, N9937B | 1 MHz to 18 GHz |
| | N9918B, N9938B | 1 MHz to 26.5 GHz |
| N995xB, N996xB | N9950B, N9960B | 1 MHz to 32 GHz |
| | N9951B, N9961B | 1 MHz to 44 GHz |
| | N9952B, N9962B | 1 MHz to 50 GHz |

| Measurements | |
|-----------------------------|--|
| Spectrum (frequency domain) | Magnitude spectrum |
| Waveform (time domain) | RF envelope |
| | I/Q waveform (Dual simultaneous top and bottom windows: I vs. time and Q vs. time) |

Display (multi-domain) User Defined

Set up and display up to 4 simultaneous and multi-domain measurements with any combination of the following:

- Frequency domain: Magnitude spectrum
- Time domain: RF envelope, Q vs. I (polar plot), Phase vs. time, Unwrapped phase vs. time, I vs. time, Q vs. time
- Time summary table showing I/Q capture settings: I/Q capture time, waveform start/stop, Spectrum FFT time

| Measurement Setup | | | |
|------------------------|---|------------------|-------------------|
| I/Q capture parameters | Capture time, sample rate, sample period, capture samples | | |
| Bandwidth options | 10 MHz (Standard) | 40 MHz (Opt B04) | 120 MHz (Opt B10) |
| Frequency span | 10 Hz to 10 MHz | 10 Hz to 40 MHz | 10 Hz to 120 MHz |

¹ Performance specified above 1 MHz. Usable down to 5 kHz.

I/Q Analyzer (IQA) (Option 351) (continued)

| Bandwidth options | 10 MHz (Standard) Typical (-10 to 55°C) | 40 MHz (Opt B04) Typical (-10 to 55°C) | 100/120 MHz (Opt B10) Typical (-10 to 55°C) |
|---|--|---|--|
| N991xB, N993xB | | | |
| IF flatness | | | |
| Magnitude | ± 0.07 dB | ± 0.06 dB | ± 0.11 dB/±0.13 dB |
| Phase deviation from linearity ¹ | 0.43° peak-to-peak 0.15° rms | 1.4° peak-to-peak 0.6° rms | 12.1° peak-to-peak 2°/5° rms |
| Group delay flatness (peak-to-peak) ¹ | 1.35 ns | 0.9 ns | 2.2 ns/3 ns |
| N995xB, N996xB | | | |
| IF flatness | | | |
| Magnitude | ± 0.07 dB | ± 0.06 dB | ± 0.11 dB/± 0.13 dB |
| Phase deviation from linearity ¹ | 0.5° peak-to-peak 0.14° rms | 1.4° peak-to-peak 0.6° rms | 7.9°/10.6° peak-to-peak 3.0°/4.3° rms |
| Group delay flatness (peak-to-peak) ¹ | 1.6 ns | 1.4 ns | 1.9 ns/3 ns |
| Bandwidth options | 10 MHz (Standard) | 40 MHz (Opt B04) | 100/120 MHz (Opt B10) |
| N991xB, N993xB | Nominal | Nominal² | Nominal³ |
| EVM (at center frequency 1 GHz) | | | |
| 5G NR 64 QAM | — | — | 0.70% |
| LTE-A FDD TM3.1 (10 MHz) | 0.50% | 0.50% | 0.50% |
| LTE-A FDD TM3.1 (20 MHz) | — | 0.40% | 0.40% |
| WCDMA TM4 (5 MHz) | 0.70% | 0.70% | 0.70% |
| EVM (at center frequency 2.1 GHz) | | | |
| LTE-A FDD TM3.1 (10 MHz) | 0.70% | 0.70% | 0.70% |
| LTE-A FDD TM3.1 (20 MHz) | — | 0.50% | 0.50% |
| WCDMA TM4 (5 MHz) | 0.75% | 0.75% | 0.75% |
| EVM (at center frequency 3.5 GHz) | | | |
| 5G NR 64 QAM | — | — | 0.85% |
| LTE-A FDD TM3.1 (20 MHz) | — | 0.80% | 0.80% |
| EVM (at center frequency 5.8 GHz) | | | |
| 5G NR 64 QAM | — | — | 1% |
| EVM (at center frequency 24 GHz) | | | |
| 5G NR 64 QAM | — | — | 2% |
| N995xB, N996xB | Nominal | Nominal | Nominal |
| EVM (at center frequency 1 GHz) | | | |
| 5G NR 64 QAM | — | — | 0.80% |
| LTE-A FDD TM3.1 (10 MHz) | 0.50% | 0.50% | 0.50% |
| LTE-A FDD TM3.1 (20 MHz) | — | 0.60% | 0.40% |
| WCDMA TM4 (5 MHz) | 0.60% | 0.70% | 0.70% |
| EVM (at center frequency 2.1 GHz) | | | |
| LTE-A FDD TM3.1 (10 MHz) | 0.65% | 0.65% | 0.65% |
| LTE-A FDD TM3.1 (20 MHz) | — | 0.60% | 0.50% |
| WCDMA TM4 (5 MHz) | 0.80% | 0.75% | 0.75% |

¹ Not guaranteed below 50 MHz

² Applies when fast channel equalization (default) is OFF..

| Bandwidth options | 10 MHz (Standard) | 40 MHz (Opt B04) | 100/120 MHz (Opt B10) |
|-----------------------------------|-------------------|------------------|-----------------------|
| EVM (at center frequency 3.5 GHz) | | | |
| 5G NR 64 QAM | — | — | 0.90% |
| LTE-A FDD TM3.1 (20 MHz) | — | 0.80% | 0.80% |
| EVM (at center frequency 5.8 GHz) | | | |
| 5G NR 64 QAM | — | — | 1% |
| EVM (at center frequency 24 GHz) | | | |
| 5G NR 64 QAM | — | — | 2.1% |
| EVM (at center frequency 28 GHz) | | | |
| 5G NR 64 QAM | — | — | 2.1% |
| EVM (at center frequency 39 GHz) | | | |
| 5G NR 64 QAM | — | — | 2.5% |

| Data acquisition | |
|----------------------------|----------------|
| Total capture memory | 1024 MB |
| Length single I/Q capture | 8 bytes/sample |
| Maximum length I/Q capture | 128 MSa |
| Sample rate (I/Q pairs) | 1.25 x span |
| ADC resolution | 14 bits |
| Maximum I/Q capture time | |
| 120 MHz span | 0.89 s |
| 100 MHz span | 1 s |
| 40 MHz span | 2.6 s |
| 10 MHz span | 10.7 s |
| 1 MHz span | 107 s |
| 100 kHz span | 1073 s |
| 10 kHz span | 10737 s |

IQA (continued)

Dynamic range specifications (wideband path)

| Displayed average noise level (DANL) - (dBm) | | | |
|---|-------------------------------------|------------------------------------|----------------|
| Input terminated, RMS detection, log averaging, 0 dB input attenuation, reference level of -20 dBm, normalized to 1 Hz RBW, measured at non-zero frequency span | | | |
| N991xB, N993xB | Preamp OFF Typical (-10 to 55°C) | Preamp ON Typical (-10 to 55°C) | |
| 9 kHz to 2 MHz | -136 | -151 | |
| ≥ 2 MHz to 120 MHz | -151 | -165 | |
| ≥ 120 MHz to 2.6 GHz | -152 | -165 | |
| ≥ 2.6 to 4.5 GHz | -153 | -164 | |
| ≥ 4.5 to 6.5 GHz | -150 | -163 | |
| ≥ 6.5 to 7.5 GHz | -148 | -161 | |
| ≥ 7.5 to 9 GHz | -147 | -163 | |
| ≥ 9 to 14 GHz | -146 | -161 | |
| ≥ 14 to 16.3 GHz | -143 | -159 | |
| ≥ 16.3 to 18 GHz | -141 | -159 | |
| ≥ 18 to 23 GHz | -141 | -158 | |
| ≥ 23 to 26.5 GHz | -137 | -155 | |
| N995xB, N996xB | Preamp OFF Typical (-10 to 55°C) | Preamp ON Typical (-10 to 55°C) | |
| 9 kHz to 2 MHz | -130 | -142 | |
| ≥ 2 MHz to 2.1 GHz | -152 | -164 | |
| ≥ 2.1 to 7.5 GHz | -152 | -162 | |
| ≥ 7.5 to 13 GHz | -149 | -158 | |
| ≥ 13 to 26.5 GHz | -144 | -154 | |
| ≥ 26.5 to 32 GHz | -152 | -157 | |
| ≥ 32 to 40 GHz | -147 | -154 | |
| ≥ 40 to 44 GHz | -139 | -149 | |
| ≥ 44 to 50 GHz | -131 | -142 | |
| Input related responses (dBc) | | | Nominal |
| Tuned frequency (f) | Excitation frequency | Spur frequency | N991xB, N993xB |
| -30 dBm signal at mixer input (excludes frequencies listed below) | | | -75 |
| f = tuned frequency | | | |
| f > 2.6 GHz to 4 GHz | $f + 10.125 \text{ GHz} / 2$ | f | -65 |
| f > 6 GHz to 7.5 GHz | $f + 2 * 10.125 \text{ GHz}$ | f | -65 |
| f > 7.5 GHz to 16 GHz | $f + 2 * 3.375 \text{ GHz}$ | f | -70 |
| f > 19.5 GHz to 23 GHz | $f - 2 * 3.375 \text{ GHz}$ | f | -75 |
| f > 23 GHz to 26.5 GHz | $f - 2 * 3.375 \text{ GHz}$ | f | -50 |
| f < 7.5 GHz | $f + 1.125 \text{ GHz} / 2$ | f | -75 |
| f > 4 GHz to 12 GHz | $f +/- 2 * 1.125 \text{ GHz}$ | f | -80 |

| Input related responses (dBc) | | | Nominal |
|---|----------------------------|-------------------------------|----------------|
| fOffset = frequency offset of excitation frequency from tuned frequency (f) | | | |
| f < 2.6 GHz, f > 7.5 GHz to 19.5 GHz | f + fOffset | f - fOffset | -70 |
| | f + fOffset | f - 2 * (37.5 MHz - fOffset) | -65 |
| | f + fOffset | f + 2 * (112.5 MHz + fOffset) | -60 |
| | f + fOffset, (fOffset < 0) | f - 6 * (37.5 MHz - fOffset) | -75 |
| | f + fOffset, (fOffset > 0) | f - 6 * (12.5 MHz + fOffset) | -75 |
| f > 2.6 GHz to 7.5 GHz, f > 19.5 GHz | f + fOffset | f - fOffset | -70 |
| | f + fOffset | f + 2 * (37.5 MHz - fOffset) | -65 |
| | f + fOffset | f - 2 * (112.5 MHz + fOffset) | -65 |
| | f + fOffset, (fOffset > 0) | f + 6 * (37.5 MHz - fOffset) | -75 |
| | f + fOffset, (fOffset < 0) | f + 6 * (12.5 MHz + fOffset) | -75 |
| Input related responses (dBc) | | | Nominal |
| Tuned frequency (f) | Excitation frequency | Spur frequency | N995xB, N996XB |
| -30 dBm signal at mixer input (excludes frequencies listed below) | | | -80 |
| f ≥ 2.6 to 7.5 GHz | f + 2 * 10.125 GHz | f | -85 |
| f ≥ 7.5 to 12.3 GHz | f + 2 * 3.375 GHz | f | -80 |
| f ≥ 12.3 to 19.5 GHz | f + 2 * 3.375 GHz | f | -65 |
| f ≥ 19.5 to 26.5 GHz | f - 2 * 3.375 GHz | f | -55 |
| f ≥ 26.5 to 29 GHz | f + 2 * 3.375 GHz | f | -70 |
| f ≥ 29 to 32.5 GHz | f + 2 * 3.375 GHz | f | -55 |
| f ≥ 32.5 to 36 GHz | f - 2 * 3.375 GHz | f | -55 |
| f ≥ 36 to 43 GHz | f - 2 * 3.375 GHz | f | -50 |
| f ≥ 43 to 46.2 GHz | f + 2 * 3.375 GHz | f | -45 |
| f ≥ 46.2 to 50 GHz | f + 2 * 3.375 GHz | f | -45 |
| f < 2.6 GHz | f + 3.375 GHz / 2 | f | -80 |
| f ≥ 2.6 to 7.5 GHz | f + 10.125 GHz / 2 | f | -80 |
| f ≥ 7.5 to 15.7 GHz | f + 3.375 GHz / 2 | f | -85 |
| f ≥ 15.7 to 19.5 GHz | f + 3.375 GHz / 2 | f | -85 |
| f ≥ 19.5 to 26.5 GHz | f - 3.375 GHz / 2 | f | -90 |
| f ≥ 26.5 to 29 GHz | f + 3.375 GHz / 2 | f | -75 |
| f ≥ 29 to 32.5 GHz | f + 3.375 GHz / 2 | f | -80 |
| f ≥ 32.5 to 36 GHz | f - 3.375 GHz / 2 | f | -65 |
| f ≥ 36 to 39.5 GHz | f - 3.375 GHz / 2 | f | -70 |
| f ≥ 39.5 to 43 GHz | f - 3.375 GHz / 2 | f | -70 |
| f ≥ 43 to 46.2 GHz | f + 3.375 GHz / 2 | f | -80 |
| f ≥ 46.2 to 50 GHz | f - 3.375 GHz / 2 | f | -80 |
| f ≥ 26.5 to 32.5 GHz | f + 2 * 1.125 GHz | f | -85 |

| Input related responses (dBc) | | | Nominal |
|---|----------------------------|-------------------------------|----------------|
| Tuned frequency (f) | Excitation frequency | Spur frequency | N995xB, N996XB |
| fOffset = frequency offset of excitation frequency from tuned frequency (f) | | | |
| f < 2.6 GHz, | f + fOffset | f - fOffset | -70 |
| f > 7.5 GHz to 19.5 GHz, | f + fOffset | f - 2 * (37.5 MHz - fOffset) | -65 |
| f > 26.5 GHz to 32.5 GHz, | f + fOffset | f + 2 * (112.5 MHz + fOffset) | -60 |
| f > 43 GHz to 46.2 GHz | f + fOffset, (fOffset < 0) | f - 6 * (37.5 MHz - fOffset) | -75 |
| | f + fOffset, (fOffset > 0) | f - 6 * (12.5 MHz + fOffset) | -75 |
| f > 2.6 GHz to 7.5 GHz, | f + fOffset | f - fOffset | -70 |
| f > 19.5 GHz to 26.5 GHz, | f + fOffset | f + 2 * (37.5 MHz - fOffset) | -65 |
| f > 32.5 GHz to 43 GHz, | f + fOffset | f - 2 * (112.5 MHz + fOffset) | -65 |
| f > 46.2 GHz | f + fOffset, (fOffset > 0) | f + 6 * (37.5 MHz - fOffset) | -75 |
| | f + fOffset, (fOffset < 0) | f + 6 * (12.5 MHz + fOffset) | -75 |
| f < 2.6 GHz, | f + fOffset | f - n * fOffset, | -75 |
| f > 7.5 GHz to 19.5 GHz, | | (n = 1, 2, 3, ...) | |
| f > 26.5 GHz to 32.5 GHz, | f + fOffset | f - 2 * (5.625 MHz | -70 |
| f > 43 GHz to 46.2 GHz | | ± fOffset) | |
| f > 2.6 GHz to 7.5 GHz, | f + fOffset | f - n * fOffset, | -75 |
| f > 19.5 GHz to 26.5 GHz, | | (n = 1, 2, 3, ...) | |
| f > 32.5 GHz to 43 GHz, | f + fOffset | f + 2 * (5.625 MHz | -70 |
| f > 46.2 GHz | | ± fOffset) | |

IQA (continued)

Dynamic range specifications (wideband path) (continued)

| Spur free dynamic range (dB) at 2.4 GHz 2/3 (TOI - DANL) in 1 Hz RBW | | Nominal |
|--|---|-------------|
| N991xB, N993xB, N995xB, N996xB | | > 106 |
| Third order intermodulation distortion (TOI) – (dBm) | | Typical |
| Two -20 dBm signals, 100 kHz spacing at mixer input (-10 to 55°C) | | |
| N991xB, N993xB | 50 MHz to 500 MHz | +5.8 |
| | ≥ 500 to 2 GHz | +7.8 |
| | ≥ 2 to 2.4 GHz | +9.8 |
| | ≥ 2.4 to 2.6 GHz | +8.3 |
| | ≥ 2.6 to 5 GHz | +6.3 |
| | ≥ 5 to 7.5 GHz | +7 |
| | ≥ 7.5 to 10 GHz | +6.8 |
| | ≥ 10 to 18 GHz | +8.5 |
| | ≥ 18 to 26.5 GHz | +11.4 |
| N995xB, N996xB | 50 to 500 MHz | +5.5 |
| | ≥ 500 MHz to 1.4 GHz | +4.6 |
| | ≥ 1.4 to 2.4 GHz | +7.6 |
| | ≥ 2.4 to 2.42 GHz | +7.9 |
| | ≥ 2.42 to 2.6 GHz | +7.7 |
| | ≥ 2.6 to 7.5 GHz | +3.2 |
| | ≥ 7.5 to 9.5 GHz | +0.9 |
| | ≥ 9.5 to 16.3 GHz | +1.1 |
| | ≥ 16.3 to 19.5 GHz | +1.7 |
| | ≥ 19.5 to 23 GHz | +3.9 |
| | ≥ 23 to 26.5 GHz | +3.8 (nom.) |
| | ≥ 26.5 to 32 GHz | -2 (nom.) |
| | ≥ 32 to 36 GHz | -0.4 (nom.) |
| | ≥ 36 to 50 GHz | +2.1 (nom.) |
| Traces | | |
| Number of windows & layout | 1, 2 (top & bottom), 3 (one top, two bottom), or 4 (quad display) | |
| Number of traces | 4, all four traces can be active simultaneously in all windows | |
| States | Clear/write, max hold, min hold, average, view, blank | |
| Markers | | |
| Number of markers | 6 normal + delta pairs | |
| Type | Normal, delta, peak, marker table (up to 6 markers) | |
| Couple markers | On/off (couple markers between traces in different windows) | |
| Marker → | Peak, next peak, center frequency, reference level | |

| Trigger | |
|-----------------------------|---|
| Trigger type | Free run, external, video, RF burst |
| Trigger slope | Positive edge, negative edge |
| Trigger delay | Range: -150 ms to 500 ms |
| | Resolution: 100 ns |
| Auto trigger | Forces a periodic acquisition in the absence of a trigger event |
| | Range: 0 (off) to 30 s |
| Data Storage | |
| Data types | Trace, Trace+state, picture (PNG) |
| I/Q capture data file types | CSV, text (TXT), SDF (compatible with 89600 VSA software), Matlab (MAT) |
| I/Q data formats via SCPI | Raw binary interleaved I/Q data recording, REAL32 (ASCII is default) |

Noise Figure (NF) (Option 356)

The specifications in this section apply to the noise figure measurement capabilities available in the following models:

| | |
|--|--|
| FieldFox RF & microwave (combination) analyzers: | N9913B, N9914B, N9915B, N9916B, N9917B, N9918B |
| FieldFox RF & microwave signal analyzers: | N9933B, N9934B, N9935B, N9936B, N9937B, N9938B |
| FieldFox microwave (combination) analyzers: | N9950B, N9951B, N9952B |
| FieldFox microwave signal analyzers: | N9960B, N9961B, N9962B |

See [FieldFox Configuration Guide](#) for option information. Many capabilities listed in this Data Sheet require options.

No warm-up is required for the instrument specifications.

| | Models | Noise figure analysis frequency range |
|----------------|----------------|---------------------------------------|
| N991xB, N993xB | N9913B, N9933B | 10 MHz to 4 GHz |
| | N9914B, N9934B | 10 MHz to 6.5 GHz |
| | N9915B, N9935B | 10 MHz to 9 GHz |
| | N9916B, N9936B | 10 MHz to 14 GHz |
| | N9917B, N9937B | 10 MHz to 18 GHz |
| | N9918B, N9938B | 10 MHz to 26.5 GHz |
| N995xB, N996xB | N9950B, N9960B | 10 MHz to 32 GHz |
| | N9951B, N9961B | 10 MHz to 44 GHz |
| | N9952B, N9962B | 10 MHz to 50 GHz |

NF (continued)

| Measurements | | | |
|-------------------------------------|--|---|--|
| Noise figure | | Noise figure (F dB) | |
| Noise factor | | Noise figure as a ratio (F) | |
| Gain | | Gain (G dB) | |
| Noise temperature | | Noise temperature in Kelvin (K) | |
| Y-factor | | Y-factor (Y dB) | |
| Setup parameters | | | Supplemental information |
| Noise source | | | Load ENR value(s) |
| DUT type | Amplifier, Downconverter, Upconverter, Multi-stage Converter | | Built-in GUI wizard aids DUT measurement setup |
| Integration | Mode | Auto | Auto Integration: optimizes gain to avoid compression, and measurement time to achieve jitter goal |
| | | Fixed | Fixed Integration: the time per point over which the measurement is averaged is fixed |
| | Jitter goal | | Sets measurement jitter performance target |
| | Max time / point | | Allows user to trade-off jitter vs. measurement time |
| | Jitter warning | | On: displays circles on trace data if jitter goal is exceeded Off (default): disables trace circle indicators |
| Loss compensation | Before DUT, After DUT | | User definable, compensates measurement for loss (dB) before and after DUT |
| Measurement bandwidth (nominal) | | | |
| Range | | 5 MHz (default), 2 MHz, 1 MHz, 300 kHz | |
| Frequency reference | | | |
| | | Refer to spectrum analyzer specifications | |
| Noise figure uncertainty calculator | | | Supplemental information |
| | | | Built-in Based on data from measurement |
| DUT | Mode | Spot | Applies single values uniformly across frequency: Input $ \Gamma $ and Output $ \Gamma $ Γ specification style: Maximum, 95th percentile, 80th percentile, Median, Mean, Fixed Γ distribution: Rayleigh, Fixed, Uniform in Circle |
| | | Table | Applies a table of values vs. frequency: Input $ \Gamma $ and Output $ \Gamma $ Γ specification style: Maximum, 95th percentile, 80th percentile, Median, Mean, Fixed Γ distribution: Rayleigh, Fixed, Uniform in Circle |
| Preamplifier | Mode | Spot | Applies single values uniformly across frequency Input $ \Gamma $ and Output $ \Gamma $ Γ specification style: Maximum, 95th percentile, 80th percentile, Median, Mean, Fixed Γ distribution: Rayleigh, Fixed, Uniform in Circle |
| | | Table | Applies a table of values vs. frequency: Input $ \Gamma $ and Output $ \Gamma $ Γ specification style: Maximum, 95th percentile, 80th percentile, Median, Mean, Fixed Γ distribution: Rayleigh, Fixed, Uniform in Circle |

NF (continued)

| Noise figure uncertainty calculator | | | Supplemental information |
|--|------------------|-------|---|
| | | | Built-in Based on data from measurement |
| Noise source | ENR Mode | Spot | Applies single values uniformly across frequency: ENR (dB), ENR Uncertainty (dB), On $ \Gamma $, Off $ \Gamma $, ENR Uncertainty Confidence (SD) Γ specification style: Maximum, 95th percentile, 80th percentile, Median, Mean, Fixed Γ distribution: Rayleigh, Fixed, Uniform in Circle |
| | | Table | Applies a table of values vs. frequency: ENR (dB), ENR Uncertainty (dB), On $ \Gamma $, Off $ \Gamma $, ENR Uncertainty Confidence (SD) Γ specification style: Maximum, 95th percentile, 80th percentile, Median, Mean, Fixed Γ distribution: Rayleigh, Fixed, Uniform in Circle |
| Uncertainty contributions | Jitter | | Random independent events (fluctuations) within the bandwidth occurring during the noise measurement |
| | ENR | | Excess noise ratio of the hot noise source connected to the DUT during the measurement |
| | Mismatch | | Errors resulting from reflections due to impedance differences between components |
| | User calibration | | Errors due to the optional user calibration which is performed with a defined noise standard (ENR source) connected to the input of an LNA, and fixturing/cables used in the DUT measurement, and port 2 of the FieldFox |
| Uncertainty coverage | | | User settable, uncertainty coverage can be set to 1σ (80%), 2σ (95% default), 3σ (99.5%) |
| Uncertainty bars | | | Displays vertical bars representing the calculated measurement uncertainty overlaid on the trace data |
| Loss compensation | Before DUT | | User definable, single value, compensates measurement for insertion loss (dB) before DUT |
| | After DUT | | User definable, single value, compensates measurement for loss (dB) after DUT |
| Instrument match | | | VSWR values are preloaded and automatically applied for instrument and U7227A/C/F or U7228A/C/F preamplifiers |
| Calibration options | | | |
| Receiver calibration | | | Uses noise source to calibrate FieldFox receiver gain bandwidth |
| User calibration with external U7227A/C/F or U7228A/C/F preamplifier | | | Optional calibration performs hot/cold measurement with external preamplifier; applies receiver and user calibrations |

NF (continued)

| Noise figure ¹ | | Internal preamplifier ON | Internal preamplifier ON + U7227/8A | Internal preamplifier ON + U7227/8C |
|---------------------------|----------------------|-----------------------------|---|---|
| | Frequency | (dB) | (dB) | (dB) |
| N991xB, N993xB | 10 to 100 MHz | 13.5 | 6.1 | — |
| | ≥ 100 MHz to 2.1 GHz | 13.5 | 5.6 | 6.6 |
| | ≥ 2.1 to 2.6 GHz | 16.5 | 5.9 | 6.9 |
| | ≥ 2.6 to 4 GHz | 14.5 | 5.5 | 6.6 |
| | ≥ 4 to 4.5 GHz | 14.5 | — | 5.7 |
| | ≥ 4.5 to 6 GHz | 16.5 | — | 6.0 |
| | ≥ 6 to 7.5 GHz | 16.5 | — | 5.2 |
| | ≥ 7.5 to 13 GHz | 15.5 | — | 4.9 |
| | ≥ 13 to 18 GHz | 18.5 | — | 5.2 |
| | ≥ 18 to 22 GHz | 19.5 | — | 5.9 |
| | ≥ 22 to 25 GHz | 21.5 | — | 6.1 |
| | ≥ 25 to 26.5 GHz | 24.5 | — | 6.7 |
| Noise figure ¹ | | Internal preamplifier ON | Internal preamplifier ON + U7227/8F ² | |
| | Frequency | (dB) | (dB) | |
| N991xB, N993xB | ≥ 2.1 to 2.6 GHz | 16.5 | 10.4 | |
| | ≥ 2.6 to 4 GHz | 14.5 | 8.4 | |
| | ≥ 4 to 4.5 GHz | 14.5 | 8.3 | |
| | ≥ 4.5 to 7.5 GHz | 16.5 | 8.5 | |
| | ≥ 7.5 to 13 GHz | 15.5 | 8.4 | |
| | ≥ 13 to 18 GHz | 18.5 | 8.5 | |
| | ≥ 18 to 22 GHz | 19.5 | 8.5 | |
| | ≥ 22 to 25 GHz | 21.5 | 8.6 | |
| | ≥ 25 to 26.5 GHz | 24.5 | 9.0 | |

¹ Noise figure (NF) = DANL - (-173.98 - 2.51) dB
Nominal calculation is based on spectrum analyzer (SA) displayed average noise level (DANL) specification (dBm) stated as input terminated, RMS detection, log averaging, 0 dB input attenuation, reference level of -20 dBm, normalized to 1 Hz RBW.

Noise figure (NF) = D - (K - L), where D is the DANL (displayed average noise level) specification, K is kTB (-173.98 dBm in a 1 Hz bandwidth at 290 K), and L is 2.51 dB (the effect of log averaging used in DANL verifications).

² U7227/8F maximum frequency is 50 GHz; can be used with N991xB or N993xB up to maximum frequency of 26.5 GHz.

| Noise figure ¹ | | Internal preamplifier ON | Internal preamplifier ON + U7227/8A | Internal preamplifier ON + U7227/8C |
|---------------------------|----------------------|-----------------------------|--|---|
| | Frequency | (dB) | (dB) | (dB) |
| N995xB, N996xB | 10 to 100 MHz | 13.5 | 6.1 | — |
| | ≥ 100 MHz to 2.1 GHz | 13.5 | 5.5 | 6.5 |
| | ≥ 2.1 to 4 GHz | 15.5 | 5.9 | 6.8 |
| | ≥ 4 to 6 GHz | 15.5 | — | 5.9 |
| | ≥ 6 to 7.5 GHz | 15.5 | — | 4.9 |
| | ≥ 7.5 to 13 GHz | 19.5 | — | 6.1 |
| | ≥ 13 to 18 GHz | 23.5 | — | 8.1 |
| | ≥ 18 to 26.5 GHz | 23.5 | — | 7.1 |
| | ≥ 26.5 to 32 GHz | 20.5 | — | — |
| | ≥ 32 to 40 GHz | 22.5 | — | — |
| | ≥ 40 to 44 GHz | 27.5 | — | — |
| | ≥ 44 to 50 GHz | 34.5 | — | — |
| Noise figure ¹ | | Internal preamplifier ON | Internal preamplifier ON + U7227/8F | |
| | Frequency | (dB) | (dB) | |
| N995xB, N996xB | ≥ 2.1 to 4 GHz | 15.5 | 10.3 | |
| | ≥ 4 to 6 GHz | 15.5 | 8.4 | |
| | ≥ 6 to 7.5 GHz | 15.5 | 8.4 | |
| | ≥ 7.5 to 13 GHz | 19.5 | 9.0 | |
| | ≥ 13 to 18 GHz | 23.5 | 10.1 | |
| | ≥ 18 to 26.5 GHz | 23.5 | 10.1 | |
| | ≥ 26.5 to 32 GHz | 20.5 | 9.2 | |
| | ≥ 32 to 40 GHz | 22.5 | 9.8 | |
| | ≥ 40 to 44 GHz | 27.5 | 9.7 | |
| | ≥ 44 to 50 GHz | 34.5 | 11.9 | |

¹ Noise figure (NF) = DANL - (-173.98 - 2.51) dB
Nominal calculation is based on spectrum analyzer (SA) displayed average noise level (DANL) specification (dBm) stated as input terminated, RMS detection, log averaging, 0 dB input attenuation, reference level of -20 dBm, normalized to 1 Hz RBW.

Noise figure (NF) = D - (K - L), where D is the DANL (displayed average noise level) specification, K is kTB (-173.98 dBm in a 1 Hz bandwidth at 290 K), and L is 2.51 dB (the effect of log averaging used in DANL verifications).

NF (continued)

| External preamplifier | | | |
|---|--|---|--|
| Specification | U7227/8A | U7227/8C | U7227/8F |
| Frequency | 10 MHz to 4 GHz | 100 MHz to 26.5 GHz | 2 GHz to 50 GHz |
| Noise figure (dB) | 10 MHz to 100 MHz: < 5.5 100 MHz to 4 GHz: < 5 | 100 MHz to 4 GHz: < 6 4 to 6 GHz: < 5 6 to 18 GHz: < 4 18 to 26.5 GHz: < 5 | 2 to 4 GHz: < 10 4 to 40 GHz: < 8 40 to 44 GHz: < 9 44 to 50 GHz: < 10 |
| Gain (dB) | 10 to 100 MHz: > 16 100 MHz to 4 GHz: > 0.5F + 17 | 100 MHz to 26.5 GHz: > 16.1 + 0.26F | 2 GHz to 50 GHz: > 16.5 + 0.23F |
| RF connector | 3.5 mm (m) | 3.5 mm (m) | 2.4 mm (m) |
| Noise source | | | |
| Model | Frequency range | | ENR |
| 346A | 10 MHz to 18 GHz | | 5 to 7 dB |
| 346B | 10 MHz to 18 GHz | | 14 to 16 dB |
| 346C | 10 MHz to 26.5 GHz | | 12 to 17 dB |
| 346CK40 | 1 GHz to 40 GHz | | 3 to 14 dB |
| 346CK01 | 1 GHz to 50 GHz | | 7 to 20 dB |
| Noise source setup | | Supplemental info | |
| ENR Mode | Spot | Single ENR value (not frequency dependent) (default: 15 dB) | |
| | Table | Applies table of ENR values vs. frequency Create, save, recall, edit ENR tables File type: .ENR | |
| T cold | Auto (default) or Manual | | Noise temperature of cold noise standard connected to DUT during the measurement |
| Noise source setup | | Supplemental info | |
| Connector type | SMB (m) | | DC bias requires accessory N9910X-713 BNC to SMB cable |
| Control voltage drive level | 28 ± 1 V | | |
| Operating temperature | 0 to 55°C | | |
| Sweep | | | |
| Number of points | 11 (default), 21, 51, 101, 201, 401, 601, 801, 1001 | | |
| Sweep mode | Continuous or single | | |
| DUT profiles available (built-in GUI wizard aids DUT measurement setup) | | | |
| Amplifier | Includes any non-frequency-converting device | | |
| Downconverter | Frequency context can be set to RF or IF; sideband can be set to LSB, USB, DSB | | |
| Upconverter | Frequency context can be set to RF or IF; sideband can be set to LSB, USB, DSB | | |
| Multi-stage converter | Frequency context can be set to RF or IF | | |

NF (continued)

| Display formats | |
|-------------------|--|
| Number of traces | Two traces available |
| Display formats | Single-trace |
| | Dual-trace overlay (both traces on one graticule) |
| | Dual-trace split (each trace on separate top and bottom graticules) |
| Display data | Display data, memory, data and memory |
| Trace memory | One memory trace per data trace, total of 2 memory traces |
| Limit lines | Upper and lower for each trace |
| Markers | |
| Number of markers | 6 |
| Type | Normal, Delta, Marker Table |
| Marker table | Display 6 markers |
| Marker to → | Peak, Next Peak, Peak Left, Peak Right, Center Frequency, Reference Level, Minimum, Target |
| Data storage | |
| Data types | Trace, Trace+State, Picture (PNG), CSV |

The performance listed in these sections below applies to the spectrum analyzer IF output, preamplifier, interference analyzer and spectrogram, channel scanner and 89600 VSA software capabilities available in the following models:

| | |
|--|--|
| FieldFox RF & microwave (combination) analyzers: | N9913B, N9914B, N9915B, N9916B, N9917B, N9918B |
| FieldFox RF & microwave signal analyzers: | N9933B, N9934B, N9935B, N9936B, N9937B, N9938B |
| FieldFox microwave (combination) analyzers | N9950B, N9951B, N9952B |
| FieldFox microwave signal analyzers | N9960B, N9961B, N9962B |

See [FieldFox Configuration Guide](#) for option information. Many capabilities listed in this Data Sheet require options.

Spectrum Analyzer IF Output

| Spectrum analyzer mode, zero span, IF output settings ¹ | | | |
|--|----------------------|------------------|-------------------|
| Bandwidth options | 10 MHz (Standard) | 40 MHz (Opt B04) | 120 MHz (Opt B10) |
| IF output mode (Narrow) | | | |
| Center frequency | 33.75 MHz | 33.75 MHz | 33.75 MHz |
| IF bandwidth | 10 MHz | 10 MHz | 10 MHz |
| IF output mode (Wide) | | | |
| Center frequency | — | 225 MHz | 225 MHz |
| IF bandwidth | — | 100 MHz | 100 MHz |
| Conversion gain ² | Center frequency | Narrowband path | Wideband path |
| N991xB, N993xB | < 120 MHz | 2 dB to -1 dB | 6 dB to 3 dB |
| | ≥ 120 MHz to 7.5 GHz | 6 dB to -2 dB | 13 dB to 4 dB |

¹ Measurements are uncalibrated in IF output mode.

² RF input to SA output with -20 dBm input power, 0 dB attenuation, and preamp off.

| Spectrum analyzer mode, zero span, IF output settings ¹ | | | |
|--|-----------------------|-----------------|----------------|
| | ≥ 7.5 GHz to 26.5 GHz | 6 dB to -6 dB | 13 dB to 0 dB |
| Conversion gain ¹ | Center frequency | Narrowband path | Wideband path |
| N995xB, N996xB | < 120 MHz | 7 dB to -3 dB | 16 dB to 0 dB |
| | ≥ 120 MHz to 7.5 GHz | 6 dB to -14 dB | 13 dB to 4 dB |
| | ≥ 7.5 GHz to 26.5 GHz | 10 dB to -6 dB | 17 dB to 6 dB |
| | ≥ 26.5 GHz to 40 GHz | 10 dB to -6 dB | 20 dB to 8 dB |
| | ≥ 40 GHz to 50 GHz | 5 dB to -21 dB | 13 dB to -9 dB |
| Connector | SMB male | | |

Preamplifier (Option 235)

| Nominal | | |
|-----------------|--|---------------------------|
| Frequency range | Full band (9 kHz to maximum frequency of instrument) | |
| Gain | N991xB, N993xB | +20 dB, 9 kHz to 26.5 GHz |
| | N995xB, N996xB | +15 dB, 9 kHz to 50 GHz |

Interference Analyzer and Spectrogram (Option 236)

| | Description |
|------------------------------|--|
| Spectrogram display | Overlay, full screen, top, or bottom with active trace |
| Waterfall angle | Moderate, steep, gradual, wide angle |
| Markers | Time, delta time |
| Trace playback and recording | <ul style="list-style-type: none"> -Record all spectrum analyzer measurements -Playback recorded data using FieldFox -Frequency mask trigger allows recording to occur upon trigger -Store data internally or USB or SD card |

Channel Scanner (Option 312)

| | Description |
|------------------------------|--|
| Scan Mode | Range or custom list |
| Display Type | Bar chart vertical, bar chart horizontal, channel power, strip chart, chart overlay, scan & listen |
| Data logging mode | Time with geo tagging |
| Trace playback and recording | <ul style="list-style-type: none"> -Record channel power measurement -Playback recorded data using FieldFox -Store data internally or USB or SD card in .csv or .kml format -Data in .kml format can be exported to Google Earth |

¹ RF input to SA output with -20 dBm input power, 0 dB attenuation, and preamp off.

89600 VSA Software

| Bandwidth options | 10 MHz (Standard) Nominal | 40 MHz (Opt B04) Nominal ¹ | 120 MHz (Opt B10) Nominal ¹ |
|-----------------------------------|------------------------------|--|---|
| N991xB, N993xB | | | |
| EVM (at center frequency 1 GHz) | | | |
| 5G NR 64 QAM | — | — | 0.70% |
| LTE-A FDD TM3.1 (10 MHz) | 0.50% | 0.50% | 0.50% |
| LTE-A FDD TM3.1 (20 MHz) | — | 0.40% | 0.40% |
| WCDMA TM4 (5 MHz) | 0.70% | 0.70% | 0.70% |
| EVM (at center frequency 2.1 GHz) | | | |
| LTE-A FDD TM3.1 (10 MHz) | 0.70% | 0.70% | 0.70% |
| LTE-A FDD TM3.1 (20 MHz) | — | 0.50% | 0.50% |
| WCDMA TM4 (5 MHz) | 0.75% | 0.75% | 0.75% |
| EVM (at center frequency 3.5 GHz) | | | |
| 5G NR 64 QAM | — | — | 0.85% |
| LTE-A FDD TM3.1 (20 MHz) | — | 0.80% | 0.80% |
| EVM (at center frequency 5.8 GHz) | | | |
| 5G NR 64 QAM | — | — | 1% |
| EVM (at center frequency 24 GHz) | | | |
| 5G NR 64 QAM | — | — | 2% |
| N995xB, N996xB | | | |
| EVM (at center frequency 1 GHz) | | | |
| 5G NR 64 QAM | — | — | 0.80% |
| LTE-A FDD TM3.1 (10 MHz) | 0.50% | 0.50% | 0.50% |
| LTE-A FDD TM3.1 (20 MHz) | — | 0.60% | 0.40% |
| WCDMA TM4 (5 MHz) | 0.60% | 0.70% | 0.70% |
| EVM (at center frequency 2.1 GHz) | | | |
| LTE-A FDD TM3.1 (10 MHz) | 0.65% | 0.65% | 0.65% |
| LTE-A FDD TM3.1 (20 MHz) | — | 0.60% | 0.50% |
| WCDMA TM4 (5 MHz) | 0.80% | 0.75% | 0.75% |
| EVM (at center frequency 3.5 GHz) | | | |
| 5G NR 64 QAM | — | — | 0.90% |
| LTE-A FDD TM3.1 (20 MHz) | — | 0.80% | 0.80% |
| EVM (at center frequency 5.8 GHz) | | | |
| 5G NR 64 QAM | — | — | 1% |
| EVM (at center frequency 24 GHz) | | | |
| 5G NR 64 QAM | — | — | 2.1% |
| EVM (at center frequency 28 GHz) | | | |
| 5G NR 64 QAM | — | — | 2.1% |
| EVM (at center frequency 39 GHz) | | | |
| 5G NR 64 QAM | — | — | 2.5% |

¹ Applies when fast channel equalization (default) is OFF.

Over-the-Air (OTA) LTE FDD/TDD (Option 370/371)

The performance listed in this section applies to the OTA analyzer capabilities available in the following models:

| | |
|--|--|
| FieldFox RF & microwave (combination) analyzers: | N9913B, N9914B, N9915B, N9916B, N9917B, N9918B |
| FieldFox RF & microwave signal analyzers: | N9933B, N9934B, N9935B, N9936B, N9937B, N9938B |
| FieldFox microwave (combination) analyzers | N9950B, N9951B, N9952B |
| FieldFox microwave signal analyzers | N9960B, N9961B, N9962B |

See [FieldFox Configuration Guide](#) for option information. Many capabilities listed in this Data Sheet require options.

| | Models | OTA analysis frequency range ¹ |
|----------------|----------------|---|
| N991xB, N993xB | N9913B, N9933B | 1 MHz to 4 GHz |
| | N9914B, N9934B | 1 MHz to 6.5 GHz |
| | N9915B, N9935B | 1 MHz to 9 GHz |
| | N9916B, N9936B | 1 MHz to 14 GHz |
| | N9917B, N9937B | 1 MHz to 18 GHz |
| | N9918B, N9938B | 1 MHz to 26.5 GHz |
| N995xB, N996xB | N9950B, N9960B | 1 MHz to 32 GHz |
| | N9951B, N9961B | 1 MHz to 44 GHz |
| | N9952B, N9962B | 1 MHz to 50 GHz |

LTE FDD/TDD Over-the-Air (OTA) Measurements²

| | |
|-------------------|---|
| Cell scan results | Frequency PCI (Physical Cell Identifier) (C/S/G) RSRP (Reference Signal Received Power) (dBm) RSRQ (Reference Signal Received Quality) (dB) RSSI (Reference Signal Strength Indicator) (dBm) PSS (Primary Synchronization Signal) (dBm) SSS (Secondary Synchronization Signal) (dBm) SINR (Signal to Interference & Noise Ratio) (dB) Freq Err (Frequency Error) (Hz) |
| Data formats | User can set up and display 1, 2, 3 or 4 simultaneous measurements of key performance indicators (KPI's) for any component carrier (CC0 through CC4), up to 5 carriers, in any combination of the following: |
| Table | Cell scan numeric results (for up to 6 cell sites (ID's) including PCI (C/S/G), RSRP, RSRQ, RSSI, PSS, SSS, SINR, Freq Err |
| Bar chart | Vertical power bar graph of selectable cell scan results for up to 6 cell sites with adjustable color "heat" amplitude scale |
| Spectrum | Magnitude spectrum frequency domain (fixed span) |
| Strip chart | Magnitude of selectable cell scan results graphed over time |

¹ Performance specified above 1 MHz. Usable down to 5 kHz.

² For center frequency signals above 1 GHz, the built-in GPS receiver (Option 307) is highly recommended or locking to any 10 MHz frequency reference. When locked to GPS as the frequency reference, this provides accuracy of ± 0.01 ppm (spec).

OTA LTE FDD/TDD (continued)

| Setup parameters | |
|----------------------|---|
| Component carrier | CC0 to CC4 |
| Channel table | Sets frequency based on band and channels |
| Favorites list | Save up to 6 favorite cellular bands/channels |
| Window configuration | Any combination of 1, 2, 3, or all 4 windows can be displayed simultaneously: 1, 2 (top & bottom), 3 (one top, two bottom), or 4 (quad display) |
| Trigger | |
| Trigger type | Free run, external |
| Record / Playback | |
| Data logging | Record, recall and playback data for all component carrier(s) |
| Record settings | Meas Interval, Interval type (time or distance), time interval, distance interval |
| Supported file types | CSV, KML |
| Saving data | Save/recall recorded data logs to/from internal memory or external USB or SD card |

Over-the-Air (OTA) 5G TF (Option 377)

The performance listed in this section applies to the OTA analyzer capabilities available in the following models:

| | |
|--|--|
| FieldFox RF & microwave (combination) analyzers: | N9913B, N9914B, N9915B, N9916B, N9917B, N9918B |
| FieldFox RF & microwave signal analyzers: | N9933B, N9934B, N9935B, N9936B, N9937B, N9938B |
| FieldFox microwave (combination) analyzers: | N9950B, N9951B, N9952B |
| FieldFox microwave signal analyzers: | N9960B, N9961B, N9962B |

See [FieldFox Configuration Guide](#) for option information. Many capabilities listed in this Data Sheet require options.

| | Models | OTA analysis frequency range ¹ |
|-----------------------------|----------------|---|
| N991xB, N993xB ² | N9913B, N9933B | 1 MHz to 4 GHz |
| | N9914B, N9934B | 1 MHz to 6.5 GHz |
| | N9915B, N9935B | 1 MHz to 9 GHz |
| | N9916B, N9936B | 1 MHz to 14 GHz |
| | N9917B, N9937B | 1 MHz to 18 GHz |
| | N9918B, N9938B | 1 MHz to 26.5 GHz |
| N995xB, N996xB | N9950B, N9960B | 1 MHz to 32 GHz |
| | N9951B, N9961B | 1 MHz to 44 GHz |
| | N9952B, N9962B | 1 MHz to 50 GHz |

5G TF Over-the-Air (OTA) Measurements³

| | |
|-------------------|--|
| Cell scan results | Center frequency PCI (Physical Cell Identifier) |
|-------------------|--|

¹ Performance specified above 1 MHz. Usable down to 5 kHz.

² Requires external mixer to down convert millimeter wave frequency to intermediate frequency (IF).

³ For center frequency signals above 1 GHz, the built-in GPS receiver (Option 307) is highly recommended or locking to any 10 MHz frequency reference. When locked to GPS as the frequency reference, this provides accuracy of ± 0.01 ppm (spec).

| 5G TF Over-the-Air (OTA) Measurements ³ | |
|--|---|
| | Power (Channel Power) (dBm) PSS (Primary Synchronization Signal) (dBm) SSS (Secondary Synchronization Signal) (dBm) Sync Corr (Sync Correlation) (%) |
| | |
| Data formats | User can setup and display 1, 2, 3 or 4 simultaneous measurements of key performance indicators (KPI's) for any component carrier (CC0 through CC7), up to 8 carriers, in any combination of the following: |
| Table | Cell scan numeric results (for up to 6 cell sites (ID's) including Cell ID, Channel Power, PSS, SSS, Sync Corr |
| Bar chart | Vertical power bar graph of selectable cell scan results for up to 8 cell sites with adjustable color "heat" amplitude scale |
| Spectrum | Magnitude spectrum frequency domain (fixed span) |
| Strip chart | Magnitude of selectable cell scan results graphed over time |
| Signal bandwidth | Up to 10 MHz |
| Setup parameters | |
| Component carrier | CC0 to CC7 |
| Channel table | Sets frequency based on band and channel |
| Window configuration | Any combination of 1, 2, 3, or all 4 windows can be displayed simultaneously: 1, 2 (top & bottom), 3 (one top, two bottom), or 4 (quad display) |
| Trigger | |
| Trigger type | Free run, external |
| Record / Playback | |
| Data logging | Record, recall and playback data for all component carrier(s) |
| Record settings | Meas Interval, Interval type (time or distance), time interval, distance interval |
| Supported file types | CSV, KML |
| Saving data | Save/recall recorded data logs to/from internal memory or external USB or SD card |

OTA 5GTF (continued)

Over-the-Air (OTA) 5G NR (Option 378)

The performance listed in this section applies to the OTA analyzer capabilities available in the following models:

| | |
|--|--|
| FieldFox RF & microwave (combination) analyzers: | N9913B, N9914B, N9915B, N9916B, N9917B, N9918B |
| FieldFox RF & microwave signal analyzers: | N9933B, N9934B, N9935B, N9936B, N9937B, N9938B |
| FieldFox microwave (combination) analyzers: | N9950B, N9951B, N9952B |
| FieldFox microwave signal analyzers: | N9960B, N9961B, N9962B |

See [FieldFox Configuration Guide](#) for option information. Many capabilities listed in this Data Sheet require options.

| | Models | OTA analysis frequency range ¹ |
|----------------|----------------|---|
| N991xB, N993xB | N9913B, N9933B | 1 MHz to 4 GHz |
| | N9914B, N9934B | 1 MHz to 6.5 GHz |
| | N9915B, N9935B | 1 MHz to 9 GHz |
| | N9916B, N9936B | 1 MHz to 14 GHz |
| | N9917B, N9937B | 1 MHz to 18 GHz |
| | N9918B, N9938B | 1 MHz to 26.5 GHz |
| N995xB, N996xB | N9950B, N9960B | 1 MHz to 32 GHz |
| | N9951B, N9961B | 1 MHz to 44 GHz |
| | N9952B, N9962B | 1 MHz to 50 MHz |

¹ Performance specified above 1 MHz. Usable down to 5 kHz.

OTA 5G NR (continued)

| 5G NR Measurements ¹ | |
|---|--|
| 5G NR Over-the-Air (OTA) Cell scan results | Frequency PCI (Physical Cell Identifier) (C-S-G) (Cell ID-Sector ID-Group ID) SSB Index (Synchronization Signal Block Index) SS-RSRP (Synchronization Signal Reference Signal Received Power) (dBm) SS-RSRQ (Synchronization Signal Reference Signal Received Quality) (dB) RSSI (Received Signal Strength Indicator) (dBm) SS-SINR (Synchronization Signal Signal-to-Noise and Interference Ratio) (dB) PSS (Primary Synchronization Signal) (dBm) SSS (Secondary Synchronization Signal) (dBm) PBCH DMRS (Physical Broadcast Channel Demodulation Reference Signal) (dBm) Freq Err (Frequency Error) (Hz) |
| 5G NR EVM Conducted Cell scan results | Frequency PCI (Physical Cell Identifier) SSB Numerology (Synchronization Signal Block Numerology) SSB Case (Synchronization Signal Block Case) SSB Lmax (Maximum Number SSB's within SSB Set, Lmax = 4, 8 or 64) SSB Periodicity (ms) SSB RB Offset (Synchronization Signal Block Resource Block Offset) SSB SC Offset (Synchronization Signal Block Subcarrier Offset) SSB Delta Center (Synchronization Signal Block Delta Center) (kHz) ² Sync Corr (Synchronization Correlation) (%) Channel Power (dBm) Freq Err (Frequency Error) (Hz) Time Offset (ms) PSS EVM (Primary Synchronization Signal EVM) (%rms) SSS EVM (Secondary Synchronization Signal EVM) (%rms) PBCH EVM (Physical Broadcast Channel EVM) (%rms) PBCH DMRS EVM (Physical Broadcast Channel Demodulation Reference Signal EVM) (%rms) Composite EVM (%rms) SS-RSRP (Synchronization Signal Reference Signal Received Power) (dBm) SS-RSRQ (Synchronization Signal Reference Signal Received Quality) (dB) RSSI (Reference Signal Strength Indicator) (dBm) PSS Power (Primary Synchronization Signal Power) (dBm) SSS Power (Secondary Synchronization Signal Power) (dBm) PBCH Power (Physical Broadcast Channel Power) (dBm) PCBCH DMRS Power (Physical Broadcast Channel Demodulation Reference Signal Power) (dBm) |
| Signal bandwidth | Up to 100 MHz (Requires Option B10) |
| Component carrier | CC0 to CC7 (5G NR over-the-air (OTA) measurements) CC0 to CC4 (5G NR conducted EVM measurements) |

¹ For center frequency signals above 1 GHz, the built-in GPS receiver (Option 307) is highly recommended or locking to any 10 MHz frequency reference. When locked to GPS as the frequency reference, this provides accuracy of ± 0.01 ppm (spec).

² Synchronization Signal Block Subcarrier Offset is the offset of the Synchronization Signal Block from the center of the channel.

| 5G NR Measurements ¹ | |
|---------------------------------|--|
| Data formats | User can set up and display 1, 2, 3 or 4 simultaneous measurements of key performance indicators (KPI's) for any component carrier, in any combination of the following ¹ : |
| Table | Cell scan numeric results (for up to 6 cell sites (ID's) |
| Bar chart | Vertical power bar graph of selectable cell scan results for up to 6 cell sites with adjustable color "heat" amplitude scale |
| Spectrum | Magnitude spectrum frequency domain (fixed span) |
| Strip chart | Magnitude of selectable cell scan results graphed over time |
| Window configuration | Any combination of 1, 2, 3, or all 4 windows can be displayed simultaneously: 1, 2 (top & bottom), 3 (one top, two bottom), or 4 (quad display) |
| Setup parameters | |
| 5G NR Over-the-Air (OTA) | |
| Frequency error threshold | 0 Hz to 7.5 kHz ² |
| Subcarrier spacing | 15 kHz, 30 kHz, 120 kHz, 240 kHz |
| SSB case | Auto, A, B, C, D, E |
| Lmax | Auto, 4, 8, 64 |
| Capture length | 4, 8, 16, 24, 32 or 40 frames |
| Drive speed | Low, medium, high |
| SS Meas DMRS | Off, On |
| Phase compensation | Off, On |
| EMF Measurement | Off, On |
| EMF Units | dBµV/m, V/m |
| 5G NR Conducted EVM | |
| Cell ID | Auto, Manual |
| Bandwidth | FR1: 5, 10, 15, 20, 25, 30, 40, 50, 60, 70, 80, 90, 100 MHz FR2: 50, 100 MHz |
| Subcarrier spacing | 15 kHz, 30 kHz, 120 kHz, 240 kHz |
| Export results | Exports SSB center frequency, SSB subcarrier spacing, SSB Case and SSB Lmax to 5G NR OTA setup |
| Trigger | |
| Trigger type | Free run, external, periodic trigger |
| Record / Playback | |
| Data logging | Record, recall and playback data for all component carrier(s) |
| Record settings | Meas Interval, Interval type (time or distance), time interval, distance interval |
| Supported file types | CSV, KML |
| Saving data | Save/recall recorded data logs to/from internal memory or external USB or SD card |

¹ You can also display the results from multiple component carriers on the table, bar chart, and strip chart displays.

² The frequency error threshold is dependent on the SCS - freq err threshold = +/- 1/4 * SCS (e.g. for 15 kHz, freq err threshold = 3.75 kHz).

Indoor and Outdoor Mapping (Option 352)

The performance listed in this section applies to the indoor and outdoor mapping capabilities available in the following models:

| | |
|--|--|
| FieldFox RF & microwave (combination) analyzers: | N9913B, N9914B, N9915B, N9916B, N9917B, N9918B |
| FieldFox RF & microwave signal analyzers: | N9933B, N9934B, N9935B, N9936B, N9937B, N9938B |
| FieldFox microwave (combination) analyzers: | N9950B, N9951B, N9952B |
| FieldFox microwave signal analyzers: | N9960B, N9961B, N9962B |

See [FieldFox Configuration Guide](#) for option information. Many capabilities listed in this Data Sheet require options.

Option 352 adds indoor and outdoor mapping capability to FieldFox analyzers, so that FieldFox can import maps from OpenStreetMap (OSM) for data collection and data plotting to the map directly on the FieldFox instrument display. The FieldFox indoor and outdoor mapping feature resides at the System level and the mapping capability can be enabled within the following modes:

Channel Scanner (Option 312)

Phased Array Antenna Support (Option 360)

Over-the-Air (OTA) LTE FDD/TDD (Option 370/371)

Over-the-Air (OTA) 5GTF (Option 377)

Over-the-Air (OTA) 5G NR (Option 378)

Indoor and outdoor mapping (Option 352) requirements:

Spectrum analyzer mode (Option 233 on N991xB, default mode on N993xB)

GPS receiver (Option 307), required for outdoor mapping

OSM maps can be saved to the FieldFox internal memory, SD card or USB drive. This can be done via a direct wired LAN connection or OSM maps can be downloaded and saved to FieldFox using the [FieldFox Map Support Tool](#).

| | Description |
|----------------------|-----------------------------|
| Map coordinates | Latitude, longitude |
| Map zoom levels | 4 to 17 |
| Map icons | Flag, point, line |
| Map labels | On, Off |
| Map panorama | North, South, East, West |
| Data logging | Record, recall and playback |
| Indoor map file type | PNG |

Using a direct wired LAN connection, FieldFox will automatically access OSM once location coordinates (latitude and longitude) and zoom levels are entered the Map Explorer menu. If using the FieldFox Map Support Tool, OSM map files can be downloaded to a .zip file and imported to FieldFox internal memory. If the FieldFox GPS receiver is enabled and OSM maps have been previously saved to FieldFox with those GPS coordinates, FieldFox can automatically load the corresponding map to match the GPS coordinates.

EMF Measurements (Option 358)

| | Description |
|---------------------------|--|
| Supported antenna | AGOS Advanced Technologies, Triaxial Isotropic Antenna Model: SDIA-6000 (or, 85572A-006 if ordered directly from Keysight) Frequency coverage: 30 MHz to 6 GHz |
| Supported operating modes | Spectrum analyzer (Channel Power measurement only) Over-the-Air (OTA) 5G NR |
| Antenna axis | Average all (Isotropic), X-axis, Y-axis, Z-axis |
| Units | Spectrum analyzer mode: dBuV/m, dBm/m ² , V/m, Watt/cm ² , W/m ² , dBμA/m, dBG, dBpT Over-the-Air (OTA) 5G NR mode: V/m, dBμV/m |
| Measurement time | Sweep time acquisition control can be set from 1 to 5000 |
| Data logging | Record, recall and playback data |
| Supported file types | Spectrum analyzer mode: CSV Over-the-Air (OTA) 5G NR mode: CSV, KML |
| Saving data | Save/recall recorded data logs to/from internal memory or external USB or SD card |

AM/FM Analog demodulation, Tune and Listen (Option 355)

The performance listed in this section applies to the AM/FM analog demodulation, tune and listen capabilities available in the following models:

| | |
|--|--|
| FieldFox RF & microwave (combination) analyzers: | N9913B, N9914B, N9915B, N9916B, N9917B, N9918B |
| FieldFox RF & microwave signal analyzers: | N9933B, N9934B, N9935B, N9936B, N9937B, N9938B |
| FieldFox microwave (combination) analyzers: | N9950B, N9951B, N9952B |
| FieldFox microwave signal analyzers: | N9960B, N9961B, N9962B |

See [FieldFox Configuration Guide](#) for option information. Many capabilities listed in this Data Sheet require options.

| | Description |
|------------------------------|--|
| Display type | RF spectrum view, demodulated waveform, including peak+ and peak- traces |
| Audio demodulation type | AM, FM narrow, FM wide, listen to the tones using FieldFox's built-in speaker or headphones |
| Audio bandwidth | 16 kHz |
| Measurement type | RF carrier power (dBm), RF carrier frequency (Hz), modulation rate (Hz), SINAD (dB), THD (%) |
| Receiver IF bandwidth | Nominal |
| AM | 35 kHz |
| FM narrow | 12 kHz |
| FM wide | 150 kHz |
| Listen time range | 0 to 100 seconds |
| AM & FM metrics | Nominal |
| SINAD | 2.5 dB to 65 dB |
| THD | 0 to 75% |
| AM measurements | Nominal |
| Maximum modulation rate | 5 kHz, demod sweep time: 50 μ s to 50 ms |
| Depth | (peak-to-peak/2) (%), \pm peak depth (%) |
| Depth accuracy | \pm 2% |
| Depth range | Modulation: 0.1 % to 99% |
| FM measurements | Nominal |
| Maximum modulation rate | 5 kHz, demod sweep time: 50 μ s to 50 ms |
| Frequency deviation | (Hz), \pm peak deviation (Hz) |
| Maximum deviation | 30 kHz (typical) |

Radio standards

With a radio standard applied, pre-defined frequency bands, channel numbers or uplink / downlink selections can be used instead of manual frequency entry. The pre-defined FieldFox radio standards include bands such as W-CDMA, LTE, and GSM. Alternately, users can create custom standards and import them into FieldFox analyzers.

Spectrum Analyzer Time Gating (Option 238)

With time gating, you can measure the spectrum of a periodic signal during a specified time interval. Pulsed-RF signals are an example of a periodic signal that can be measured with time gating. For example, you can measure the pulse during the on period, not the transition or the off period. Or you can exclude interfering signals such as a periodic transient. Time gating allows you to view spectral components that would otherwise be hidden. FieldFox's time gating method is a Gated FFT.

| | Description |
|---------------------------|---|
| Gate method | Gated FFT |
| Span range | Any span |
| RBW range | 1 Hz to 300 kHz (derived from gate width) |
| Gate delay range | -150 ms to 10 s |
| Gate width (length) range | 6 μ s to 1.8 s |
| Gate sources | External, RF burst, Video |

Reflection Measurements (RL, VSWR) (Option 320, applicable to SA only models)

The performance listed in this section applies to the reflection measurements capabilities available in the following models:

| | |
|---|---|
| FieldFox RF & microwave spectrum analyzers: | N9933B, N9934B, N9935B, N9936B, N9937B, N9938B ¹ |
| FieldFox microwave signal analyzers | N9960B, N9961B, N9962B |

See [FieldFox Configuration Guide](#) for option information. Many capabilities listed in this Data Sheet require options.

| | Models | Reflection Measurements |
|--|---------------------|-------------------------|
| N993xB | N9933B | 30 kHz to 9 GHz |
| | N9934B | 30 kHz to 9 GHz |
| | N9935B | 30 kHz to 9 GHz |
| | N9936B | 30 kHz to 14 GHz |
| | N9937B | 30 kHz to 18 GHz |
| | N9938B ¹ | 30 kHz to 26.5 GHz |
| N996xB | N9960B | 300 kHz to 32 GHz |
| | N9961B | 300 kHz to 44 GHz |
| | N9962B | 300 kHz to 50 GHz |
| Measurements | | |
| Return loss, VSWR normalization using data/memory (requires Option 220 tracking generator) | | |

¹ Reflection measurements in N9938B specifically require 3.5 mm (m) test ports instead of the standard Type-N (f).

Extended Range Transmission Analysis (ERTA) (Option 209)

ERTA specifications apply to the following FieldFox models. The RF & microwave analyzers must be equipped with the spectrum analyzer option.

FieldFox RF & microwave (combination) analyzers: N9913B, N9914B, N9915B, N9916B, N9917B, N9918B

FieldFox RF & microwave signal analyzers: N9933B, N9934B, N9935B, N9936B, N9937B, N9938B

FieldFox microwave (combination) analyzers: N9950B, N9951B, N9952B


FieldFox microwave signal analyzers: N9960B, N9961B, N9962B

ERTA operation requires two FieldFox units, each one configured with specific options, and certain accessories. See [FieldFox Configuration Guide](#) for option information. Many capabilities listed in this Data Sheet require options.

System description

ERTA can be used to measure the scalar transmission gain or loss of an RF system. It is useful when measuring long lossy cables where the two ends cannot easily be brought together, such as those bolted in on ships or aircrafts. It is also useful in measuring the insertion loss of waveguide systems, or using the frequency-offset feature, devices such as mixers and converters.

ERTA measurements are based on two FieldFox units; one at each end of the measured DUT. One FieldFox is the source and reference receiver (R), while the other is the measurement receiver (B). The two FieldFox units are synchronized using hardware triggering. By taking advantage of FieldFox's InstAlign technique, ERTA can be used to make accurate gain or loss measurements.



ERTA (continued)

Frequency specifications

The ERTA frequency range is limited by each individual analyzer's frequency range.

| | Models | Source frequency range | Receiver frequency range ¹ |
|--|---|------------------------|---------------------------------------|
| N991xB, N993xB | N9913B, N9933B | 30 kHz to 4 GHz | 9 kHz to 4 GHz |
| | N9914B, N9934B | 30 kHz to 6.5 GHz | 9 kHz to 6.5 GHz |
| | N9915B, N9935B | 30 kHz to 9 GHz | 9 kHz to 9 GHz |
| | N9916B, N9936B | 30 kHz to 14 GHz | 9 kHz to 14 GHz |
| | N9917B, N9937B | 30 kHz to 18 GHz | 9 kHz to 18 GHz |
| | N9918B, N9938B | 30 kHz to 26.5 GHz | 9 kHz to 26.5 GHz |
| N995xB, N996xB | N9950B, N9960B | 300 kHz to 32 GHz | 9 kHz to 32 GHz |
| | N9951B, N9961B | 300 kHz to 44 GHz | 9 kHz to 44 GHz |
| | N9952B, N9962B | 300 kHz to 50 GHz | 9 kHz to 50 GHz |
| Frequency reference | | | |
| Refer to the frequency accuracy specifications. | | | |
| Source output power | | | |
| Refer to the test port output power typical data. | | | |
| Frequency setup parameters | | | |
| Receiver frequency | Center/span or start/stop (standard spectrum analyzer settings) Reverse receiver sweep direction (default direction is forward, but can be set to reverse) | | |
| Source frequency [Remote] | [Tracking] – FieldFox source tracks the receiver by default. The frequencies are identical. [CW] – FieldFox’s source can be set to a CW frequency independent of FieldFox’s receiver frequency. FieldFox’s source is at a single CW frequency; FieldFox’s receiver is swept. [Coupled CW] – FieldFox’s source CW frequency is auto-coupled to FieldFox’s receiver [Center Frequency] setting. | | |
| Frequency-offset capability | | | |
| This feature allows the FieldFox’s source frequency to be offset from FieldFox’s receiver frequency. The offset frequency can be negative, zero, or positive. The frequency-offset capability is useful when characterizing the scalar transmission response of devices such as mixers and converters. | | | |

¹ The receiver (spectrum analyzer) is usable to 5 kHz, though only specified to 9 kHz.

ERTA (continued)

Frequency specifications (continued)

| Frequency-offset setup parameters | |
|-----------------------------------|---|
| Receiver frequency | Center/span or start/stop (standard spectrum analyzer settings) Reverse receiver sweep direction (default direction is forward, but can be set to reverse) |
| Frequency tracking offset | On/Off Offset values: 0, > 0, < 0 |
| Receiver sweep direction | Reversal: Off Default setting Both source and receiver sweep in the forward direction. Receiver stop frequency > Receiver start frequency $\text{Source frequency} = \text{Offset} + \text{Receiver frequency}$ Reversal: On Source and receiver sweep in opposite directions. $\text{Source frequency} = \text{Offset} - \text{Receiver frequency}$ Offset > receiver frequency |

Dynamic range and maximum attenuation

Dynamic range is the difference between the maximum output power available from FieldFox's source and the noise floor of the second FieldFox, while ensuring that neither FieldFox's ADC goes into over-range. Dynamic range also accounts for the loss of the power splitter. Dynamic range is applicable when testing devices such as filters, where there is low loss in the passband, and significant loss in the stopband, and both passband and stopband need to be on the display at the same time (same sweep).

Maximum attenuation is the difference between maximum output power available from FieldFox's source and the noise floor of FieldFox. It also accounts for the loss of power splitter. Maximum attenuation is applicable when testing devices such as cables, which have relatively uniform loss over the swept frequency range.

The values shown are based on the recommended minimum RBW of 3 kHz when the frequency references are locked via GPS, and 300 kHz when the frequency references are unlocked. Locking the frequency references to GPS allows for greater frequency accuracy of the FieldFox units and use of a narrower RBW, which in turn results in a lower DANL, and hence a wider measurement range. When the GPS signals cannot be present at all times, the GPS hold-over mode can be used.

ERTA (continued)

Dynamic range and maximum attenuation (continued)

| Dynamic range (dB) | | | | |
|-------------------------------|---|---|--|--|
| N991xB, N993xB | Typical | | | |
| | Preamp off | Preamp on | Preamp off | Preamp on |
| | Frequency references locked to GPS, RBW 3 kHz | Frequency references locked to GPS, RBW 3 kHz | Frequency references unlocked, RBW 300 kHz | Frequency references unlocked, RBW 300 kHz |
| > 2 MHz ¹ to 6 GHz | 88 | 83 | 68 | 63 |
| > 6 to 13 GHz | 86 | 83 | 66 | 63 |
| > 13 to 22 GHz | 70 | 86 | 50 | 66 |
| > 22 to 25 GHz | 63 | 83 | 43 | 63 |
| > 25 to 26.5 GHz | 58 | 77 | 38 | 57 |

| Maximum attenuation (dB) | | | | |
|--------------------------|---|---|--|--|
| N991xB, N993xB | Typical | | | |
| | Preamp off | Preamp on | Preamp off | Preamp on |
| | Frequency references locked to GPS, RBW 3 kHz | Frequency references locked to GPS, RBW 3 kHz | Frequency references unlocked, RBW 300 kHz | Frequency references unlocked, RBW 300 kHz |
| > 2 MHz to 6 GHz | 93 | 108 | 73 | 88 |
| > 6 to 13 GHz | 86 | 103 | 66 | 83 |
| > 13 to 22 GHz | 70 | 91 | 50 | 71 |
| > 22 to 25 GHz | 63 | 83 | 43 | 63 |
| > 25 to 26.5 GHz | 58 | 77 | 38 | 57 |

| Dynamic range (dB) | | | | |
|--------------------|---|---|--|--|
| N995xB, N996xB | Typical | | | |
| | Preamp off | Preamp on | Preamp off | Preamp on |
| | Frequency references locked to GPS, RBW 3 kHz | Frequency references locked to GPS, RBW 3 kHz | Frequency references unlocked, RBW 300 kHz | Frequency references unlocked, RBW 300 kHz |
| > 2 to 5 MHz | 83 | 87 | 62 | 58 |
| > 5 MHz to 11 GHz | 93 | 97 | 69 | 68 |
| > 11 to 19 GHz | 95 | 96 | 71 | 70 |
| > 19 to 22 GHz | 93 | 94 | 69 | 68 |
| > 22 to 40 GHz | 88 | 90 | 63 | 65 |
| > 40 to 43 GHz | 82 | 89 | 57 | 64 |
| > 43 to 46 GHz | 81 | 93 | 56 | 68 |
| > 46 to 50 GHz | 77 | 88 | 52 | 63 |

¹ Dynamic range is decreased from 3 to 9 dB at 2 MHz.

| Maximum attenuation (dB) | | | | |
|--------------------------|---|---|--|--|
| N995xB, N996xB | Typical | | | |
| | Preamp off | Preamp on | Preamp off | Preamp on |
| | Frequency references locked to GPS, RBW 3 kHz | Frequency references locked to GPS, RBW 3 kHz | Frequency references unlocked, RBW 300 kHz | Frequency references unlocked, RBW 300 kHz |
| > 2 MHz to 13 GHz | 100 | 113 | 74 | 88 |
| > 13 to 18 GHz | 101 | 110 | 76 | 85 |
| > 18 to 22 GHz | 99 | 108 | 74 | 83 |
| > 22 to 35 GHz | 95 | 105 | 70 | 80 |
| > 35 to 40 GHz | 88 | 100 | 63 | 75 |
| > 40 to 46 GHz | 81 | 93 | 56 | 63 |
| > 46 to 50 GHz | 77 | 88 | 52 | 63 |

Absolute power and gain measurement uncertainties

Verified with input level of -10 dBm, peak detector, 10 dB attenuation, preamplifier off, all settings auto-coupled, no warm-up required. Includes frequency response uncertainties. Assumes an ERTA system using a Keysight 11667A, 11667B, or 11667C power splitter.

| N991xB and N993xB | | | | |
|--|---------------------|------------------------|------------------------|---------------------------|
| Input power (R) measurements uncertainty, 30 kHz RBW (dB) | | | | |
| | Spec (23 ± 5 °C) | Spec (-10 to 55 °C) | Typical (23 ± 5 °C) | Typical (-10 to 55 °C) |
| 100 kHz to 18 GHz | ± 1.10 | ± 1.30 | ± 0.40 | ± 0.50 |
| > 18 to 26.5 GHz | ± 1.40 | ± 1.50 | ± 0.50 | ± 0.60 |
| Output power (B) measurement uncertainty, frequency references locked to GPS, RBW ≥ 3 kHz (dB) | | | | |
| 100 kHz to 18 GHz | ± 1.00 | ± 1.20 | ± 0.40 | ± 0.50 |
| > 18 to 26.5 GHz | ± 1.20 | ± 1.40 | ± 0.50 | ± 0.60 |
| Output power (B) measurement uncertainty, frequency references unlocked, RBW ≥ 300 kHz (dB) | | | | |
| 100 kHz to 18 GHz | ± 1.00 | ± 1.30 | ± 0.40 | ± 0.50 |
| > 18 to 26.5 GHz | ± 1.40 | ± 1.60 | ± 0.50 | ± 0.60 |
| Gain/Loss (B/R) measurement uncertainty, frequency references locked to GPS, RBW ≥ 3 kHz (dB) | | | | |
| 100 kHz to 18 GHz | ± 1.30 | ± 1.70 | ± 0.60 | ± 0.70 |
| > 18 to 26.5 GHz | ± 1.70 | ± 2.10 | ± 0.70 | ± 0.90 |
| Gain/Loss (B/R) measurement uncertainty, frequency references unlocked, RBW ≥ 300 kHz (dB) | | | | |
| 100 kHz to 18 GHz | ± 1.40 | ± 1.70 | ± 0.70 | ± 0.70 |
| > 18 to 26.5 GHz | ± 2.00 | ± 2.10 | ± 0.90 | ± 1.00 |

| N995xB and N996xB | | | | |
|--|---------------------|------------------------|------------------------|---------------------------|
| Input power (R) measurements uncertainty, 30 kHz RBW (dB) | | | | |
| | Spec (23 ± 5 °C) | Spec (-10 to 55 °C) | Typical (23 ± 5 °C) | Typical (-10 to 55 °C) |
| 2 MHz to 18 GHz | ± 1.10 | ± 1.30 | ± 0.50 | ± 0.60 |
| > 18 to 32 GHz | ± 1.20 | ± 1.50 | ± 0.50 | ± 0.70 |
| > 32 to 40 GHz | ± 1.30 | ± 1.80 | ± 0.60 | ± 0.80 |
| > 40 to 43 GHz | ± 1.60 | ± 2.30 | ± 0.70 | ± 1.10 |
| > 43 to 50 GHz | ± 1.70 | ± 3.20 | ± 0.80 | ± 1.40 |
| Output power (B) measurement uncertainty, frequency references locked to GPS, RBW ≥ 3 kHz (dB) | | | | |
| 2 MHz to 18 GHz | ± 0.40 | ± 1.00 | ± 0.40 | ± 0.50 |
| > 18 to 32 GHz | ± 0.45 | ± 1.30 | ± 0.40 | ± 0.60 |
| > 32 to 40 GHz | ± 0.50 | ± 1.50 | ± 0.50 | ± 0.70 |
| > 40 to 43 GHz | ± 0.80 | ± 2.30 | ± 0.70 | ± 1.00 |
| > 43 to 50 GHz | ± 0.90 | ± 3.00 | ± 0.80 | ± 1.40 |
| Output power (B) measurement uncertainty, frequency references unlocked, RBW ≥ 300 kHz (dB) | | | | |
| 2 MHz to 18 GHz | ± 1.00 | ± 1.10 | ± 0.40 | ± 0.50 |
| > 18 to 32 GHz | ± 1.20 | ± 1.50 | ± 0.50 | ± 0.60 |
| > 32 to 40 GHz | ± 1.60 | ± 1.90 | ± 0.60 | ± 0.80 |
| > 40 to 43 GHz | ± 2.10 | ± 2.50 | ± 0.70 | ± 1.30 |
| > 43 to 50 GHz | ± 2.60 | ± 3.60 | ± 1.00 | ± 1.60 |
| Gain/Loss (B/R) measurement uncertainty, frequency references locked to GPS, RBW ≥ 3 kHz (dB) | | | | |
| 2 MHz to 18 GHz | ± 1.40 | ± 1.70 | ± 0.60 | ± 0.70 |
| > 18 to 32 GHz | ± 1.50 | ± 2.00 | ± 0.70 | ± 0.90 |
| > 32 to 40 GHz | ± 1.60 | ± 2.30 | ± 0.80 | ± 1.00 |
| > 40 to 43 GHz | ± 2.20 | ± 3.10 | ± 1.00 | ± 1.40 |
| > 43 to 50 GHz | ± 2.40 | ± 4.00 | ± 1.20 | ± 1.90 |
| Gain/Loss (B/R) measurement uncertainty, frequency references unlocked, RBW ≥ 300 kHz (dB) | | | | |
| 2 MHz to 18 GHz | ± 1.40 | ± 1.70 | ± 0.70 | ± 0.70 |
| > 18 to 32 GHz | ± 1.80 | ± 2.10 | ± 0.80 | ± 1.00 |
| > 32 to 40 GHz | ± 2.10 | ± 2.80 | ± 1.00 | ± 1.30 |
| > 40 to 43 GHz | ± 2.70 | ± 3.50 | ± 1.40 | ± 1.70 |
| > 43 to 50 GHz | ± 3.00 | ± 4.80 | ± 1.60 | ± 2.40 |

Cable correction

Input and output jumper cable losses can be accounted for using ERTA's cable correction wizard.

The performance listed in built-on power meter, external USB power sensor support, pulse measurements, USB power sensor measurements versus frequency sections applies to the capabilities available in the following models:

| | |
|--|--|
| FieldFox RF & microwave (combination) analyzers: | N9913B, N9914B, N9915B, N9916B, N9917B, N9918B |
| FieldFox RF & microwave signal analyzers: | N9933B, N9934B, N9935B, N9936B, N9937B, N9938B |
| FieldFox microwave (combination) analyzers | N9950B, N9951B, N9952B |
| FieldFox microwave signal analyzers | N9960B, N9961B, N9962B |

See [FieldFox Configuration Guide](#) for option information. Many capabilities listed in this Data Sheet require options.

Built-in Power Meter (Option 310)

Using the built-in power meter, FieldFox is able to make very accurate channel power measurements. The channel bandwidth can be set wide to simulate average power meter measurements. This measurement function provides the flexibility to make user definable channel power measurements.

| Description | | | |
|------------------|--|-------------------|-----------------|
| Setup parameters | Center frequency, including selection of radio standards and channel selection, span or channel width | | |
| Functions | Relative/absolute measurements, offsets, units of dBm or Watts, or dB or %, minimum and maximum limits | | |
| | Models | Frequency range | |
| N991xB, N993xB | N9913B, N9933B | 9 kHz to 4 GHz | Usable to 5 kHz |
| | N9914B, N9934B | 9 kHz to 6.5 GHz | Usable to 5 kHz |
| | N9915B, N9935B | 9 kHz to 9 GHz | Usable to 5 kHz |
| | N9916B, N9936B | 9 kHz to 14 GHz | Usable to 5 kHz |
| | N9917B, N9937B | 9 kHz to 18 GHz | Usable to 5 kHz |
| | N9918B, N9938B | 9 kHz to 26.5 GHz | Usable to 5 kHz |
| N995xB, N996xB | N9950B, N9960B | 9 kHz to 32 GHz | Usable to 5 kHz |
| | N9951B, N9961B | 9 kHz to 44 GHz | Usable to 5 kHz |
| | N9952B, N9962B | 9 kHz to 50 GHz | Usable to 5 kHz |

| Total absolute amplitude accuracy (dB) | | | |
|--|--|--------------------|-----------------------|
| 10 dB attenuation, input signal -15 to -5 dBm, peak detector, 300 Hz RBW, all settings auto-coupled, includes frequency response uncertainties. No warm-up required. | | | |
| N991xB, N993xB | | Spec (-10 to 55°C) | Typical (-10 to 55°C) |
| 9 kHz to 100 kHz | | ± 2.00 | ± 0.25 |
| ≥ 100 kHz to 500 MHz | | ± 0.80 | ± 0.20 |
| ≥ 500 MHz to 16.3 GHz | | ± 1.00 | ± 0.20 |
| ≥ 16.3 GHz to 26.5 GHz | | ± 1.00 | ± 0.35 |
| N995xB, N996xB | | Spec (-10 to 55°C) | Typical (-10 to 55°C) |
| 9 to 500 kHz | | ± 2.20 | ± 0.60 |
| > 500 kHz to 15 MHz | | ± 1.00 | ± 0.10 |
| > 15 MHz to 18 GHz | | ± 1.00 | ± 0.20 |
| > 18 to 26.5 GHz | | ± 1.10 | ± 0.25 |
| > 26.5 to 32 GHz | | ± 1.20 | ± 0.35 |
| > 32 to 36 GHz | | ± 1.40 | ± 0.35 |
| > 36 to 44 GHz | | ± 2.00 | ± 0.55 |
| > 44 to 50 GHz | | ± 2.40 | ± 0.55 |

External USB Power Sensor Support (Option 302)

The external USB power sensor option supports various Keysight USB power sensors. For an up-to-date listing of the supported power sensors, visit <http://www.keysight.com/find/fieldfoxsupport>

| | Description |
|------------------|---|
| Setup parameters | Frequency |
| Functions | Relative/absolute measurements, offsets, units of dBm or Watts, or dB or %, minimum and maximum limits. |
| Internal source | FieldFox's internal source can be turned on in the USB power sensor mode. CW frequency and nominal power level control are available. |

Pulse Measurements (Option 330)

FieldFox's pulse measurement option can be used to characterize RF pulses such as those used in radar and electronic warfare systems. Measurements are made using FieldFox and Keysight's USB peak power sensors.

Performance specifications such as frequency, dynamic range and minimum pulse width depend on the peak power sensor. Supported peak power sensors: <http://www.keysight.com/find/fieldfoxsupport>

| | Description |
|------------------|---|
| Setup parameters | Frequency, time (center), time/division, gating, triggering, video bandwidth, averaging |
| Functions | Average power, peak power, and peak to average ratio |
| | Analog gauge display and digital display, dBm and Watts |
| | Relative/absolute measurements, offset, dB or %, minimum and maximum limits |
| | Trace graph for pulse profiling with gating |
| | Rise time, fall time, pulse width, pulse period, pulse repetition frequency |

USB Power Sensor Measurements versus Frequency (Option 208)

This feature allows FieldFox's source frequency to be set independently from the power sensor (receiver) frequency. With frequency-offset using power sensor (FOPS), the frequency of both the source and receiver are swept, and the two track each other. The offset frequency can be negative, zero, or positive.

FOPS can be used to characterize the scalar transmission response of devices such as mixers and converters. This frequency-offset capability is necessary for conversion loss/gain measurements on frequency-translating devices, since by definition, the input and output frequencies of the DUT are different. The FieldFox source stimulates the DUT and the power sensor is used as the measurement receiver.

Since power sensors are inherently broadband devices (not frequency-selective), the user should ensure that only the signal of interest is present at the power sensor input and that all other signals are filtered appropriately.

USB Power Sensor Measurements versus Frequency (continued)

| Setup parameters | |
|---------------------|--|
| Source frequency | Center/span or start/stop |
| Receiver frequency | Range determined by power sensor range |
| Frequency offset | Positive offset or negative offset |
| Frequency step size | 30 kHz minimum |
| Number of points | 2 to 1601 (Combination of number of points and frequency step size limited by span.) |
| Dwell time/point | 0 to 1.0 sec |

Source frequency span must be equal to receiver frequency span.

Receiver sweep direction: forward (default setting) or reverse.


For some DUTs, the output frequency may sweep in a reverse direction, as compared to the source frequency. The basic relationships between the source, receiver and offset frequencies are shown in the table below. The FieldFox analyzer includes an offset calculator that ensures a fast measurement setup.

| Src sweep direction | Rx sweep direction | Frequency calculations |
|-------------------------------|-----------------------------|--|
| Forward $f_{2src} > f_{1src}$ | Forward $f_{2rx} > f_{1rx}$ | Receiver frequency = Source frequency \pm Offset |
| Forward $f_{2src} > f_{1src}$ | Reverse $f_{2rx} > f_{1rx}$ | Receiver frequency = Offset - Source Frequency Offset > Source frequency |

| | Description |
|---------------|--|
| Measurements | Source power, gain/loss and receiver (Rx) power Gain = Rx power / source power (memory). Source power (memory) is measured during setup. |
| Output power | Refer to the test port output power typical data on page 5. |
| Dynamic range | The dynamic range with FOPS is dependent on FieldFox's output power and the power sensor's dynamic range. Supported USB power sensors: www.keysight.com/find/fieldfoxsupport |

The graph below shows a filter measurement using two different power sensors, the U2002A (- 60 to +20 dBm) and the U2021XA (- 45 to +20 dBm). While a filter is not commonly measured using FOPS, it is a useful device for demonstrating dynamic range.

For both measurements, the FieldFox source power was set to - 1 dBm, the maximum available in the selected frequency range of 7.25 to 13.25 GHz. An external amplifier was not used in this case, but one can be added to increase the source power and hence dynamic range.



Example showing typical dynamic range of FOPS

Built-In GNSS (GPS+) Receiver (Option 307)

| | Description |
|-----------------------|--|
| GNSS (GPS+) receiver | The internal GNSS/GPS receiver can be used as a frequency reference. ¹ |
| Supported systems | GPS, GLONASS, BeiDou and Galileo |
| Modes | Off, internal, external |
| Sync clock | On, off |
| Functionality | Geo-location: latitude, longitude, altitude (elevation), time, sync time/date Requires external GNSS/GPS antenna (can use N9910X-825, GPS active antenna) |
| Connector for antenna | SMA (f), 3.3 or 5 V |
| Maximum DC current | 20 mA |

DC Bias Variable-Voltage Source (Option 309)

| | Description |
|-------------------------------|---|
| | Nominal |
| Connector | SMB (m) |
| Voltage | +1 to +32 V |
| Resolution | 0.1 V |
| Maximum current ² | 0.65 A |
| DC current readout resolution | 0.01 A |
| Maximum power ² | 7 watts |
| Display read out | Voltage, current |
| Overload trip protection | Automatically engages when voltage source is on. The trip circuit can be reset from front panel without pre-setting or power cycling the analyzer. |

¹ External GPS USB receivers can be used to provide geo-location data. However, they cannot be used for frequency reference locking.

² Battery life will be reduced when DC source is used. A trip function turns off the power supply when the rated current or power is exceeded.

Remote Control Capability (Option 030)

Option 030 adds remote control capability to FieldFox analyzers, so that FieldFox can be controlled via an iOS device. The FieldFox app, running on the iOS device, combined with Option 030 on the FieldFox analyzer provides full control of the instrument from a remote location. The app emulates the front panel of FieldFox, so users can press the FieldFox hard keys or softkeys using their iPhone or iPad and make measurements remotely. For example, a tower climber can be on the tower with a FieldFox analyzer, while the technician controls and makes the measurements down below, using an iPad. The iPad and FieldFox communicate via a network connection.

iOS device requirements
iPad, iPhone, or iPod Touch
iOS of 6.1 or higher
A WiFi or 3G/4G connection

The FieldFox app communicates with FieldFox via a network connection, so both the iOS device and FieldFox need to be on a network where both devices can reach the other. For example, a company intranet or a site installation using a wireless router. FieldFox can directly be connected to a LAN cable, or if wired LAN is not available, a user supplied wireless router can be configured to work with FieldFox. FieldFox does not include a wireless router.

FieldFox app without Option 030

The FieldFox app can be installed on an iOS device independent of the presence of Option 030 on the analyzer. Without Option 030, users can view the live display screen of their FieldFox remotely but cannot control the instrument. With 030 purchased and installed on their FieldFox, users can both view and control their FieldFox. Control refers to the ability to press hard keys, softkeys, make or change measurements, etc. Option 030 does not include the iOS device itself. Users must supply their own iOS device. Option 030 is a license on the FieldFox analyzer. Option 030 and the FieldFox app are not applicable to Android, BlackBerry, or Windows phone/tablet devices. FieldFox can be remote controlled via PC software using a wireless or wired LAN connection. FieldFox Data Link software provides a remote display tool with a virtual keypad that allows remote access to the FieldFox display (Option 030 not required).

General Information

| | |
|--------------------------------|--|
| Calibration cycle | |
| | 1 year |
| Weight | |
| N991xB, N993xB, N995xB, N996xB | 3.34 kg or 7.35 lb. including battery (approx.) |
| Dimensions: H x W x D | |
| | 292 x 188 x 82 mm (11.5 in x 7.4 in x 3.2 in) (approx.) |
| Environmental | |
| MIL-PRF-28800F Class 2 | Operating temperature Storage temperature Operating humidity Random vibration Functional shock Bench drop |

General Information (continued)

| | |
|--|--|
| Environmental (continued) | |
| Maximum humidity | Maximum relative humidity (non-condensing): 95% relative humidity up to 40°C, decreases linearly to 45% relative humidity at 55°C ¹ |
| Altitude – operating | 9,144 m or 30,000 ft (using battery) |
| Altitude – Non-operating | 15,240 m or 50,000 ft |
| Altitude – AC to DC adapter | 3,000 m or 9,840 ft |
| Ingress protection | |
| This product has been type tested to meet the requirements for ingress protection IP53 in accordance with IEC/EN 60529 (IP rating for instrument by itself, with no cover). | |
| Temperature range | |
| Operating, AC power, spec ² | -10 to 55°C (14 to 131°F) (-10 to 45°C/14 to 113°F in RTSA mode) |
| Operating, battery, spec | -10 to 50°C (14 to 122°F) |
| Operating, battery, typical | -10 to 55°C (14 to 131°F) |
| Storage, spec ^{3,4} | -51 to 71°C (-60 to 160°F) |
| EMC: Complies with the essential requirements of the European Radio Equipment Directive as well as current editions of the following standards (dates and editions are cited in the Declaration of Conformity): | |
| IEC/EN 61326-1 | |
| EN 301 489-1, EN 301 489-19 | |
| CISPR Pub 11 Group 1, Class B | |
| AS/NZS CISPR 11 | |
| ICES/NMB-001 | |
| This ISM device complies with Canadian ICES-001. | |
| Cet appareil ISM est conforme à la norme NMB-001 du Canada. | |
| Radio Equipment (GNSS): Complies with the essential requirements of the European Radio Equipment Directive: | |
| EN 303 413 | |
| SAFETY: Complies with the essential requirements of the European Low Voltage Directive as well as current editions of the following standards (dates and editions are cited in the Declaration of Conformity): | |
| IEC/EN 61010-1 | |
| Canada: CSA C22.2 No. 61010-1 | |
| USA: UL std no. 61010-1 | |
| To find a current Declaration of Conformity for a specific Keysight product, go to: http://www.keysight.com/go/conformity | |
| Explosive environment | |
| This product has been type tested to meet the requirements for operation in explosive environments in accordance with MIL-STD-810G, Method 511.5, Procedure I. | |

¹ From 40°C to 55°C, the maximum % relative humidity follows the line of constant dew point.

² Power supply: 0 to 40°C at 90 W output rating, derate linearly at 3 watts per degree C, to 45 W at 55°C, 30 W at -20°C.

³ The battery packs should be stored in an environment with low humidity. Extended exposure to temperature above 45°C could degrade battery performance and life.

⁴ Power supply: -40°C to 85°C (-40°F to 185°F).

General Information (continued)


| | |
|---------------------------------|---|
| Power supply | |
| External DC input | 15 to 19 VDC, 4 amps maximum when battery charging |
| External AC power adapter | Efficiency level VI |
| Input | 100 to 240 VAC, 50 to 60 Hz, 1.5 to 0.75 A |
| Output | 15 VDC, 6 A |
| Power consumption | 16 to 30 watts (typical) Battery consumption depends on battery saver selection, measurement mode and temperature. |
| Battery | |
| Lithium ion | 10.8 V, 6.4 A-h, 70 Wh |
| Operating time | 4 hours (typical), mode dependent |
| Charge time | A fully discharged battery takes about 1.5 hours to recharge to 80%. Four hours to 100%. |
| Discharge temperature limits | -10 to 60°C, ≤ 85% RH |
| Charge temperature limits | 0 to 45°C, ≤ 85% RH |
| Storage temperature limits | -20 to 50°C, ≤ 85 % RH The battery packs should be stored in an environment with low humidity. Extended exposure to temperatures above 45°C could degrade battery performance and life. |
| Test port connectors | |
| ≤ 18 GHz models | Type-N (f) |
| 26.5 GHz models | 3.5 mm (m) for FieldFox microwave analyzer, N9918B. On FieldFox SA N9938B, you may choose 3.5 mm (m) or Type-N (f). Type-N (f) port connector is not available for the 26.5 GHz microwave analyzer, N9918B. |
| Display | |
| | 6.5" transfective color LCD-LED backlit |
| Headphone jack connector | |
| | 3.5 mm (1/8 inch) miniature audio jack |
| USB-A, 2-ports | |
| | Hi-speed USB 2.0 |
| Mini USB, 1 port | |
| | Hi-speed USB 2.0; used for SCPI programming; USBTMC (USB IEEE488) |
| Keyboard | |
| | USB keyboards are supported (user must supply their own keyboard) |
| LAN | |
| Connector | RJ-45 Used for programming, data saving, remote control, and connection to DataLink software |
| N991xB, N993xB | 1000/100/10 base-T (auto switching) SCPI over LAN using sockets and VX11 (LAN IEEE488); HTTP |

General Information (continued)

| | |
|---|--|
| Programming | |
| | SCPI, using the built-in LAN interface, PathWave BenchVue |
| Languages | |
| | English, Spanish, German, Italian, French, Russian, Japanese, Chinese, Turkish, Korean, and Portuguese |
| Preset | |
| | User preset for both mode preset and complete system preset |
| Limit lines | |
| The limit line capabilities listed in this section apply to the cable and antenna analyzer, network analyzer and spectrum analyzer modes in all FieldFox analyzers. | |
| <ul style="list-style-type: none"> Limit lines can be a combination of horizontal lines, sloping lines, or discrete data points Limit types: Fixed or relative Each trace can have its own limit line Limit lines can be built from a current trace Limit segments > 100, limited by memory size Max limit line number of points: 10,001 Beep: Beep off, Beep on fail, Beep on pass Pass/fail warning: on/off Offset and margin: An increase or decrease in the limit line Save/recall limit lines | |
| Data storage | |
| Internal | Internal Minimum: 4 GB Minimum states and traces: 1000 |
| External | Supports USB 2.0 compatible memory devices and SD/SDHC memory cards with FAT and exFAT format |
| Data types | Trace, trace+state, picture (png), data (csv), S1P, S2P |
| Secure operation | |
| Frequency blanking | For protection of sensitive data all frequency information can be turned off. |
| Erase user data | All user data can be erased on a FieldFox analyzer. For more information visit: http://www.keysight.com/find/securefieldfox |
| Reference out/trigger out | |
| Connector | SMB (m), 50 Ω |
| Output amplitude | ≥ 0 dBm |
| Frequency | 10 MHz (1 + frequency reference accuracy) |
| Trigger out | Reserved for future use; currently only used for ERTA 2-box handshaking |
| Reference in/trigger in | |
| Connector | SMA (f), 50 Ω |
| Reference input | 10 MHz, - 5 to +10 dBm |
| Trigger input | 3.3 or 5 V TTL logic levels |


FieldFox Physical Dimensions

FieldFox models with Type-N test port connectors




FieldFox Physical Dimensions (continued)

FieldFox models with 3.5 mm test port connectors



FieldFox Physical Dimensions (continued)

FieldFox models with 2.4 mm test port connectors



Carry Precision with You

Every piece of gear in your field kit had to prove its worth. Measuring up and earning a spot is the driving idea behind Keysight's FieldFox analyzers. They're equipped to handle routine maintenance, in-depth troubleshooting, and anything in between. Better yet, FieldFox delivers precise microwave measurements—wherever you need to go. Add FieldFox to your kit and carry precision with you.

| Related Literature | Publication Number |
|--|--------------------|
| FieldFox Handheld Analyzers, Configuration Guide | 5992-3701EN |
| FieldFox Handheld Analyzers, Technical Overview | 5992-3703EN |

Download application notes, watch videos, and learn more: www.keysight.com/find/fieldfox

Learn more at: www.keysight.com

For more information on Keysight Technologies' products, applications, or services, please contact your local Keysight office. The complete list is available at: www.keysight.com/find/contactus

