

SM4529 DATA SHEET

RA N Male to N Female Adapter

RA type N male to type N female adapter part number SM4529 from Fairview Microwave is in-stock and ships same day. This Fairview type N to type N adapter has a male to female gender configuration. SM4529 type N male to type N female adapter operates to 6 GHz. This low profile right angle type N adapter allows for easier connections in tight spaces. The Fairview Microwave RF adapter provides good VSWR of 1.3:1 maximum.

RF adapters can be used to enable connections between two connector types that would otherwise not mate. Certain RF adapter configurations can also be used to protect connectors on expensive equipment where the number of connect and disconnect cycles is high. An RF, microwave, or millimeter wave adapter is connected to the equipment and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connnector savers. Fairview Microwave also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications

Description	Min	Тур	Мах	Units	
Frequency Range	DC		6	GHz	
VSWR			1.3:1		
Operating Voltage (AC)			1,000	Vrms	

Description	F1	F2	F3	F4	F5	Units
Frequency Range	DC to 3	3 to 6				GHz
VSWR, Max	1.2:1	1.3:1				

Mechanical Specifications

Size Length Width	1.441 in [36.6 mm] 1.268 in [32.21 mm]			
Weight	C	0.15476 lbs [70.2 g]		
Description	Connector 1	Connector 2		
Туре	N Male	N Female		
Polarity	Standard	Standard		
Interface Specification	MIL-STD-348A	MIL-STD-348A		



Configuration:

- N Male Connector 1
- N Female Connector 2
- 50 Ohms
- Right Angle Body Geometry

Features:

- VSWR of 1.3:1 max up to 6 GHz
- N interface meets MIL-STD-348A
- Gold Plated Brass Contact

Applications:

• General Purpose Test

Fairview Microwave 1130 Junction Dr. #100 Allen, TX 75013 Tel: 1-800-715-4396 / (972) 649-6678 Fax: (972) 649-6689 www.fairviewmicrowave.com sales@fairviewmicrowave.com





Material Specifications

TypeN MaleN FemaleContact MaterialBrassBrassContact PlatingGoldGold
Contact Plating Gold Gold
Insulation Material PTFE PTFE PTFE
Outer Contact Material Brass
Outer Contact Plating Nickel
Outer Conductor Contact Spec. 100 µin minimum
Body Material Brass
Body Plating Nickel
Body Plating Spec. 100 µin minimum
Coupling Nut Material Brass
Coupling Nut Plating Nickel
Coupling Nut Plating Spec. 100 µin minimum

Environmental Specifications

Temperature Operating Range


-65 to +165 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Typical Performance Data



1130 Junction Dr. #100 Allen, TX 75013 | Tel: 1-800-715-4396 / (972) 649-6678 / Fax: (972) 649-6689





RA N Male to N Female Adapter from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Allen, Texas. Fairview Microwave is RF ondemand.

The information contained in this document is accurate to the best of our knowledge and representative of the part


For additional information on this product, please click the following link: RA N Male to N Female Adapter SM4529

URL: https://www.fairviewmicrowave.com/ra-n-male-n-female-adapter-sm4529-p.aspx

described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.







STANDARD TOLERANCES .X ±0.2 .XX ±0.1 .XXX ±0.05

*STANDARD TOLERANCES APPLY ONLY TO DIMENSIONS IN INCHES

FAIRVIEW MICROWAVE INC.	NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. 3. DIMENSIONS ARE IN INCHES [mm].					
RA N Male to N Female Adapter	DWG NO SM4529			CAGE (GE CODE 3FKR5	
	CAD FILE 121715	SHEET	SCAL	E N/A	SIZE A	150

1130 Junction Dr. #100 Allen, TX 75013 | Tel: 1-800-715-4396 / (972) 649-6678 / Fax: (972) 649-6689