

SM2080 DATA SHEET

SMA Male to SSMB Jack Adapter

SMA male to SSMB jack adapter part number SM2080 from Fairview Microwave is in-stock and ships same day. This Fairview SMA to SSMB adapter has a male to jack gender configuration. SM2080 SMA male to SSMB jack adapter operates to 12 GHz. The SMA connector mates mechanically with commercially available 3.5mm and 2.92mm (K) connectors. The Fairview Microwave RF adapter provides excellent VSWR of 1.25:1 maximum.

RF adapters can be used to enable connections between two connector types that would otherwise not mate. Certain RF adapter configurations can also be used to protect connectors on expensive equipment where the number of connect and disconnect cycles is high. An RF, microwave, or millimeter wave adapter is connected to the equipment and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Fairview Microwave also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications

Description	Min	Тур	Max	Units
Frequency Range	DC		12	GHz
VSWR			1.25:1	

Electrical Specification Notes: Values at 25° C, sea level.

Mechanical Specifications

Si	ze
----	----

0.20	
Length	0.77 in [19.56 mm]
Weight	0.0075 lbs [3.4 g]

Description	Connector 1	Connector 2
Туре	SMA Male	SSMB Jack
Polarity	Standard	Standard
Interface Specification	MIL-STD-348	MIL-STD-348
Hex Size	5/16 inch	



Configuration:

- SMA Male Connector 1
- SSMB Jack Connector 2
- 50 Ohms
- Straight Body Geometry

Features:

- VSWR of 1.25:1 max up to 12 GHz
- SMA interface meets MIL-STD-348
- SSMB interface meets MIL-STD-348
- Contact plating according to MIL-G-45204
- · Gold Plated Brass Contact

Applications:

- Enables Between Series Connections
- General Purpose Test

Fairview Microwave 1130 Junction Dr. #100 Allen, TX 75013 Tel: 1-800-715-4396 / (972) 649-6678

Fax: (972) 649-6689 www.fairviewmicrowave.com sales@fairviewmicrowave.com





Material Specifications


Description	Connector 1	Connector 2	
Туре	SMA Male	SSMB Jack	
Contact Material	Brass	Brass	
Contact Plating	Gold	Gold	
Contact Plating Spec.	MIL-G-45204	MIL-G-45204	
Outer Contact Material		Brass	
Outer Contact Plating		Nickel	
Outer Conductor Contact Spec.		QQ-N-290	
Body Material	Brass		
Body Plating	Nickel		
Body Plating Spec.	QQ-N-290		

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Typical Performance Data







SMA Male to SSMB Jack Adapter from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Allen, Texas. Fairview Microwave is RF ondemand.

> The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order


For additional information on this product, please click the following link: SMA Male to SSMB Jack Adapter SM2080

URL: https://www.fairviewmicrowave.com/sma-male-mini-smb-jack-adapter-sm2080-p.aspx

stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.
arising out of the use of any part or documentation.







FAIRVIEW MICROWAVE INC. ALLEN, TX 75013 WWW.FAIRVIEWMICROWAVE.COM	NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. 3. DIMENSIONS ARE IN INCHES [mm].					
SMA Male to SSMB Jack Adapter	DWG NO SM2080			CAGE C	3FKR5	
	CAD FILE 072116	SHEET	SCALI	E N/A	SIZE A	5568