

QD SMA Male to RP SMA Female Adapter

Electrical Specifications

| | |
|---------------------------------|--------------|
| Frequency Range | DC to 18 GHz |
| Maximum VSWR | 1.25:1 |
| Dielectric Withstanding Voltage | 1,500 Vrms |

Mechanical Specifications

| | |
|-------------|-------------------|
| Size | |
| Length | 1.13 in [28.7 mm] |
| Width | 0.5 in [12.7 mm] |

Connector 1

| | |
|---------------------------------------|----------------------------|
| Type | QD SMA Male |
| Inner Conductor Material and Plating | Brass, Gold |
| Inner Conductor Plating Specification | MIL-G-45204 |
| Coupling Nut Material and Plating | Passivated Stainless Steel |
| Coupling Nut Plating Specification | QQ-P-35 |
| Body Material and Plating | Beryllium Copper, Nickel |
| Body Plating Specification | QQ-N-290 |
| Dielectric Type | PTFE |

Connector 2

| | |
|---------------------------------------|-----------------------------|
| Type | SMA Female Reverse Polarity |
| Inner Conductor Material and Plating | Brass, Gold |
| Inner Conductor Plating Specification | MIL-G-45204 |
| Body Material and Plating | Beryllium Copper, Nickel |
| Body Plating Specification | QQ-N-290 |
| Dielectric Type | PTFE |

Environmental Specifications

| | |
|--------------------|-------------------|
| Temperature | |
| Operating Range | -65 to +165 deg C |

Compliance Certifications (visit www.FairviewMicrowave.com for current document)

| | |
|-----------------|------------|
| RoHS Compliant | Yes |
| REACH Compliant | 06/06/2014 |

Plotted and Other Data

- Notes:
- Values at 25 °C, sea level



Features:

- Connector 1: QD SMA Male
- Impedance 1: 50 Ohms
- Connector 2: SMA Female Reverse Polarity
- Impedance 2: 50 Ohms
- Adapter Design: Standard
- Body Style: Straight

Fairview Microwave
1130 Junction Dr. #100
Allen, TX 75013
Tel: 1-800-715-4396 / (972) 649-6678
Fax: (972) 649-6689
www.fairviewmicrowave.com
sales@fairviewmicrowave.com


QD SMA Male to RP SMA Female Adapter from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Allen, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [QD SMA Male to RP SMA Female Adapter SM4986](#)

URL: <http://www.fairviewmicrowave.com/qd-sma-male-rp-sma-female-adapter-sm4986-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.





| | | | | | |
|---|--------|---|-------|--------------------|------------|
| FAIRVIEW MICROWAVE INC. ALLEN, TX 75013 WWW.FAIRVIEWMICROWAVE.COM | | NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. 3. DIMENSIONS ARE IN INCHES [mm]. | | | |
| TITLE QD SMA Male to RP SMA Female Adapter | | DWG NO SM4986 | | CAGE CODE 3FKR5 | |
| CAD FILE | 112514 | SHEET | SCALE | N/A | SIZE A 150 |