

3.5mm Male to 2.92mm Female Adapter

3.5mm male to 2.92mm female adapter part number SM3370 from Fairview Microwave is in-stock and ships same day. This Fairview 3.5mm to 2.92mm adapter has a male to female gender configuration. SM3370 3.5mm male to 2.92mm female adapter operates to 34 GHz. The 3.5mm connector mates mechanically with commercially available SMA and 2.92mm (K) connectors. The Fairview Microwave RF adapter provides excellent VSWR of 1.25:1 maximum.

RF adapters can be used to enable connections between two connector types that would otherwise not mate. Certain RF adapter configurations can also be used to protect connectors on expensive equipment where the number of connect and disconnect cycles is high. An RF, microwave, or millimeter wave adapter is connected to the equipment and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Fairview Microwave also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications

| Description | Min | Typ | Max | Units |
|-----------------|-----|-----|--------|-------|
| Frequency Range | DC | | 34 | GHz |
| VSWR | | | 1.25:1 | |

Electrical Specification Notes:
Values at 25°C, sea level.

Mechanical Specifications

Size

| | |
|--------|---------------------|
| Length | 0.739 in [18.77 mm] |
| Width | 0.218 in [5.54 mm] |
| Height | 0.218 in [5.54 mm] |
| Weight | 0.0075 lbs [3.4 g] |

| Description | Connector 1 | Connector 2 |
|---------------|-------------------------------------|---------------|
| Type | 3.5mm Male | 2.92mm Female |
| Polarity | Standard | Standard |
| Mating Cycles | 500 | 500 |
| Mating Torque | 8 to 10 in-lbs [0.90 to 1.13 Nm] | |



Configuration:

- 3.5mm Male Connector 1
- 2.92mm Female Connector 2
- 50 Ohms
- Straight Body Geometry

Features:

- VSWR of 1.25:1 max up to 34 GHz
- Contact plating according to MIL-G-45204
- Gold over Nickel Plated Beryllium Copper Contact

Applications:

- Enables Between Series Connections
- General Purpose Test

Fairview Microwave
1130 Junction Dr. #100
Allen, TX 75013
Tel: 1-800-715-4396 / (972) 649-6678
Fax: (972) 649-6689
www.fairviewmicrowave.com
sales@fairviewmicrowave.com

Material Specifications

| Description | Connector 1 | Connector 2 |
|-------------------------------|----------------------------|----------------------------|
| Type | 3.5mm Male | 2.92mm Female |
| Contact Material | Beryllium Copper | Beryllium Copper |
| Contact Plating | Gold over Nickel | Gold over Nickel |
| Contact Plating Spec. | MIL-G-45204 | MIL-G-45204 |
| Insulation Material | Oxide-Noryl | Oxide-Noryl |
| Outer Contact Material | | Passivated Stainless Steel |
| Outer Conductor Contact Spec. | | ASTM A380 |
| Body Material | Passivated Stainless Steel | |
| Body Plating Spec. | ASTM A380 | |
| Coupling Nut Material | Passivated Stainless Steel | |
| Coupling Nut Plating Spec. | ASTM A380 | |

Environmental Specifications

Temperature

Operating Range

-55 to +100 deg C

Vibration

MIL-STD 202, Method 204, Condition D (20 G's)

Salt Spray


MIL-STD 202, Method 101, Condition B, 5% salt solution

Compliance Certifications (see [product page](#) for current document)

Plotted and Other Data

Notes:

Typical Performance Data





3.5mm Male to 2.92mm Female Adapter from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Allen, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [3.5mm Male to 2.92mm Female Adapter SM3370](#)

URL: <https://www.fairviewmicrowave.com/3.5mm-male-2.92mm-female-adapter-sm3370-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.





| | | | | | |
|---|------------------|---|--------------------|--------|-----|
| FAIRVIEW MICROWAVE INC. ALLEN, TX 75013 WWW.FAIRVIEWMICROWAVE.COM | | NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. 3. DIMENSIONS ARE IN INCHES [mm]. | | | |
| TITLE 3.5mm Male to 2.92mm Female Adapter | DWG NO SM3370 | | CAGE CODE 3FKR5 | | |
| | CAD FILE 111715 | SHEET | SCALE N/A | SIZE A | 150 |