

## SMA Female to N Female Bulkhead Adapter

SMA female to type N female bulkhead adapter part number SM4239A from Fairview Microwave is in-stock and ships same day. This Fairview SMA to type N adapter has a female to female gender configuration. SM4239A SMA female to type N female adapter operates to 11 GHz. The SMA connector mates mechanically with commercially available 3.5mm and 2.92mm (K) connectors. Our RF SMA to type N bulkhead adapter allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications. The Fairview Microwave RF adapter provides good VSWR of 1.35:1 maximum.

RF adapters can be used to enable connections between two connector types that would otherwise not mate. Certain RF adapter configurations can also be used to protect connectors on expensive equipment where the number of connect and disconnect cycles is high. An RF, microwave, or millimeter wave adapter is connected to the equipment and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Fairview Microwave also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

### Electrical Specifications

| Description            | Min | Typ | Max    | Units |
|------------------------|-----|-----|--------|-------|
| Frequency Range        | DC  |     | 11     | GHz   |
| VSWR                   |     |     | 1.35:1 |       |
| Operating Voltage (AC) |     |     | 500    | Vrms  |

Electrical Specification Notes:  
 Values at 25°C, sea level.

### Mechanical Specifications

| Size   |                     |
|--------|---------------------|
| Length | 1.232 in [31.29 mm] |
| Width  | 0.78 in [19.81 mm]  |
| Weight | 0.082 lbs [37.19 g] |

| Description             | Connector 1  | Connector 2  |
|-------------------------|--------------|--------------|
| Type                    | SMA Female   | N Female     |
| Polarity                | Standard     | Standard     |
| Interface Specification | MIL-STD-348A | MIL-STD-348A |
| Mating Cycles           | 100          | 100          |



### Configuration:

- SMA Female Connector 1
- N Female Connector 2
- 50 Ohms
- Straight Body Geometry
- Bulkhead Mount Method

### Features:

- VSWR of 1.35:1 max up to 11 GHz
- SMA interface meets MIL-STD-348A
- N interface meets MIL-STD-348A
- Gold Plated Beryllium Copper Contact

### Applications:

- Enables Between Series Connections
- General Purpose Test
- Rack Mounted Equipment

Fairview Microwave  
 1130 Junction Dr. #100  
 Allen, TX 75013  
 Tel: 1-800-715-4396 / (972) 649-6678  
 Fax: (972) 649-6689  
[www.fairviewmicrowave.com](http://www.fairviewmicrowave.com)  
[sales@fairviewmicrowave.com](mailto:sales@fairviewmicrowave.com)

**Material Specifications**

| Description                 | Connector 1      | Connector 2      |
|-----------------------------|------------------|------------------|
| Type                        | SMA Female       | N Female         |
| Contact Material            | Beryllium Copper | Beryllium Copper |
| Contact Plating             | Gold             | Gold             |
| Insulation Material         | PTFE             | PTFE             |
| Outer Contact Material      | Brass            | Brass            |
| Outer Contact Plating       | Nickel           | Nickel           |
| Outer Contact Plating Spec. | 100 µin minimum  | 100 µin minimum  |

**Environmental Specifications**

**Temperature**

Operating Range


-65 to +165 deg C

**Compliance Certifications** (see [product page](#) for current document)

**Plotted and Other Data**

Notes:

**Typical Performance Data**




SMA Female to N Female Bulkhead Adapter from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Allen, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [SMA Female to N Female Bulkhead Adapter SM4239A](#)

URL: <https://www.fairviewmicrowave.com/sma-female-n-female-bulkhead-adapter-sm4239a-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.





|   |        |   |       |                    |            |
|---|--------|---|-------|--------------------|------------|
| <b>FAIRVIEW MICROWAVE INC.</b><br>ALLEN, TX 75013 WWW.FAIRVIEWMICROWAVE.COM |        | NOTES:<br>1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.<br>2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.<br>3. DIMENSIONS ARE IN INCHES [mm]. |       |                    |            |
| TITLE<br>SMA Female to N Female Bulkhead Adapter                            |        | DWG NO<br>SM4239A   |       | CAGE CODE<br>3FKR5 |            |
| CAD FILE  | 111115 | SHEET   | SCALE | N/A                | SIZE A 150 |